

Page 1/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier
· Trade name: <u>C090 2K PLASTICISER MATT</u>
 Article number: C090 1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet
 • 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: P.O. Box 7623 Beirut LEBANON info@hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559
 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41
SECTION 2: Hazarda idantification
SECTION 2: Hazards identification • 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 GHS02 flame
Flam. Liq. 3 H226 Flammable liquid and vapour.
GHS07
Skin Irrit. 2 H315 Causes skin irritation.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. (Contd. on page 2) GB



Page 2/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: C090 2K PLASTICISER MATT

	(Contd. of page 1)
2.2 Label el	lements
	ccording to Regulation (EC) No 1272/2008
	is classified and labelled according to the CLP regulation.
Hazard pict	
A	
	\mathbf{A}
< જ > <	
	\checkmark
GHS02 G	HS07
Signal word	d Warning
Hazard stat	•
	nable liquid and vapour.
	es skin irritation.
	ful to aquatic life with long lasting effects.
	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
. 2.10	No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
. =	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skir
	with water/shower.
P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.
Additional	information:
	s(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-
	nyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-, n-butyl acrylate, methyl methacrylate,
	acrylate. May produce an allergic reaction.
2.3 Other h	
	PBT and vPvB assessment
PBT: Not ap	
vPvB: Not a	

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB



Page 3/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: C090 2K PLASTICISER MATT

Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32	xylene	>25- <i>≤</i> 50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate � Flam. Liq. 3, H226; � STOT SE 3, H336	>10- <i>≤</i> 25%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene	>2.5- <i>≤</i> 10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%
CAS: 41556-26-7 Reg.nr.: 01-2119491304-40	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	<i>≤</i> 2.5%
CAS: 104810-47-1 ELINCS: 400-830-7 Reg.nr.: 01-0000015075-76-0017	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4- hydroxyphenyl)propionol-ohydroxypoly(oxyethylene); a-3-(3-(2h- Aquatic Chronic 2, H411; ① Skin Sens. 1, H317	<i>≤</i> 2.5%
CAS: 141-32-2 EINECS: 205-480-7 Reg.nr.: 01-2119453155	n-butyl acrylate Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<i>≤</i> 2.5%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<i>≤</i> 2.5%
CAS: 103-11-7 EINECS: 203-080-7 Reg.nr.: 01-2119453458-37	2-ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<i>≤</i> 2.5%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

After inhalation: In case of unconsciousness place patient stably in side position for transportation.
 After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

(Contd. of page 3)

Page 4/12

Trade name: C090 2K PLASTICISER MATT

- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling No special precautions are necessary if used correctly.

- Information about fire and explosion protection:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.

(Contd. on page 5)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: C090 2K PLASTICISER MATT

(Contd. of page 4)

Page 5/12

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

 Ingredients with limit values that require monitoring at the workplace: 		
1330-20-7 xylene		
WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV		
123-86-4 n-butyl acetate		
WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm		
100-41-4 ethylbenzene		
WEL Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk		
108-65-6 2-methoxy-1-methylethyl acetate		
WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk		
141-32-2 n-butyl acrylate		
WEL Short-term value: 26 mg/m³, 5 ppm Long-term value: 5 mg/m³, 1 ppm		
80-62-6 methyl methacrylate		
WEL Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm		
	(Contd. on page	





Page 6/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: C090 2K PLASTICISER MATT

		(Contd. of page 5)		
· Ingredi	ents with biological limit values:			
1330-20	1330-20-7 xylene			
	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid			
· Additio	nal information: The lists valid during the making were used as basis.			
 Person Genera Keep av Immedi Wash h Avoid c Avoid c Respira 	osure controls al protective equipment: al protective and hygienic measures: way from foodstuffs, beverages and feed. ately remove all soiled and contaminated clothing ands before breaks and at the end of work. ontact with the skin. ontact with the eyes and skin. atory protection: Not required. tion of hands:			
Mar I	Protective gloves			
Due to prepara	ve material has to be impermeable and resistant to the product/ the substance/ missing tests no recommendation to the glove material can be given for t tion/ the chemical mixture. on of the glove material on consideration of the penetration times, rates of o	the product/ the		

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

(Contd. of page 6)

Page 7/12

Trade name: C090 2K PLASTICISER MATT

· Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information	
Appearance:	
Form:	Liquid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	· 124 °C
Flash point:	27 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	1.032 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.



GB



Page 8/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: C090 2K PLASTICISER MATT

	(Contd. of pag	je 7
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	52.1 %	
VÕC (EC)	537.9 g/l	
Solids content:	46.8 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

(Contd. of page 8)

Page 9/12

Trade name: C090 2K PLASTICISER MATT

- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA

UN1263

(Contd. on page 10)





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Page 10/12

Trade name: C090 2K PLASTICISER MATT

· 14.2 UN proper shipping name	(Contd. of page 9
· ADR	1263 PAINT
· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
- Label	3
· 14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L October 51
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per niner packaging: 30 mi Maximum net quantity per outer packaging: 1000 m
Transport category	3
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
UN "Model Regulation":	UN 1263 PAINT, 3, III

(Contd. on page 11)



Page 11/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: C090 2K PLASTICISER MATT

(Contd. of page 10)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department
- · Contact: N/A
- Abbreviations and acronyms:
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

GB



Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: C090 2K PLASTICISER MATT

	(Contd. of page 11)
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Lig. 2: Flammable liguids – Category 2	
Flam. Lig. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Skin Sens. 1: Skin sensitisation – Category 1	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3	
······································	GB