

Page 1/11

٦

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier
· Trade name: <u>S620 ACCELERATOR</u>
 Article number: S620 CAS Number: 123-86-4 EC number: 204-658-1 Index number: 607-025-00-1 Registration number 01-2119485493-29 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. use as industrial paint Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet
 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: P.O. Box 7623 Beirut LEBANON info@hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559
 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41
SECTION 2: Hazards identification
2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame
Flam. Liq. 3 H226 Flammable liquid and vapour. (Contd. on page 2)



Page 2/11


Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S620 ACCELERATOR





Page 3/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S620 ACCELERATOR

(Contd. of page 2) P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P405

Store locked up.

Dispose of contents/container in accordance with local/regional/national/ international regulations.

· 2.3 Other hazards

P501

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.1 Chemical characterisation: Substances
- · CAS No. Description 123-86-4 n-butyl acetate
- Identification number(s)
- · EC number: 204-658-1
- · Index number: 607-025-00-1

· Dangerous components:

CAS: 77-58-7

dibutyltin dilaurate EINECS: 201-039-8 🔶 Acute Tox. 3, H301; 🕹 Muta. 2, H341; Repr. 1B, H360FD; STOT RE 1. H372

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eve contact: Rinse opened eve for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 4)

GB

*≤*2.5%



Page 4/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S620 ACCELERATOR

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
 Mount respiratory protective device.
 Wash protective equipment. Keep unprotected persons even.
- Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

(Contd. of page 4)

Page 5/11

Trade name: S620 ACCELERATOR

• Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

77-58-7 dibutyltin dilaurate

WEL Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³ as Sn; Sk

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Trade name: S620 ACCELERATOR

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information	
Appearance:	,,
Form:	Liquid
Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	5
Change in condition	
Melting point/freezing point:	-76 °C
Initial boiling point and boiling ra	ange: 124-128 °C
Flash point:	27 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosiv air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.88193 g/cm³
Relative density	Not determined.
Vapour density	Not determined.

Revision: 20.09.2019

(Contd. of page 5)

Page 6/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Page 7/11

Trade name: S620 ACCELERATOR

	(Contd. of pa	ge 6
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water at 20 °C:	5 g/l	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic at 20 °C:	0.7 mPas	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	98.8 %	
VÕC (EC)	871.3 g/l	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)
77-58-7 d	ibutyltin d	ilaurate
Oral	LD50	175 mg/kg (rat)
	rritant effe	

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Page 8/11

Trade name: S620 ACCELERATOR

- (Contd. of page 7) • **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity
- Suspected of causing genetic defects.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** May damage fertility. May damage the unborn child.
- **STOT-single exposure** May cause drowsiness or dizziness.
- · STOT-repeated exposure
- May cause damage to the immune system through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small guantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S620 ACCELERATOR

(Contd. of page 8)

Page 9/11

14.4 LINI Number	
14.1 UN-Number ADR, IMDG, IATA	UN1123
14.2 UN proper shipping name	
ADR	1123 BUTYL ACETATES solution
IMDG, IATA	BUTYL ACETATES solution
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	<i>III</i>
14.5 Environmental hazards:	
Marine pollutant:	No
•	
14.6 Special precautions for user Danger code (Kemler):	Warning: Flammable liquids. 30
EMS Number:	50 F-E,S-D
Stowage Category	A
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
-	Maximum net quantity per outer packaging: 1000 r
Transport category Tunnel restriction code	3 D/E
	ν/ Ε
	<i>E</i> 1
Limited quantities (LQ)	5L Code: E1
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 30 mi Maximum net quantity per outer packaging: 1000 r
	(Contd. on page -



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

(Contd. of page 9)

Page 10/11

Trade name: S620 ACCELERATOR

· UN "Model Regulation":

UN 1123 BUTYL ACETATES SOLUTION, 3, III

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I Substance is not listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20, 30
- · Regulation (EU) No 649/2012

77-58-7 dibutyltin dilaurate

Annex I Part 1

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed.

H341 Suspected of causing genetic defects.

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to the immune system through prolonged or repeated exposure.

· Department issuing SDS: Product safety department

· Contact: N/A

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

- International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 11)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S620 ACCELERATOR

(Contd. of page 10)

Page 11/11

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity – Category 3 Muta. 2: Germ cell mutagenicity – Category 2 Repr. 1B: Reproductive toxicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2



