Page 1/11

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 30.09.2019

# SECTION 1: Identification of the substance/mixture and of the company, undertaking

- · 1.1 Product identifier
- · Trade name: CO60R ULTRA GLOSS HS CLEARCOAT
- · Article number: C060R
- · UFI: MT23-80DY-900C-DUG3
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available. use as industrial paint
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- Product category
   PC9a Coatings and paints, thinners, paint removers
   PC9b Fillers, putties, plasters, modelling clay
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: P.O. Box 7623 Beirut LEBANON info@hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France
- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number: +33 (0)1 60 86 77 65

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

GHS02	2 flame	
Flam. Liq. 3	H226 Flammable liquid and vapour.	
GHS07		
STOT SE 3	H336 May cause drowsiness or dizziness.	
Aquatic Chronic	3 H412 Harmful to aquatic life with long lasting effects.	
	ents rding to Regulation (EC) No 1272/2008 lassified and labelled according to the CLP regulation.	(Contd. on page 2)

Page 2/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 30.09.2019

(Contd. of page 1)

### Trade name: C060R ULTRA GLOSS HS CLEARCOAT

· Hazard pictograms

GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

n-butyl acetate

### · Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.
- · Additional information:

Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, methyl methacrylate, 2,3-epoxypropyl neodecanoate, s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-, 2-hydroxyethyl methacrylate, methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate. May produce an allergic reaction.

2.3 Other hazards

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

<ul> <li>Dangerous components:</li> </ul>		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate � Flam. Liq. 3, H226; � STOT SE 3, H336	>25- <i>≤</i> 50%
	(C	ontd. on page 3)

Printing date 11.03.2021

HYMA

Revision: 30.09.2019

### Trade name: C060R ULTRA GLOSS HS CLEARCOAT

CAS: 108-65-6	2-methoxy-1-methylethyl acetate	ontd. of page 2 >2.5-≤10%
EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56	🚸 Flam. Liq. 3, H226	
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32	xylene	>2.5- <i>≤</i> 10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	Solvent naphtha (petroleum), light arom. � Acute Tox. 4, H332; STOT SE 3, H335	>2.5- <i>≤</i> 10%
CAS: 41556-26-7 Reg.nr.: 01-2119491304-40	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	<i>≤</i> 2.5%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate	<i>≤</i> 2.5%
CAS: 26761-45-5 EINECS: 247-979-2 Reg.nr.: 01-2119431597-33	2,3-epoxypropyl neodecanoate Acute Tox. 3, H331;	<i>≤</i> 2.5%
CAS: 104810-47-1 ELINCS: 400-830-7 Reg.nr.: 01-0000015075-76-0017	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl) propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h- Aquatic Chronic 2, H411;	<i>≤</i> 2.5%
CAS: 868-77-9 EINECS: 212-782-2 Reg.nr.: 01-2119490169-29	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	<i>≤</i> 2.5%
CAS: 82919-37-7	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	<i>≤</i> 2.5%

### SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

GB

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 30.09.2019

(Contd. of page 3)

Page 4/11

### Trade name: C060R ULTRA GLOSS HS CLEARCOAT

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
   6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

# SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 5)

GB

### Page 5/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 30.09.2019

### Trade name: C060R ULTRA GLOSS HS CLEARCOAT

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

HYMA

· Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

	36-4 n-butyl acetate Short-term value: 966 mg/m³, 200 ppm	
	Long-term value: 724 mg/m <sup>3</sup> , 150 ppm	
108-6	55-6 2-methoxy-1-methylethyl acetate	
NEL	Short-term value: 548 mg/m³, 100 ppm	
	Long-term value: 274 mg/m <sup>3</sup> , 50 ppm	
	Sk	
1330	-20-7 xylene	
NEL	Short-term value: 441 mg/m³, 100 ppm	
	Long-term value: 220 mg/m <sup>3</sup> , 50 ppm	
	Sk; BMGV	
30-62	2-6 methyl methacrylate	
NEL	Short-term value: 416 mg/m³, 100 ppm	
	Long-term value: 208 mg/m³, 50 ppm	
ngre	dients with biological limit values:	
1330	-20-7 xylene	
ЗMG	V 650 mmol/mol creatinine	
	Medium: urine	
	Sampling time: post shift	
	Parameter: methyl hippuric acid	
Addi	tional information: The lists valid during the making were used as basis.	
3.2 E	xposure controls	
	onal protective equipment:	

Wash hands before breaks and at the end of work.

(Contd. on page 6)

GB

Page 6/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 30.09.2019

(Contd. of page 5)

### Trade name: C060R ULTRA GLOSS HS CLEARCOAT

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. • Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### · Eye protection:



Tightly sealed goggles

9.1 Information on basic physical a General Information	nd chemical properties	
Appearance:		
Form:	Liquid	
Colour:	Clear	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point: Initial boiling point and boiling ra	Undetermined. <b>nge:</b> 124 °C	
Flash point:	25 °C	

Page 7/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 30.09.2019

### Trade name: C060R ULTRA GLOSS HS CLEARCOAT

	(Contd. of page 6	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	315 °C	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive. However, formation of explosiv air/vapour mixtures are possible.	
· Explosion limits:		
Lower:	1.2 Vol %	
Upper:	7.5 Vol %	
· Vapour pressure at 20 °C:	10.7 hPa	
· Density at 20 °C:	0.985 g/cm <sup>3</sup>	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	46.0 %	
VOC (EC)	453.2 g/l	
Solids content:	52.5 %	
· 9.2 Other information	No further relevant information available.	

### SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 8)

GB

Printing date 11.03.2021

Revision: 30.09.2019

### Trade name: C060R ULTRA GLOSS HS CLEARCOAT

(Contd. of page 7) · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

### 1330-20-7 xylene

Oral

Dermal

LD50 4,300 mg/kg (rat) LD50

2,000 mg/kg (rabbit)

### 64742-95-6 Solvent naphtha (petroleum), light arom.

>6,800 mg/kg (rat) Oral LD50 Dermal

LD50 >3,400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

· Primarv irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · **12.4 Mobility in soil** No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

(Contd. on page 9)

Printing date 11.03.2021

Revision: 30.09.2019

### Trade name: C060R ULTRA GLOSS HS CLEARCOAT

· 12.5 Results of PBT and vPvB assessment

• PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

#### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

#### SECTION 14: Transport information · 14.1 UN-Number · ADR, IMDG, IATA UN1263 · 14.2 UN proper shipping name · ADR 1263 PAINT PAINT · IMDG, IATA · 14.3 Transport hazard class(es) · ADR, IMDG, IATA · Class 3 Flammable liquids. · Label 3 · 14.4 Packing group ||| · ADR, IMDG, IATA · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 30 · EMS Number: F-E,S-E · Stowage Category Α · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. (Contd. on page 10) GB

(Contd. of page 8)

Page 9/11

Printing date 11.03.2021

Revision: 30.09.2019

### Trade name: C060R ULTRA GLOSS HS CLEARCOAT

(Contd. of page 9)
5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
3
D/E
5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
UN 1263 PAINT, 3, III

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

(Contd. on page 11)

GB

Printing date 11.03.2021

Revision: 30.09.2019

#### Trade name: C060R ULTRA GLOSS HS CLEARCOAT

(Contd. of page 10) H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. · Department issuing SDS: Product safety department · Contact: N/A Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - dermal – Category 4 Acute Tox. 3: Acute toxicity - inhalation – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3