Printing date 08.01.2021

Revision: 20.08.2020

# SECTION 1: Identification of the substance/mixture and of the company, undertaking

- · 1.1 Product identifier
- · Trade name: C076 HYFLASH AIR-DRY VOC CLEAR
- · Article number: C076
- · UFI: XS74-A0M9-M00Q-JVN4
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available. use as industrial paint
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- Product category
   PC9a Coatings and paints, thinners, paint removers
   PC9b Fillers, putties, plasters, modelling clay
   Application of the substance (the mixture refer to the relevant Technical Data Silvert)
- Application of the substance / the mixture refer to the relevant Technical Data Sheet
- $\cdot$  1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Générale de Peinture,
   70 Rue Cortambert 75116 Paris, France info@hymax.biz
- · Further information obtainable from: Product Safety Department
- 1.4 Emergency telephone number: +33 (0)1 60 86 77 65

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008
 GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

С Снѕот

Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### · 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Page 2/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.01.2021

Revision: 20.08.2020

### Trade name: C076 HYFLASH AIR-DRY VOC CLEAR

Hazard pict	tograms
$\wedge$	$\wedge$
<**>><	
GHS02 G	HS07
Signal word	d Warning
Hazard-det	ermining components of labelling:
n-butyl acet	
	penzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-
(2h-	
	6-pentamethyl-4-piperidyl) sebacate
Hazard stat	nable liquid and vapour.
	ause an allergic skin reaction.
	ause drowsiness or dizziness.
	ful to aquatic life with long lasting effects.
Precaution	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sourc No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse s
	with water [or shower].
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/nation international regulations.
	azards

· vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

<ul> <li>Dangerous components:</li> </ul>		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate 🚸 Flam. Liq. 3, H226; 🐠 STOT SE 3, H336	>25- <i>≤</i> 50%
		Contd. on page 3

GB

Printing date 08.01.2021

Revision: 20.08.2020

Page 3/11

#### Trade name: C076 HYFLASH AIR-DRY VOC CLEAR

CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%	
EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	♦ Acute Tox. 4, H332; STOT SE 3, H335		
CAS: 1330-20-7	xylene	>2.5- <i>≤</i> 10%	
EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32	Flam. Liq. 3, H226;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315		
CAS: 104810-47-1 ELINCS: 400-830-7	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl) propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	<i>≤</i> 2.5%	
Reg.nr.: 01-0000015075-76-0017	🗞 Aquatic Chronic 2, H411; ၇ Skin Sens. 1, H317		
CAS: 763-69-9	ethyl 3-ethoxypropionate	<i>≤</i> 2.5%	
EINECS: 212-112-9	♦ Flam. Liq. 3, H226; ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319		
CAS: 41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	<i>≤</i> 2.5%	
Reg.nr.: 01-2119491304-40	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317		
CAS: 77-58-7	dibutyltin dilaurate	<i>≤</i> 2.5%	
EINECS: 201-039-8	♦ Acute Tox. 3, H301; ♦ Muta. 2, H341; Repr. 1B, H360FD; STOT RE 1, H372		

Additional information: For the wording of the listed hazard phrases refer to section 16.

# SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 4)

Printing date 08.01.2021

Revision: 20.08.2020

#### Trade name: C076 HYFLASH AIR-DRY VOC CLEAR

(Contd. of page 3)

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available. • 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

#### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

(Contd. on page 5)

<sup>-</sup> GB

Printing date 08.01.2021

#### Trade name: C076 HYFLASH AIR-DRY VOC CLEAR

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

#### 1330-20-7 xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm Long-term value: 220 mg/m<sup>3</sup>, 50 ppm Sk; BMGV

77-58-7 dibutyltin dilaurate

WEL Short-term value: 0.2 mg/m<sup>3</sup> Long-term value: 0.1 mg/m<sup>3</sup> as Sn; Sk

#### · Ingredients with biological limit values:

#### 1330-20-7 xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

• Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

### Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. (Contd. on page 6)

(Contd. of page 4)

Revision: 20.08.2020

Printing date 08.01.2021

Revision: 20.08.2020

#### Trade name: C076 HYFLASH AIR-DRY VOC CLEAR

(Contd. of page 5) Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation
• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

# • **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

#### SECTION 9: Physical and chemical properties · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Colour: Clear · Odour: Characteristic · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition *Melting point/freezing point:* Undetermined. Initial boiling point and boiling range: 127 °C · Flash point: 24 °C · Flammability (solid, gas): Not applicable. 370 °C · Ignition temperature: · Decomposition temperature: Not determined. · Auto-ignition temperature: Product is not selfigniting. Product is not explosive. However, formation of explosive · Explosive properties: air/vapour mixtures are possible. (Contd. on page 7)

– GB

Page 7/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.01.2021

Revision: 20.08.2020

#### Trade name: C076 HYFLASH AIR-DRY VOC CLEAR

	(Co	ntd. of page 6
· Explosion limits:		
Lower:	1 Vol %	
Upper:	7.5 Vol %	
· Vapour pressure at 20 °C:	10.7 hPa	
· Density at 20 °C:	0.997 g/cm³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	43.7 %	
VÕC (EC)	435.4 g/l	
Solids content:	53.4 %	
· 9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)

(Contd. on page 8)

Printing date 08.01.2021

HYMA

Revision: 20.08.2020

#### Trade name: C076 HYFLASH AIR-DRY VOC CLEAR

		(Contd. of page
		>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
77-58-7 di	butyltin d	ilaurate
Oral	LD50	175 mg/kg (rat)
Primary in		
		ation Based on available data, the classification criteria are not met.
		e/irritation Based on available data, the classification criteria are not met. sensitisation
		ic skin reaction.
		ogenity, mutagenicity and toxicity for reproduction)
		icity Based on available data, the classification criteria are not met.
		sed on available data, the classification criteria are not met.
Reproduc STOT-sing		ity Based on available data, the classification criteria are not met.
		ss or dizziness.
		osure Based on available data, the classification criteria are not met.
Aspiration	n <mark>hazard</mark> E	Based on available data, the classification criteria are not met.
Aquatic to	oxicity: No	o further relevant information available.
12.2 Persi 12.3 Bioad 12.4 Mobil Ecotoxica Remark: H Additional General no Water haza Do not allo Danger to Harmful to 12.5 Resu PBT: Not a	oxicity: No istence and ccumulati lity in soil of effects: Harmful to I ecologic otes: ard class 2 ow product drinking w aquatic ou Its of PB1 applicable.	nd degradability No further relevant information available. ve potential No further relevant information available. 'No further relevant information available. fish ral information: ? (German Regulation) (Self-assessment): hazardous for water to reach ground water, water course or sewage system. rater if even small quantities leak into the ground. rganisms T and vPvB assessment
Aquatic to 12.2 Persi 12.3 Bioad 12.4 Mobil Ecotoxica Remark: H Additional General no Water haza Do not allo Danger to Harmful to 12.5 Resu PBT: Not a vPvB: Not 12.6 Other	oxicity: No istence an ccumulati lity in soil of effects: Harmful to I ecologic otes: ard class 2 ow product drinking w aquatic of its of PB1 applicable. applicable r adverse	nd degradability No further relevant information available. ve potential No further relevant information available. 'No further relevant information available. fish ral information: ? (German Regulation) (Self-assessment): hazardous for water to reach ground water, water course or sewage system. rater if even small quantities leak into the ground. rganisms T and vPvB assessment

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. (Contd. on page 9)

Printing date 08.01.2021

Revision: 20.08.2020

## Trade name: C076 HYFLASH AIR-DRY VOC CLEAR

Uncleaned packaging:
 Recommendation: Disposal must be made according to official regulations.

• 14.1 UN-Number • ADR, IMDG, IATA	UN1263
• 14.2 UN proper shipping name • ADR • IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	///
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
14.7 Transport in bulk according to Annex II c Marpol and the IBC Code	of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r
Transport category Tunnel restriction code	3 D/E

(Contd. of page 8)

Page 9/11

Page 10/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.01.2021

Revision: 20.08.2020

#### Trade name: C076 HYFLASH AIR-DRY VOC CLEAR

(Contd. of page 9)

· IMDG
--------

Limited quantities (LQ)
 Excepted quantities (EQ)

5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III

#### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20

· Regulation (EU) No 649/2012

77-58-7 dibutyltin dilaurate

Annex I Part 1

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.

(Contd. on page 11)

GB

GB

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.01.2021

Revision: 20.08.2020

#### Trade name: C076 HYFLASH AIR-DRY VOC CLEAR

(Contd. of page 10) H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. · Department issuing SDS: Product safety department · Contact: N/A Abbreviations and acronvms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity - oral – Category 3 Acute Tox. 4: Acute toxicity - inhalation – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Muta. 2: Germ cell mutagenicity - Category 2 Repr. 1B: Reproductive toxicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3