Page 1/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.05.2020

Revision: 30.09.2019

## SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: HO82 2K L.E. HARDENER FAST
- · Article number: HO82
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint
- Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: General Paint Co. S.A.L. -Safety Department-For further information, please consult our Internet site www.generalpaint.biz

· Further information obtainable from: Product Safety Department

• 1.4 Emergency telephone number: Phone : +33 (0)1 60 86 77 65

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



GHS02 flame

H226 Flammable liquid and vapour. Flam. Liq. 3

GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled.

(Contd. on page 2)

## Page 2/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.05.2020

Revision: 30.09.2019

(Contd. on page 3)

GB

## Trade name: HO82 2K L.E. HARDENER FAST

	(Contd. of page 1)
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H335 May cause respiratory irritation.
	cording to Regulation (EC) No 1272/2008 is classified and labelled according to the CLP regulation.
$\langle \rangle$	
GHS02 GH	IS07 GHS08
Signal word	Danger
Homopolyme Isophorone I 2-Heptanone xylene hexamethyle <b>Hazard state</b> H226	ne-di-isocyanate e <b>ments</b> Flammable liquid and vapour.
	Harmful in contact with skin or if inhaled. Causes skin irritation.
	Causes skin initiation. Causes serious eye irritation.
	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	May cause respiratory irritation.
	ry statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
	P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skir with water [or shower].
	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
2.3 Other ha	
	BT and vPvB assessment
PBT: Not app	
ap	(Contd. on page 3)

Printing date 07.05.2020

Revision: 30.09.2019

(Contd. of page 2)

#### Trade name: HO82 2K L.E. HARDENER FAST

#### · vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

#### · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 28182-81-2	Homopolymer of hexamethylene diisocyanate	>50-≤100%	
Reg.nr.: 01-2119485796-17	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335		
CAS: 110-43-0	2-Heptanone	>10- <i>≤</i> 25%	
EINECS: 203-767-1 Reg.nr.: 01-2119902391-49-0000	� Flam. Liq. 3, H226; � Acute Tox. 4, H302; Acute Tox. 4, H332		
CAS: 123-86-4	n-butyl acetate	>10- <i>≤</i> 25%	
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	🚸 Flam. Liq. 3, H226; <b>()</b> STOT SE 3, H336		
CAS: 1330-20-7	xylene	>2.5- <i>≤</i> 10%	
EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32	Flam. Liq. 3, H226;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315		
CAS: 53880-05-0	Isophorone Diisocyanate homopolymer	>2.5- <i>≤</i> 10%	
Reg.nr.: 01-2119488734-24	Resp. Sens. 1, H334; () Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335		
CAS: 822-06-0	hexamethylene-di-isocyanate	<i>≤</i> 2.5%	
EINECS: 212-485-8	發 Acute Tox. 3, H311; Acute Tox. 3, H331; 🚸 Resp.		
Reg.nr.: 01-2119457571-37	Sens. 1, H334; () Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335		

#### **on:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

GB

HYMA

Page 3/11

Printing date 07.05.2020

Revision: 30.09.2019

(Contd. of page 3)

#### Trade name: HO82 2K L.E. HARDENER FAST

· After eye contact:

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 5)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.05.2020

Revision: 30.09.2019

#### Trade name: HO82 2K L.E. HARDENER FAST

(Contd. of page 4)

Page 5/11

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

-	dients with limit values that require monitoring at the workplace: 3-0 2-Heptanone	
	Short-term value: 475 mg/m³, 100 ppm Long-term value: 237 mg/m³, 50 ppm Sk	
123-8	6-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
1330-	20-7 xylene	
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV	
822-0	6-0 hexamethylene-di-isocyanate	
WEL	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO	
Ingre	dients with biological limit values:	
1330-	20-7 xylene	
BMG	/ 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid	
822-0	6-0 hexamethylene-di-isocyanate	
BMG	/ 1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine	
Addie	ional information: The lists valid during the making were used as basis.	

HYMA

Printing date 07.05.2020

Revision: 30.09.2019

#### Trade name: HO82 2K L.E. HARDENER FAST

(Contd. of page 5)

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- **Respiratory protection:** In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

SECTION 9: P	hysical and	chemical	properties
--------------	-------------	----------	------------

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:	Fluid
Colour:	According to product description
· Odour:	Characteristic

(Contd. on page 7)

GB

Printing date 07.05.2020

HYMAX

Revision: 30.09.2019

Page 7/11

## Trade name: HO82 2K L.E. HARDENER FAST

	(Contd. of page 6)
· Odour threshold:	Not determined.
· pH-value:	Not determined.
<ul> <li>Change in condition</li> <li>Melting point/freezing point:</li> <li>Initial boiling point and boiling range</li> </ul>	Undetermined. a: 124 °C
· Flash point:	25 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<ul> <li>Explosion limits: Lower: Upper:</li> </ul>	1 Vol % 7.5 Vol %
<ul> <li>Vapour pressure at 20 °C:</li> </ul>	10.7 hPa
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	1.008 g/cm <sup>3</sup> Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic:</li> </ul>	Not determined. Not determined.
<ul> <li>Solvent content: Organic solvents: VOC (EC)</li> </ul>	38.6 % 389.4 g/l
Solids content: • 9.2 Other information	61.8 % No further relevant information available.

## SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 8)

GB –

## Page 8/11

## Safety data sheet according to 1907/2006/EC, Article 31

*Printing date 07.05.2020* 

Revision: 30.09.2019

(Contd. of page 7)

#### Trade name: HO82 2K L.E. HARDENER FAST

- · 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5** Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- Harmful in contact with skin or if inhaled.
- · LD/LC50 values relevant for classification:

#### 1330-20-7 xylene

- Oral LD50 4,300 mg/kg (rat)
- Dermal LD50 2,000 mg/kg (rabbit)
- Primary irritant effect:
- Skin corrosion/irritation
- Causes skin irritation. • Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause respiratory irritation.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

## · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 9)

## Page 9/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.05.2020

HYMA

Revision: 30.09.2019

(Contd. of page 8)

#### Trade name: HO82 2K L.E. HARDENER FAST

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT	
14.3 Transport hazard class(es)		
ADR, IMDG, IATA		
Class Label	3 Flammable liquids. 3	
14.4 Packing group ADR, IMDG, IATA	III	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A	

Printing date 07.05.2020

Revision: 30.09.2019

#### Trade name: HO82 2K L.E. HARDENER FAST

14.7 Transport in bulk apparding to An	(Contd. of page s
<ul> <li>14.7 Transport in bulk according to Anr Marpol and the IBC Code</li> </ul>	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 m
· Transport category	3
· Tunnel restriction code	D/E
·IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 m
· UN "Model Regulation":	UN 1263 PAINT, 3, III

#### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed. H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 11)

<sup>–</sup> GB

GB

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.05.2020

HYMA

Revision: 30.09.2019

#### Trade name: HO82 2K L.E. HARDENER FAST

(Contd. of page 10) H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. · Department issuing SDS: Product safety department · Contact: N/A Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 3: Acute toxicity - dermal – Category 3 Acute Tox. 4: Acute toxicity - dermal – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3