



Printing date 24.09.2019 Revision: 06.05.2019

## SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: B450 OXIDE RED
- · Article number: B450
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC9a Coatings and paints, thinners, paint removers

PC9b Fillers, putties, plasters, modelling clay

- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

P.O. Box 7623

Beirut LEBANON

info@hymax.biz

Générale de Peinture, 70 Rue Cortambert 75116 Paris, France

Tel:+33(0)175293559

- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number: +33 (0)6 07 87 13 41

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Page 2/11

(Contd. of page 1)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 06.05.2019

Trade name: B450 OXIDE RED

· Hazard pictograms





GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

n-butyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Page 3/11



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 06.05.2019

Trade name: B450 OXIDE RED

· Dangerous components:	(6	Contd. of page 2
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate  Plam. Liq. 3, H226; STOT SE 3, H336	>25- <i>≤</i> 50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32	xylene  Tam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	>2.5-≤10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56	2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226	>2.5-≤10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	Solvent naphtha (petroleum), light arom.  Output  Description  Output  D	>2.5-≤10%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 4)



Page 4/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 06.05.2019

Trade name: B450 OXIDE RED

(Contd. of page 3)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5)





Printing date 24.09.2019 Revision: 06.05.2019

Trade name: B450 OXIDE RED

(Contd. of page 4)

#### · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

#### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

#### 1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm

Long-term value: 274 mg/m³, 50 ppm

#### · Ingredients with biological limit values:

#### 1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 6)





Printing date 24.09.2019 Revision: 06.05.2019

Trade name: B450 OXIDE RED

(Contd. of page 5)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

· Explosion limits: Lower:

· Density at 20 °C:

· Vapour pressure at 20 °C:

Upper:



Tightly sealed goggles

SECTION 9: Phy	⁄sical and	chemical	properties
----------------	------------	----------	------------

•			
9.1 Information on basic physical ar     General Information	9.1 Information on basic physical and chemical properties		
· Appearance:			
Form:	Liquid		
Colour:	Red		
· Odour:	Characteristic		
· Odour threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition Melting point/freezing point: Initial boiling point and boiling rar	Undetermined. nge: 124°C		
· Flash point:	27 °C		
· Flammability (solid, gas):	Not applicable.		
· Ignition temperature:	315 °C		
· Decomposition temperature:	Not determined.		
· Auto-ignition temperature:	Product is not selfigniting.		
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.		

1.2 Vol % 7.5 Vol %

10.7 hPa

1.04 g/cm<sup>3</sup>

(Contd. on page 7)





Printing date 24.09.2019 Revision: 06.05.2019

Trade name: B450 OXIDE RED

	(Contd. of pag
· Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	70.1 %
VOC (EC)	728.8 g/l
Solids content:	29.9 %
· 9.2 Other information	No further relevant information available.

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:			
1330-20-7	1330-20-7 xylene			
Oral	LD50	4,300 mg/kg (rat)		
Dermal	LD50	2,000 mg/kg (rabbit)		
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.			
Oral	LD50	>6,800 mg/kg (rat)		
Dermal	LD50	>3,400 mg/kg (rab)		

(Contd. on page 8)



Page 8/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 06.05.2019

Trade name: B450 OXIDE RED

(Contd. of page 7)

### Inhalative LC50/4 h >10.2 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.





Printing date 24.09.2019 Revision: 06.05.2019

Trade name: B450 OXIDE RED

(Contd. of page 8)

ADR, IMDG, IATA  14.2 UN proper shipping name ADR IMDG, IATA  14.3 Transport hazard class(es)  ADR  Class  IMDG, IATA  Class  IMDG, IATA   Class  3 Flammable liquids.  IMDG, IATA  Class  14.4 Packing group ADR, IMDG, IATA  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user EMS Number: Stowage Category  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code  Transport/Additional information: ADR Limited quantities (LQ)  5 L	SECTION 14: Transport information	on
1.4.2 UN proper shipping name ADR IMDG, IATA  1.4.3 Transport hazard class(es)  ADR  Class  IMDG, IATA  Class  3 Flammable liquids.  IMDG, IATA  Class  3 Flammable liquids.  1.4.4 Packing group ADR, IMDG, IATA  III  1.5 Environmental hazards: Marine pollutant: No  1.4.6 Special precautions for user EMS Number: Stowage Category  1.4.7 Transport in bulk according to Annex II of Marpol and the IBC Code  Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  Excepted quantities (EQ)  1.6 Special precautions for user EMS Number: Stowage Category  A  SL  Code: E1  Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 30 ml Maximum net quantity per inner packaging: 30 ml	· 14.1 UN-Number	11114060
ADR 1263 PAINT   IMDG, IATA	<u> </u>	UN 1263
IMDG, IATA  14.3 Transport hazard class(es)  ADR  Class 3 Flammable liquids.  IMDG, IATA  Class 3 Flammable liquids.  Class 3 Flammable liquids.  14.4 Packing group ADR, IMDG, IATA  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user EMS Number: F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  EXCEPTION A  A SIMMATINITY OF AIM TO A SIMMATINITY OF AIM TO AIM		40.00 DAILIT
ADR  Class 3 Flammable liquids.  IMDG, IATA  Class 3 Flammable liquids.  Class 3 Flammable liquids.  Class 3 Flammable liquids.  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user EMS Number: Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
Class 3 Flammable liquids.  IMDG, IATA  Class 3 Flammable liquids.  Class 3 Flammable liquids. 3  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user EMS Number: Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) 5L Excepted quantities (EQ) 5L Excepted quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· IMDG, IATA	PAINI
Class 3 Flammable liquids.  IMDG, IATA  Class 3 Flammable liquids.  Label 3  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user EMS Number: F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· 14.3 Transport hazard class(es)	
IMDG, IATA  Class 3 Flammable liquids. 3  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user EMS Number: F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· ADR	
IMDG, IATA  Class 3 Flammable liquids. 14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user EMS Number: F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  5L Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
Class Label 3  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user EMS Number: F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  SI Hammable liquids. P-E,S-E Not applicable.  Toda:  SI Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	Class	3 Flammable liquids.
Class Label 3  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user EMS Number: F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  SI Hammable liquids. P-E,S-E Not applicable.  Today:  SI Hammable liquids. No  Warning: Flammable liquids. P-E,S-E Not applicable.  Today:  Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· IMDG. IATA	
Label 3  14.4 Packing group ADR, IMDG, IATA III  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user EMS Number: F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000		
ADR, IMDG, IATA  14.5 Environmental hazards: Marine pollutant: No  14.6 Special precautions for user EMS Number: Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· Class · Label	
Marine pollutant:  14.6 Special precautions for user EMS Number: Stowage Category  A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code  Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  SL  Code: E1  Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· 14.4 Packing group · ADR, IMDG, IATA	III
EMS Number: F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· 14.5 Environmental hazards: · Marine pollutant:	No
EMS Number: F-E,S-E Stowage Category A  14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· 14.6 Special precautions for user	Warning: Flammable liquids.
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.  Transport/Additional information:  ADR Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	EMS Number:	
Marpol and the IBC Code  Not applicable.  Transport/Additional information:  ADR  Limited quantities (LQ)  Excepted quantities (EQ)  Code: E1  Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· Stowage Category	A
Transport/Additional information:  ADR Limited quantities (LQ) Excepted quantities (EQ)  SL Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	· 14.7 Transport in bulk according to Anne Marpol and the IBC Code	
Limited quantities (LQ)  Excepted quantities (EQ)  Code: E1  Maximum net quantity per inner packaging: 30 ml  Maximum net quantity per outer packaging: 1000	Transport/Additional information:	
Limited quantities (LQ)  Excepted quantities (EQ)  Code: E1  Maximum net quantity per inner packaging: 30 ml  Maximum net quantity per outer packaging: 1000	· ADR	
Excepted quantities (EQ)  Code: E1  Maximum net quantity per inner packaging: 30 ml  Maximum net quantity per outer packaging: 1000		5L
Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000	Excepted quantities (EQ)	
	- ,	Maximum net quantity per inner packaging: 30 ml
Transport category 3	_	, , , , , , ,
	· Transport category	3



Page 10/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 06.05.2019

Trade name: B450 OXIDE RED

(	Cor	nta.	ΟŢ	page	9)

	(Comai or page o)		
· Tunnel restriction code	D/E		
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml		
· UN "Model Regulation":	UN 1263 PAINT, 3, III		

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a quarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 11)



Page 11/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 06.05.2019

Trade name: B450 OXIDE RED

(Contd. of page 10)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3