

Page 1/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

| <ul> <li>SECTION 1: Identification of the substance/mixture and of the company undertaking</li> <li>1.1 Product identifier</li> <li>Trade name: <u>B500 PURE MAROON</u></li> <li>Article number: <u>B500</u></li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint</li> <li>Sector of Use</li> <li>SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)</li> <li>Product category</li> <li>PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay</li> <li>Application of the substance / the mixture refer to the relevant Technical Data Sheet</li> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier:</li> <li>P.O. Box 7623</li> <li>Beirut LEBANON</li> <li>info@mymax.biz</li> <li>Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel-1-33(0)175293559</li> <li>Further information obtainable from: Product Safety Department</li> <li>1.4 Emergency telephone number: +33 (0)6 07 87 13 41</li> </ul> SECTION 2: Hazards Identification (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. 2.1 Classification according to Regulation (EC) No 1272/2008 STOT SE 3 H336 May cause drowsiness or dizziness. 2.2 Label elements Labeling according to Regulation (EC) No 1272/2008 Tort SE 3 H336 May cause drowsiness or dizziness. 2.2 Label elements Labeling according to Regulation (EC) No 1272/2008 Tort SE 3 H336 May cause drowsiness or dizziness. (Cent. on page 2) (Cent. on page 2) (Cent. on page 2)  |  |
|--|--|
| <ul> <li>Trade name: <u>B560 PURE MAROON</u></li> <li>Article number: <u>B560</u></li> <li><b>1.2</b> Relevant identified uses of the substance or mixture and uses advised against use as industrial paint</li> <li>Sector of Use</li> <li>SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites</li> <li>SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)</li> <li>Product category</li> <li>PC9a Coatings and paints, thinners, paint removers</li> <li>PC9b Fillers, putties, plasters, modelling clay</li> <li>Application of the substance / the mixture refer to the relevant Technical Data Sheet</li> <li><b>1.3</b> Details of the substance / the mixture refer to the relevant Technical Data Sheet</li> <li><b>1.3</b> Details of the substance / the mixture refer to the relevant Technical Data Sheet</li> <li><b>1.3</b> Details of the substance from: Product Safety Department</li> <li><b>1.4</b> Emergency telephone number: +33 (0)6 07 87 13 41</li> </ul> SECTION 2: Hazerds identification <b>EVALUATION</b> (For a substance or mixture <b>Classification according to Regulation (EC) No 1272/2008 Course of the Substance or disziness. Course of the Substance or disziness. Course of the Substance or CCO No 1272/2008 Term</b> E and May cause drowsiness or disziness. <b>Course of the Same of Same Society of CO No 1272/2008 Tor SE 3</b> H336 May cause drowsiness or disziness. <b>Course of Same Society of Same Society of CO No 1272/2008 Tor SE 3</b> H336 May cause drowsiness or disziness. <b>Course of Same Society of Regulation (EC) No 1272/2008 Tor SE 3</b> H336 May cause drowsiness or disziness. <b>Course or Same Society of Same Society of Color 1272/2008 Tor SE 3</b> H336 May cause drowsiness or disziness. <b>Course or Same Society of S</b> |  |
| <ul> <li>Article number: B560</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint</li> <li>Sector of Use</li> <li>SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites</li> <li>SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)</li> <li>Product category</li> <li>PC96 Coatings and paints, thinners, paint removers</li> <li>PC96 Fillers, putties, plasters, modelling clay</li> <li>Application of the substance / the mixture refer to the relevant Technical Data Sheet</li> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier:</li> <li>P.O. Box 7623</li> <li>Beirul LEBANON</li> <li>info@hymax.biz</li> <li>Générale de Peinture, 70 Rue Contambert 75116 Paris, France</li> <li>Tel.+33(0)175293559</li> <li>Further information obtainable from: Product Safety Department</li> <li>1.4 Emergency telephone number: +33 (0)6 07 87 13 41</li> </ul> SECTION 2: Hazards identification Elassification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 STOT SE 3 H336 May cause drowsiness or dizziness. 22 Label elements <ul> <li>Labelling according to Regulation (EC) No 1272/2008</li> <li>The product is classified and labelled according to the CLP regulation.</li> </ul>  | · 1.1 Product identifier   |
| <ul> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint</li> <li>Sector of USe</li> <li>SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites</li> <li>SU2 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)</li> <li>Product category</li> <li>PC96 Coatings and paints, thinners, paint removers</li> <li>PC9b Fillers, putties, plasters, modelling clay</li> <li>Application of the substance / the mixture refer to the relevant Technical Data Sheet</li> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier:</li> <li>P.O. Box 7623</li> <li>Beirut LEBANON</li> <li>into @hymax.biz</li> <li>Générale de Peinture, 70 Rue Cortambert 75116 Paris, France</li> <li>Tel:+33(0)175293559</li> <li>Further information obtainable from: Product Safety Department</li> <li>1.4 Emergency telephone number: +33 (0)6 07 87 13 41</li> </ul> SECTION 2: Hazards identification Elassification of the substance or mixture <ul> <li>Classification of the substance or mixture</li> <li>Classification according to Regulation (EC) No 1272/2008</li> <li>GHS07</li> <li>STOT SE 3 H336 May cause drowsiness or dizziness.</li> <li>2.2 Label elements</li> <li>Labelling according to Regulation (EC) No 1272/2008</li> <li>The product is classified and labelled according to the CLP regulation.</li> </ul>   | · Trade name: <u>B560 PURE MAROON</u>  |
| <ul> <li>Manufacturer/Supplier:<br/>P.O. Box 7623<br/>Beirut LEBANON<br/>info@hymax.biz<br/>Générale de Peinture, 70 Rue Cortambert 75116 Paris, France<br/>Tel:+33(0)175293559</li> <li>Further information obtainable from: Product Safety Department</li> <li>1.4 Emergency telephone number: +33 (0)6 07 87 13 41</li> <li>SECTION 2: Hazards identification</li> <li>2.1 Classification of the substance or mixture</li> <li>Classification according to Regulation (EC) No 1272/2008</li> <li>GHS02 flame</li> <li>Flam. Liq. 3 H226 Flammable liquid and vapour.</li> <li>GHS07</li> <li>STOT SE 3 H336 May cause drowsiness or dizziness.</li> <li>2.1 Label elements</li> <li>Label elements</li> <li>Label ing according to Regulation (EC) No 1272/2008</li> <li>The product is classified and labelled according to the CLP regulation.</li> </ul>   | <ul> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against<br/>use as industrial paint</li> <li>Sector of Use<br/>SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites<br/>SU22 Professional uses: Public domain (administration, education, entertainment, services,<br/>craftsmen)</li> <li>Product category<br/>PC9a Coatings and paints, thinners, paint removers<br/>PC9b Fillers, putties, plasters, modelling clay</li> </ul> |
| <ul> <li>SECTION 2: Hazards identification</li> <li>2.1 Classification of the substance or mixture</li> <li>Classification according to Regulation (EC) No 1272/2008</li> <li>GHS02 flame</li> <li>Flam. Liq. 3 H226 Flammable liquid and vapour.</li> <li>GHS07</li> <li>STOT SE 3 H336 May cause drowsiness or dizziness.</li> <li>2.2 Label elements</li> <li>Labelling according to Regulation (EC) No 1272/2008</li> <li>The product is classified and labelled according to the CLP regulation.</li> </ul>   | <ul> <li>Manufacturer/Supplier:<br/>P.O. Box 7623<br/>Beirut LEBANON<br/>info@hymax.biz<br/>Générale de Peinture, 70 Rue Cortambert 75116 Paris, France<br/>Tel:+33(0)175293559</li> <li>Further information obtainable from: Product Safety Department</li> </ul>   |
| <ul> <li>2.1 Classification of the substance or mixture</li> <li>Classification according to Regulation (EC) No 1272/2008</li> <li>GHS02 flame</li> <li>Flam. Liq. 3 H226 Flammable liquid and vapour.</li> <li>GHS07</li> <li>GHS07</li> <li>STOT SE 3 H336 May cause drowsiness or dizziness.</li> <li>2.2 Label elements</li> <li>Labelling according to Regulation (EC) No 1272/2008</li> <li>The product is classified and labelled according to the CLP regulation.</li> </ul>   |  |
| <ul> <li>Classification according to Regulation (EC) No 1272/2008</li> <li>GHS02 flame</li> <li>Flam. Liq. 3 H226 Flammable liquid and vapour.</li> <li>GHS07</li> <li>STOT SE 3 H336 May cause drowsiness or dizziness.</li> <li>2.2 Label elements</li> <li>Labelling according to Regulation (EC) No 1272/2008</li> <li>The product is classified and labelled according to the CLP regulation.</li> </ul>  | SECTION 2: Hazards identification  |
| GHS07<br>STOT SE 3 H336 May cause drowsiness or dizziness.<br>• 2.2 Label elements<br>• Labelling according to Regulation (EC) No 1272/2008<br>The product is classified and labelled according to the CLP regulation.   | Classification according to Regulation (EC) No 1272/2008   |
| GHS07<br>STOT SE 3 H336 May cause drowsiness or dizziness.<br>• <b>2.2 Label elements</b><br>• <b>Labelling according to Regulation (EC) No 1272/2008</b><br>The product is classified and labelled according to the CLP regulation.   |  |
| STOT SE 3 H336 May cause drowsiness or dizziness.<br>• 2.2 Label elements<br>• Labelling according to Regulation (EC) No 1272/2008<br>The product is classified and labelled according to the CLP regulation.  | Flam. Liq. 3 H226 Flammable liquid and vapour.   |
| <ul> <li>• 2.2 Label elements</li> <li>• Labelling according to Regulation (EC) No 1272/2008</li> <li>The product is classified and labelled according to the CLP regulation.</li> </ul>   |  |
| • Labelling according to Regulation (EC) No 1272/2008<br>The product is classified and labelled according to the CLP regulation.   | GHS07  |
| GB —   |  |
|  | <ul> <li>STOT SE 3 H336 May cause drowsiness or dizziness.</li> <li>2.2 Label elements</li> <li>Labelling according to Regulation (EC) No 1272/2008<br/>The product is classified and labelled according to the CLP regulation.</li> </ul>   |



Page 2/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Trade name: B560 PURE MAROON

|              | (Contd. of page 1  |
|--------------|--|
| Hazard pict  | fograms  |
| $\wedge$     | $\wedge$   |
| <**><        |  |
|              |  |
| GHS02 G      | HS07   |
| Signal word  | d Warning  |
|              | ermining components of labelling:  |
| n-butyl acet |  |
| Hazard stat  |  |
|              | nable liquid and vapour.   |
|              | ause drowsiness or dizziness.  |
|              | ary statements   |
| P101         | If medical advice is needed, have product container or label at hand.  |
| P102         | Keep out of reach of children.   |
| P103         | Read label before use.   |
| P210         | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources<br>No smoking.             |
| P241         | Use explosion-proof electrical/ventilating/lighting equipment.   |
| P261         | Avoid breathing dust/fume/gas/mist/vapours/spray.  |
| P303+P361    | +P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skii<br>with water/shower. |
| P405         | Store locked up.   |
| P501         | Dispose of contents/container in accordance with local/regional/national international regulations.          |
| 2.3 Other h  | azards   |
| Results of I | PBT and vPvB assessment  |

· vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Page 3/11

#### Trade name: B560 PURE MAROON

| CAS: 123-86-4                                  | n-butyl acetate   | >25- <i>≤</i> 50%  |
|--|---|--------------------|
| EINECS: 204-658-1<br>Reg.nr.: 01-2119485493-29 | 🚸 Flam. Liq. 3, H226; <b>(</b> ) STOT SE 3, H336  |                    |
|  | xylene  | >2.5- <i>≤</i> 10% |
|  | Solvent naphtha (petroleum), light arom.  | >2.5- <i>≤</i> 10% |
|  | 2-methoxy-1-methylethyl acetate   | >2.5- <i>≤</i> 10% |
|  | ethylbenzene<br>🔞 Flam. Liq. 2, H225; 🚯 STOT RE 2, H373; Asp. Tox. 1,<br>H304; 🕦 Acute Tox. 4, H332 | <i>≤</i> 2.5%      |

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

GB

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

(Contd. of page 3)

Page 4/11

Trade name: B560 PURE MAROON

- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Trade name: B560 PURE MAROON

|   | (Contd. of page 4  |
|---|--|
|   | ontrol parameters  |
| -   | dients with limit values that require monitoring at the workplace:   |
|   | 6-4 n-butyl acetate  |
|   | Short-term value: 966 mg/m³, 200 ppm<br>Long-term value: 724 mg/m³, 150 ppm  |
|   | 20-7 xylene  |
| WEL   | Short-term value: 441 mg/m³, 100 ppm<br>Long-term value: 220 mg/m³, 50 ppm<br>Sk; BMGV   |
| 108-6   | 5-6 2-methoxy-1-methylethyl acetate  |
|   | Short-term value: 548 mg/m³, 100 ppm<br>Long-term value: 274 mg/m³, 50 ppm<br>Sk   |
| 100-4   | 1-4 ethylbenzene   |
| WEL   | Short-term value: 552 mg/m³, 125 ppm<br>Long-term value: 441 mg/m³, 100 ppm<br>Sk  |
| · Ingre   | dients with biological limit values:   |
| 1330-   | 20-7 xylene  |
| BMG   | V 650 mmol/mol creatinine<br>Medium: urine<br>Sampling time: post shift<br>Parameter: methyl hippuric acid   |
| <ul> <li>8.2 Ex</li> <li>Perso</li> <li>Gene</li> <li>Imme</li> <li>Wash</li> <li>Resp</li> <li>In cas</li> <li>exposi</li> </ul> | <b>Fional information:</b> The lists valid during the making were used as basis.<br><b>Aposure controls</b><br><b>Inal protective equipment:</b><br><b>ral protective and hygienic measures:</b><br>diately remove all soiled and contaminated clothing<br>hands before breaks and at the end of work.<br><b>iratory protection:</b><br>se of brief exposure or low pollution use respiratory filter device. In case of intensive or longe<br>sure use self-contained respiratory protective device.<br><b>ction of hands:</b> |
|   | Protective gloves  |
| i ne g  | love material has to be impermeable and resistant to the product/ the substance/ the preparation<br>(Contd. on page)   |

Page 5/11





Page 6/11

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

#### Trade name: B560 PURE MAROON

(Contd. of page 5)

GB

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

| 9.1 Information on basic physical a<br>General Information | and chemical properties      |  |
|--|------------------------------|--|
| Appearance:  |                              |  |
| Form:  | Liquid                       |  |
| Colour:  | Brown                        |  |
| Odour:   | Characteristic               |  |
| Odour threshold:   | Not determined.              |  |
| pH-value:  | Not determined.              |  |
| Change in condition  |                              |  |
| Melting point/freezing point:                              | Undetermined.                |  |
| Initial boiling point and boiling ra                       | ange: 120 °C                 |  |
| Flash point:   | 27 °C                        |  |
| Flammability (solid, gas):                                 | Not applicable.              |  |
| Ignition temperature:                                      | 315 °C                       |  |
| Decomposition temperature:                                 | Not determined.              |  |
| Auto-ignition temperature:                                 | Product is not selfigniting. |  |



Page 7/11

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

#### Trade name: B560 PURE MAROON

|   | (Contd. of page 6   |
|---|---|
| Explosive properties:                   | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Explosion limits:                       |   |
| Lower:                                  | 1.2 Vol %   |
| Upper:                                  | 7.5 Vol %   |
| Vapour pressure at 20 °C:               | 10.7 hPa  |
| Density at 20 °C:                       | 0.958 g/cm <sup>3</sup>   |
| Relative density                        | Not determined.   |
| Vapour density                          | Not determined.   |
| Evaporation rate                        | Not determined.   |
| Solubility in / Miscibility with        |   |
| water:                                  | Not miscible or difficult to mix.   |
| Partition coefficient: n-octanol/water: | Not determined.   |
| Viscosity:                              |   |
| Dynamic:                                | Not determined.   |
| Kinematic:                              | Not determined.   |
| Solvent content:                        |   |
| Organic solvents:                       | 72.3 %  |
| VOC (EC)                                | 692.8 g/l   |
| Solids content:                         | 27.8 %  |
| 9.2 Other information                   | No further relevant information available.  |

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

### Trade name: B560 PURE MAROON

(Contd. of page 7)

Page 8/11

### SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

### 1330-20-7 xylene

Oral

Dermal

LD50 4,300 mg/kg (rat) LD50 2.000 mg/kg (rab)

D50 2,000 mg/kg (rabbit)

### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)

Dermal LD50 >3,400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

· Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.

· vPvB: Not applicable.

(Contd. on page 9)

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

(Contd. of page 8)

Page 9/11

### Trade name: B560 PURE MAROON

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

| SECTION 14: Transport information  |   |                 |
|--|---|-----------------|
| 14.1 UN-Number<br>ADR, IMDG, IATA  | UN1263  |                 |
| 14.2 UN proper shipping name<br>ADR<br>IMDG, IATA                          | 1263 PAINT<br>PAINT                                 |                 |
| 14.3 Transport hazard class(es)<br>ADR, IMDG, IATA                         |   |                 |
| Class<br>Label   | 3 Flammable liquids.<br>3                           |                 |
| <i>14.4 Packing group<br/>ADR, IMDG, IATA</i>                              | <i>III</i>  |                 |
| 14.5 Environmental hazards:<br>Marine pollutant:                           | No  |                 |
| 14.6 Special precautions for user<br>EMS Number:<br>Stowage Category       | Warning: Flammable liquids.<br>F-E, <u>S-E</u><br>A |                 |
| 14.7 Transport in bulk according to Annex II of<br>Marpol and the IBC Code | f<br>Not applicable.                                |                 |
|  |   | (Contd. on page |





Page 10/11

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Trade name: B560 PURE MAROON

|   | (Contd. of page   |
|---|---|
| <ul> <li>Transport/Additional information:</li> </ul>                                       |   |
| <ul> <li>ADR</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>  | 5L<br>Code: E1  |
| Transport category     Tunnel restriction code  | Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 m<br>3<br>D/E       |
| <ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul> | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 m |
| · UN "Model Regulation":  | UN 1263 PAINT, 3, III   |

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

(Contd. on page 11)

GB

# Safety data sheet according to 1907/2006/EC, Article 31

| Printing date 24.09.2019  | Revision: 06.05.2019                               |
|---|--|
| Trade name: B560 PURE MAROON  |  |
|   | (Contd. of page 10                                 |
| H336 May cause drowsiness or dizziness.   |  |
| H373 May cause damage to the hearing organs through prolo   | onged or repeated exposure.                        |
| · Department issuing SDS: Product safety department   |  |
| Contact: N/A  |  |
| · Abbreviations and acronyms:   |  |
| RID: Règlement international concernant le transport des marchandises dans<br>the International Transport of Dangerous Goods by Rail) | gereuses par chemin de fer (Regulations Concerning |
| ICAO: International Civil Aviation Organisation   |  |
| ADR: Accord européen sur le transport des marchandises dangereuses<br>International Carriage of Dangerous Goods by Road)              | par Route (European Agreement concerning th        |
| IMDG: International Maritime Code for Dangerous Goods   |  |
| IATA: International Air Transport Association   |  |
| GHS: Globally Harmonised System of Classification and Labelling of Chemic   | als  |
| EINECS: European Inventory of Existing Commercial Chemical Substances   |  |
| ELINCS: European List of Notified Chemical Substances   | 4  |
| CAS: Chemical Abstracts Service (division of the American Chemical Society<br>VOC: Volatile Organic Compounds (USA, EU)               | ()   |
| LC50: Lethal concentration, 50 percent  |  |
| LD50: Lethal dose, 50 percent   |  |
| PBT: Persistent, Bioaccumulative and Toxic  |  |
| vPvB: very Persistent and very Bioaccumulative  |  |
| Flam. Liq. 2: Flammable liquids – Category 2  |  |
| Flam. Liq. 3: Flammable liquids – Category 3  |  |
| Acute Tox. 4: Acute toxicity – Category 4   |  |
| Skin Irrit. 2: Skin corrosion/irritation – Category 2   |  |
| STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  |  |
| STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  |  |
| Asp. Tox. 1: Aspiration hazard – Category 1   |  |

Page 11/11

