

Page 1/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier
· Trade name: <u>B690 FINE SATIN WHITE</u>
<ul> <li>Article number: B690</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint</li> <li>Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)</li> <li>Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay</li> <li>Application of the substance / the mixture refer to the relevant Technical Data Sheet</li> </ul>
<ul> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier: <ul> <li>P.O. Box 7623</li> <li>Beirut LEBANON</li> <li>info@hymax.biz</li> <li>Générale de Peinture, 70 Rue Cortambert 75116 Paris, France</li> <li>Tel:+33(0)175293559</li> </ul> </li> <li>Further information obtainable from: Product Safety Department <ul> <li>1.4 Emergency telephone number: +33 (0)6 07 87 13 41</li> </ul> </li> </ul>
SECTION 2: Hazards identification
• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 GHS02 flame
Flam. Liq. 3 H226 Flammable liquid and vapour.
GHS07
STOT SE 3 H336 May cause drowsiness or dizziness.
<ul> <li>· 2.2 Label elements</li> <li>· Labelling according to Regulation (EC) No 1272/2008</li> </ul>
The product is classified and labelled according to the CLP regulation. (Contd. on page 2)



Page 2/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Trade name: B690 FINE SATIN WHITE

	(Contd. of page	
Hazard pictog	<i>jrams</i>	
$\wedge$		
く きょく 1		
VÝ V		
GHS02 GHS	507	
Signal word V	Varning	
Hazard-deteri	mining components of labelling:	
n-butyl acetate		
Hazard staten		
H226 Flamma	ble liquid and vapour.	
	ise drowsiness or dizziness.	
Precautionary	/ statements	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read label before use.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources No smoking.	
P241	Use explosion-proof electrical/ventilating/lighting equipment.	
P261		
P303+P361+F	2353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse ski	
	with water/shower.	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/nationa international regulations.	
2.3 Other haza	ards	
Results of PB	BT and vPvB assessment	
	ards 8T and vPvB assessment	

· vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3) GB

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Page 3/11

### Trade name: B690 FINE SATIN WHITE

CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate	>50- <i>≤</i> 100%
Reg.nr.: 01-2119485493-29	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
CAS: 1330-20-7	xylene	>2.5-≤10%
EINECS: 215-535-7 Reg.nr.: 01-2119486136-34	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4,	
05-2116602925-45	H332, SKIII IIIII. 2, H315	
01-2119488216-32		
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
EINECS: 265-199-0	🚸 Acute Tox. 4, H332; STOT SE 3, H335	
Reg.nr.: 01-2119455851-35		
05-2116598517-27		
CAS: 100-41-4	ethylbenzene	<i>≤</i> 2.5%
EINECS: 202-849-4	🤣 Flam. Liq. 2, H225; 🕹 STOT RE 2, H373; Asp. Tox. 1,	
Reg.nr.: 01-2119489370-35	H304; 🕦 Acuté Tox. 4, H332	

## SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- $\cdot$  5.2 Special hazards arising from the substance or mixture
- No further relevant information available.

(Contd. on page 4)



GB

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

### Trade name: B690 FINE SATIN WHITE

#### 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

## ECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5) GB



(Contd. of page 3)

Page 4/11

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Page 5/11

## Trade name: B690 FINE SATIN WHITE

	(Contd. of page 4
8.1 Co	ontrol parameters
Ingrea	lients with limit values that require monitoring at the workplace:
123-86	6-4 n-butyl acetate
	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
1330-2	20-7 xylene
1	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
100-41	1-4 ethylbenzene
1	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk
· Ingrea	lients with biological limit values:
1330-2	20-7 xylene
	Medium: urine Sampling time: post shift Parameter: methyl hippuric acid ional information: The lists valid during the making were used as basis. posure controls
<ul> <li>Persol</li> <li>Gener</li> <li>Immed</li> <li>Wash</li> <li>Respin</li> <li>In case</li> <li>exposition</li> </ul>	nal protective equipment: ral protective and hygienic measures: diately remove all soiled and contaminated clothing hands before breaks and at the end of work. ratory protection: e of brief exposure or low pollution use respiratory filter device. In case of intensive or longe ure use self-contained respiratory protective device. ction of hands:
MAS-	Protective gloves
Due to	love material has to be impermeable and resistant to the product/ the substance/ the preparation or missing tests no recommendation to the glove material can be given for the product/ the ration/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 6)



Page 6/11

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

## Trade name: B690 FINE SATIN WHITE

(Contd. of page 5) substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemic	
9.1 Information on basic physical and c	hemical properties
General Information	
Appearance: Form:	Liquid
Form. Colour:	Whitish
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	
	27 °C
•	Not applicable.
Ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.984 g/cm <sup>3</sup>

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Page 7/11

### Trade name: B690 FINE SATIN WHITE

	(Contd. of pa	age
· Relative density	Not determined.	
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	73.3 %	
VÕC (EC)	721.4 g/l	
Solids content:	26.7 %	
· 9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
1330-20-	7 xylene		
Oral	LD50	4,300 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
64742-95	5-6 Solver	nt naphtha (petroleum), light arom.	
Oral	LD50	>6,800 mg/kg (rat)	
Dermal	LD50	>3,400 mg/kg (rab)	
	•	•	(Contd. on page 8)

- page 0) ------ GB

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

(Contd. of page 7)

Page 8/11

### Trade name: B690 FINE SATIN WHITE

#### Inhalative LC50/4 h >10.2 mg/l (rat)

- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 9)

GB



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

## Trade name: B690 FINE SATIN WHITE

(Contd. of page 8)

Page 9/11

14.1 UN-Number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
EMS Number:	F-E,S-E
Stowage Category	A
14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
Transport optogory	Maximum net quantity per outer packaging: 1000 m
Transport category Tunnel restriction code	3 D/E
IMDG	5L
Limited quantities (LQ) Excepted quantities (EQ)	SL Code: E1
LAUpieu quantities (LQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 m
	(Contd. on page 1



according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

(Contd. of page 9)

Page 10/11

### Trade name: B690 FINE SATIN WHITE

· UN "Model Regulation":

UN 1263 PAINT, 3, III

#### SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### · Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 11)

GB



Page 11/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

## Trade name: B690 FINE SATIN WHITE

(Contd. of page 10)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

GB -