

Page 1/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier
· Trade name: <u>B778 XIRALLIC GREEN</u>
<ul> <li>Article number: B778</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint</li> <li>Sector of Use</li> <li>SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites</li> <li>SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)</li> <li>Product category</li> <li>PC9a Coatings and paints, thinners, paint removers</li> <li>PC9b Fillers, putties, plasters, modelling clay</li> <li>Application of the substance / the mixture refer to the relevant Technical Data Sheet</li> </ul>
<ul> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier: <ul> <li>P.O. Box 7623</li> <li>Beirut LEBANON</li> <li>info@hymax.biz</li> <li>Générale de Peinture, 70 Rue Cortambert 75116 Paris, France</li> <li>Tel:+33(0)175293559</li> </ul> </li> <li>Further information obtainable from: Product Safety Department</li> <li>1.4 Emergency telephone number: +33 (0)6 07 87 13 41</li> </ul>
SECTION 2: Hazards identification
<ul> <li>2.1 Classification of the substance or mixture</li> <li>Classification according to Regulation (EC) No 1272/2008</li> <li>GHS02 flame</li> </ul>
Flam. Liq. 3 H226 Flammable liquid and vapour.
GHS07
STOT SE 3 H336 May cause drowsiness or dizziness.
· 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation. (Contd. on page 2) GB



Page 2/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Trade name: B778 XIRALLIC GREEN

	(Contd. of page 7
Hazard pict	ograms
	$\wedge$
/ Mr /	
	•
GHS02 G	HS07
611502 6	1507
Signal word	I Warning
Hazard-det	ermining components of labelling:
n-butyl aceta	
Hazard stat	
H226 Flamn	nable liquid and vapour.
	ause drowsiness or dizziness.
Precaution	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skil with water/shower.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national international regulations.
2.3 Other ha	5
Results of I	PBT and vPvB assessment
PBT: Not ap	oplicable.
vPvB: Not a	applicable.

**SECTION 3: Composition/information on ingredients** 

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Page 3/11

#### Trade name: B778 XIRALLIC GREEN

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate � Flam. Liq. 3, H226; � STOT SE 3, H336	>50- <i>≤</i> 100%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32		>2.5- <i>≤</i> 10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	Solvent naphtha (petroleum), light arom. � Acute Tox. 4, H332; STOT SE 3, H335	>2.5- <i>≤</i> 10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene	<i>≤</i> 2.5%

# SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

GB

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

(Contd. of page 3)

Page 4/11

Trade name: B778 XIRALLIC GREEN

- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

# SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Page 5/11

## Trade name: B778 XIRALLIC GREEN

<ul> <li>8.1 Control parameters</li> <li>Ingredients with limit values that require monitoring at the workplace:</li> <li>123-86-4 n-butyl acetate</li> <li>WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm</li> <li>130-20-7 xylene</li> <li>WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk: BMGV</li> <li>108-65-6 2-methoxy-1-methylethyl acetate</li> <li>WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk: BMGV</li> <li>100-41-4 ethylbenzene</li> <li>WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 522 mg/m³, 125 ppm Sk</li> <li>100-41-4 ethylbenzene</li> <li>WEL Short-term value: 552 mg/m³, 100 ppm Sk</li> <li>Ingredients with biological limit values:</li> <li>1330-20-7 xylene</li> <li>BMGV ( 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid</li> <li>Additional information: The lists valid during the making were used as basis.</li> <li>8.2 Exposure controls</li> <li>Personal protective and hygienic measures: Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> <li>Protective gloves</li> </ul>		(Contd. of page 4
123-86-4 n-butyl acetate         WEL       Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm         1330-20-7 xylene         WEL       Short-term value: 411 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm         Sk; BMGV         108-65-62-methoxy-1-methylethyl acetate         WEL       Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm         VBL       Short-term value: 527 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk         100-41-4 ethylbenzene         WEL       Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk         100-41-4 ethylbenzene         WEL       Short-term value: 548 mg/m³, 100 ppm Sk         100-41-4 ethylbenzene         WEL       Short-term value: 548 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk         Ingredients with biological limit values:         130-20-7 xylene         BMGV       650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid       Parameter:         Additional information: The lists valid during the making were used as basis.       8.2         8.2 Exposure controls       Personal protective and hygienic measures: Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work.         Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of int		-
WEL       Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm         1330-20-7 xylene         WEL       Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV         108-65-6 2-methoxy-1-methylethyl acetate         WEL       Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk         100-41-4 ethylbenzene         WEL       Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk         100-41-4 ethylbenzene         WEL       Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk         100-41-4 ethylbenzene         WEL       Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk         130-20-7 xylene         BMGV       650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid         Additional information: The lists valid during the making were used as basis.         8.2 Exposure controls         Personal protective equipment: General protective and hygienic measures: Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work.         Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device.         Protection of hands:       Protective gloves	-	
Long-term value: 724 mg/m³, 150 ppm         1330-20-7 xylene         WEL       Short-term value: 241 mg/m³, 100 ppm         Long-term value: 220 mg/m³, 50 ppm         Sk; BMGV         108-65-6 2-methoxy-1-methylethyl acetate         WEL       Short-term value: 548 mg/m³, 100 ppm         Long-term value: 274 mg/m³, 50 ppm         Sk       Short-term value: 274 mg/m³, 50 ppm         Sk       Short-term value: 552 mg/m³, 125 ppm         Long-term value: 441 mg/m³, 100 ppm         Sk       Short-term value: 441 mg/m³, 100 ppm         Long-term value: 552 mg/m³, 125 ppm         Long-term value: 441 mg/m³, 100 ppm         Sk         Ingredients with biological limit values:         1330-20-7 xylene         BMGV       650 mmo/mol creatinine         Medium: urine       Sampling time: post shift         Parameter: methyl hippuric acid       Additional information: The lists valid during the making were used as basis.         8.2 Exposure controls       Personal protective equipment:         General protective and hygienic measures:       Immediately remove all solied and contaminated clothing         Wash hands before breaks and at the end of work.       Respiratory protection:         In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-		•
WEL       Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV         108-65-6 2-methoxy-1-methylethyl acetate         WEL       Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk         100-41-4 ethylbenzene         WEL       Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk         100-etrm value: 441 mg/m³, 100 ppm Sk         Ingredients with biological limit values:         1330-20-7 xylene         BMGV       650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid         Additional information: The lists valid during the making were used as basis.         8.2 Exposure controls         Personal protective equipment: General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.         Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device.         Protection of hands:         Votective gloves		
Long-term value: 220 mg/m³, 50 ppm Sk; BMGV <b>108-65-6 2-methoxy-1-methylethyl acetate</b> WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk <b>100-41-4 ethylbenzene</b> WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk <b>100-41-4 ethylbenzene</b> <b>1330-20-7 xylene</b> BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid <b>Additional information</b> : The lists valid during the making were used as basis. <b>8.2 Exposure controls</b> <b>Personal protective equipment:</b> <b>General protective equipment:</b> <b>General protective equipment:</b> <b>Inmediately remove all solied and contaminated clothing</b> Wash hands before breaks and at the end of work. <b>Respiratory protection:</b> In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device. <b>Protection of hands:</b> <i>Protective gloves</i>	1330-2	20-7 xylene
<ul> <li>WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m<sup>3</sup>, 50 ppm Sk</li> <li>100-41-4 ethylbenzene</li> <li>WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm Long-term value: 441 mg/m<sup>3</sup>, 100 ppm Sk</li> <li>Ingredients with biological limit values:</li> <li>1330-20-7 xylene</li> <li>BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid</li> <li>Additional information: The lists valid during the making were used as basis.</li> <li>8.2 Exposure controls</li> <li>Personal protective equipment:</li> <li>General protective and hygienic measures: Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> <li>Protective gloves</li> </ul>		Long-term value: 220 mg/m <sup>3</sup> , 50 ppm
Long-term value: 274 mg/m³, 50 ppm Sk 100-41-4 ethylbenzene WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device. Protection of hands: Protective gloves	108-6	5-6 2-methoxy-1-methylethyl acetate
WEL       Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk         Ingredients with biological limit values:         1330-20-7 xylene         BMGV       650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid         Additional information: The lists valid during the making were used as basis.         8.2 Exposure controls         Personal protective equipment:         General protective and hygienic measures: Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work.         Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device.         Protective gloves		Long-term value: 274 mg/m <sup>3</sup> , 50 ppm
Long-term value: 441 mg/m³, 100 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device. Protection of hands: Protective gloves	100-4	1-4 ethylbenzene
1330-20-7 xylene         BMGV       650 mmol/mol creatinine         Medium: urine       Sampling time: post shift         Parameter: methyl hippuric acid       Additional information: The lists valid during the making were used as basis.         Additional information: The lists valid during the making were used as basis.         Additional information: The lists valid during the making were used as basis.         Additional information: The lists valid during the making were used as basis.         Bersonal protective equipment:         General protective and hygienic measures:         Immediately remove all soiled and contaminated clothing         Wash hands before breaks and at the end of work.         Respiratory protection:         In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device.         Protection of hands:         Volume         Protective gloves		Long-term value: 441 mg/m <sup>3</sup> , 100 ppm
BMGV       650       mmol/mol creatinine         Medium: urine       Sampling time: post shift         Parameter: methyl hippuric acid       Parameter: methyl hippuric acid         Additional information: The lists valid during the making were used as basis.         8.2 Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Immediately remove all soiled and contaminated clothing         Wash hands before breaks and at the end of work.         Respiratory protection:         In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device.         Protection of hands:         Protective gloves	Ingree	dients with biological limit values:
Medium: urine Sampling time: post shift Parameter: methyl hippuric acid • Additional information: The lists valid during the making were used as basis. • 8.2 Exposure controls • Personal protective equipment: • General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. • Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device. • Protection of hands: • Protective gloves	1330-2	20-7 xylene
<ul> <li>8.2 Exposure controls</li> <li>Personal protective equipment:</li> <li>General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> <li>Protective gloves</li> </ul>	BMG\	Medium: urine Sampling time: post shift
<ul> <li>Personal protective equipment:</li> <li>General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> <li>Protective gloves</li> </ul>	· Addit	ional information: The lists valid during the making were used as basis.
	<ul> <li>Perso</li> <li>Genel Immed Wash</li> <li>Respin In cass expos</li> </ul>	nal protective equipment: ral protective and hygienic measures: diately remove all soiled and contaminated clothing hands before breaks and at the end of work. iratory protection: se of brief exposure or low pollution use respiratory filter device. In case of intensive or long- ure use self-contained respiratory protective device.
	MJ-	Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. (Contd. on page 6)



Page 6/11

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

#### Trade name: B778 XIRALLIC GREEN

(Contd. of page 5)

GB

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

9.1 Information on basic physical a General Information	and chemical properties	
Appearance:		
Form:	Liquid	
Colour:	Green	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ra	ange: 124 °C	
Flash point:	27 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	370 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	



Page 7/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

#### Trade name: B778 XIRALLIC GREEN

	(Contd. of page 6
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.962 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	74.3 %
VÕC (EC)	714.5 g/l
Solids content:	25.7 %
9.2 Other information	No further relevant information available.

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

#### Trade name: B778 XIRALLIC GREEN

(Contd. of page 7)

Page 8/11

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

## 1330-20-7 xylene

Oral

Dermal

LD50 4,300 mg/kg (rat) LD50

2,000 mg/kg (rabbit)

## 64742-95-6 Solvent naphtha (petroleum), light arom.

LD50 >6,800 mg/kg (rat) Oral

LD50 Dermal >3,400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

- · Serious eve damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

· vPvB: Not applicable.

(Contd. on page 9)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

### Trade name: B778 XIRALLIC GREEN

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT	
14.3 Transport hazard class(es) ADR, IMDG, IATA		
Class Label	3 Flammable liquids. 3	
14.4 Packing group ADR, IMDG, IATA	<i>III</i>	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids. F-E,S-E A	
14.7 Transport in bulk according to Annex Marpol and the IBC Code	Il of Not applicable.	



(Contd. of page 8)

Page 9/11



Page 10/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

Trade name: B778 XIRALLIC GREEN

· Transport/Additional information:	(Contd. of page s
<ul> <li>ADR</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
<ul> <li>Transport category</li> <li>Tunnel restriction code</li> </ul>	Maximum net quantity per outer packaging: 1000 m 2 E
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
· UN "Model Regulation":	UN 1263 PAINT, 3, III

#### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

(Contd. on page 11)

GB



Printing date 24.09.2019	Revision: 06.05.2019
rade name: B778 XIRALLIC GREEN	
	(Contd. of page 10
H336 May cause drowsiness or dizziness.	
H373 May cause damage to the hearing organs through prolong	ged or repeated exposure.
· Department issuing SDS: Product safety department	
· Contact: N/A	
· Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises danger	reuses par chemin de fer (Regulations Concerning
the International Transport of Dangerous Goods by Rail)	
ICAO: International Civil Aviation Organisation	
ADR: Accord européen sur le transport des marchandises dangereuses p	ar Route (European Agreement concerning the
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	5
EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	

Page 11/11

