

Page 1/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

| SECTION 1: Identification of the substance/mixture and of the company/<br>undertaking  |
|--|
| · 1.1 Product identifier   |
| · Trade name: <u>P40 2K RAPID PRIMER BEIGE</u>   |
| <ul> <li>Article number: P40</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against<br/>use as industrial paint</li> <li>Sector of Use</li> <li>SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites</li> <li>SU22 Professional uses: Public domain (administration, education, entertainment, services,<br/>craftsmen)</li> <li>Product category</li> <li>PC9a Coatings and paints, thinners, paint removers</li> <li>PC9b Fillers, putties, plasters, modelling clay</li> <li>Application of the substance / the mixture refer to the relevant Technical Data Sheet</li> </ul> |
| <ul> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier: <ul> <li>P.O. Box 7623</li> <li>Beirut LEBANON</li> <li>info@hymax.biz</li> <li>Générale de Peinture, 70 Rue Cortambert 75116 Paris, France</li> <li>Tel:+33(0)175293559</li> </ul> </li> <li>Further information obtainable from: Product Safety Department</li> <li>1.4 Emergency telephone number: +33 (0)6 07 87 13 41</li> </ul>  |
| SECTION 2: Hazards identification  |
| • 2.1 Classification of the substance or mixture<br>• Classification according to Regulation (EC) No 1272/2008<br>GHS02 flame  |
| Flam. Liq. 3 H226 Flammable liquid and vapour.   |
| GHS07  |
| Skin Irrit. 2 H315 Causes skin irritation.   |
| • 2.2 Label elements     • Labelling according to Regulation (EC) No 1272/2008     The product is classified and labelled according to the CLP regulation.     (Contd. on page 2)  |
|  |



Page 2/11

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

### Trade name: P40 2K RAPID PRIMER BEIGE

(Contd. of page 1) Hazard pictograms GHS02 GHS07 · Signal word Warning · Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. Wear protective gloves/protective clothing/eye protection/face protection. P280 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P501 Dispose of contents/container in accordance with local/regional/national/ international regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable.

• **vPvB:** Not applicable.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| CAS: 1330-20-7            | xylene  | >10- <i>≤</i> 25 |
|---------------------------|---|------------------|
| EINECS: 215-535-7         | 🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H312; Acute Tox. 4, |                  |
| Reg.nr.: 01-2119486136-34 | H332; Skin Irrit. 2, H315                                 |                  |
| 05-2116602925-45          |   |                  |
| 01-2119488216-32          |   |                  |
| CAS: 123-86-4             | n-butyl acetate   | >2.5-≤10         |
| EINECS: 204-658-1         | 🗞 Flam. Liq. 3, H226; 🚯 STOT SE 3, H336                   |                  |
| Reg.nr.: 01-2119485493-29 |   |                  |



Page 3/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

### Trade name: P40 2K RAPID PRIMER BEIGE

|                              | (0  | Contd. of page 2) |
|------------------------------|---|-------------------|
| CAS: 64742-95-6              | Solvent naphtha (petroleum), light arom.                        | <i>≤</i> 2.5%     |
| EINECS: 265-199-0            | 🚸 Acute Tox. 4, H332; STOT SE 3, H335                           |                   |
| Reg.nr.: 01-2119455851-35    |   |                   |
| 05-2116598517-27             |   |                   |
| CAS: 100-41-4                | ethylbenzene  | <i>≤</i> 2.5%     |
| EINECS: 202-849-4            | 🚸 Flam. Liq. 2, H225; 🚸 STOT RE 2, H373; Asp. Tox. 1,           | 1                 |
| Reg.nr.: 01-2119489370-35    | H304; 🚸 Acute Tox. 4, H332                                      |                   |
| CAS: 77-58-7                 | dibutyltin dilaurate  | <i>≤</i> 2.5%     |
| EINECS: 201-039-8            | ♦ Acute Tox. 3, H301; ♦ Muta. 2, H341; Repr. 1B,                |                   |
|                              | H360FD; STOT RE 1, H372   |                   |
| · Additional information: Fo | r the wording of the listed hazard phrases refer to section 16. |                   |

### SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

<sup>-</sup> GB



Page 4/11

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

(Contd. of page 3)

### Trade name: P40 2K RAPID PRIMER BEIGE

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3** Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

### SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters
Ingredients with limit values that require monitoring at the workplace:
1330-20-7 xylene
WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm Long-term value: 220 mg/m<sup>3</sup>, 50 ppm Sk; BMGV
123-86-4 n-butyl acetate
WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm
100-41-4 ethylbenzene
WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm Long-term value: 441 mg/m<sup>3</sup>, 100 ppm Sk

(Contd. on page 5)

GB



Page 5/11

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

### Trade name: P40 2K RAPID PRIMER BEIGE

|                        | The statistic states and a   | (Contd. of page 4 |
|------------------------|--|-------------------|
|                        | -7 dibutyltin dilaurate  |                   |
| WEL                    | Short-term value: 0.2 mg/m <sup>3</sup>  |                   |
|                        | Long-term value: 0.1 mg/m <sup>3</sup>   |                   |
|                        | as Sn; Sk  |                   |
| Ingre                  | dients with biological limit values:   |                   |
| 1330-                  | 20-7 xylene  |                   |
| BMG                    | 650 mmol/mol creatinine  |                   |
|                        | Medium: urine  |                   |
|                        | Sampling time: post shift  |                   |
|                        | Parameter: methyl hippuric acid  |                   |
| Addit                  | ional information: The lists valid during the making were used as basis.   |                   |
| Wash<br>Avoid<br>Avoid | diately remove all soiled and contaminated clothing<br>hands before breaks and at the end of work.<br>contact with the skin. |                   |
|                        | contact with the eyes and skin.<br>ratory protection: Not required.<br>ction of hands:                                       |                   |
|                        | ratory protection: Not required.   |                   |

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

### Trade name: P40 2K RAPID PRIMER BEIGE

· Eye protection:

Tightly sealed goggles

## **SECTION 9: Physical and chemical properties**

| General Information                     |   |
|---|---|
| Appearance:                             |   |
| Form:                                   | Liquid  |
| Colour:                                 | Beige   |
| Odour:                                  | Characteristic  |
| Odour threshold:                        | Not determined.   |
| pH-value:                               | Not determined.   |
| Change in condition                     |   |
| Melting point/freezing point:           | Undetermined.   |
| Initial boiling point and boiling range | : 124 °C  |
| Flash point:                            | 25 ℃  |
| Flammability (solid, gas):              | Not applicable.   |
| Ignition temperature:                   | 370 °C  |
| Decomposition temperature:              | Not determined.   |
| Auto-ignition temperature:              | Product is not selfigniting.  |
| Explosive properties:                   | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Explosion limits:                       |   |
| Lower:                                  | 1.1 Vol %   |
| Upper:                                  | 7 Vol %   |
| Vapour pressure at 20 °C:               | 6.7 hPa   |
| Density at 20 °C:                       | 1.63 g/cm <sup>3</sup>  |
| Relative density                        | Not determined.   |
| Vapour density                          | Not determined.   |
| Evaporation rate                        | Not determined.   |

GB





(Contd. of page 5)



Page 7/11

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

### Trade name: P40 2K RAPID PRIMER BEIGE

|   | (Contd. of pag                             | je 6 |
|---|--|------|
| <ul> <li>Solubility in / Miscibility with<br/>water:</li> </ul> | Not miscible or difficult to mix.          |      |
| · Partition coefficient: n-octanol/water:                       | Not determined.                            |      |
| · Viscosity:  |  |      |
| Dynamic:  | Not determined.                            |      |
| Kinematic:  | Not determined.                            |      |
| · Solvent content:  |  |      |
| Organic solvents:   | 25.0 %                                     |      |
| VÕC (EC)  | 406.8 g/l                                  |      |
| Solids content:   | 74.7 %                                     |      |
| · 9.2 Other information   | No further relevant information available. |      |

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

| 7 xylene   |   |  |
|------------|---|--|
| LD50       | 4,300 mg/kg (rat)                                 |  |
| LD50       | 2,000 mg/kg (rabbit)                              |  |
| -6 Solvent | naphtha (petroleum), light arom.                  |  |
| LD50       | >6,800 mg/kg (rat)                                |  |
| LD50       | >3,400 mg/kg (rab)                                |  |
| LC50/4 h   | >10.2 mg/l (rat)                                  |  |
|            |   | (Contd. on page 8  |
| ;          | LD50<br>LD50<br><b>-6 Solvent</b><br>LD50<br>LD50 | LD50       4,300 mg/kg (rat)         LD50       2,000 mg/kg (rabbit) <b>i-6 Solvent naphtha (petroleum), light arom.</b> LD50       >6,800 mg/kg (rat) |



Page 8/11

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

(Contd. of page 7)

### Trade name: P40 2K RAPID PRIMER BEIGE

### 77-58-7 dibutyltin dilaurate

Oral LD50 175 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- SECTION 12: Ecological information
- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. (Contd. on page 9)

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

(Contd. of page 8)

Page 9/11

### Trade name: P40 2K RAPID PRIMER BEIGE

Uncleaned packaging:
 Recommendation: Disposal must be made according to official regulations.

| 14.1 UN-Number<br>ADR, IMDG, IATA   | UN1263  |
|---|---|
| 14.2 UN proper shipping name<br>ADR<br>IMDG, IATA   | 1263 PAINT<br>PAINT   |
| 14.3 Transport hazard class(es)   |   |
| ADR, IMDG, IATA   |   |
|   |   |
| Class<br>Label  | 3 Flammable liquids.<br>3   |
| 14.4 Packing group<br>ADR, IMDG, IATA   | <i>III</i>  |
| 14.5 Environmental hazards:<br>Marine pollutant:  | No  |
| 14.6 Special precautions for user<br>Danger code (Kemler):<br>EMS Number:<br>Stowage Category | Warning: Flammable liquids.<br>30<br>F-E <u>,S-E</u><br>A         |
| 14.7 Transport in bulk according to Ann<br>Marpol and the IBC Code                            | ex II of<br>Not applicable.                                       |
| Transport/Additional information:   |   |
| ADR<br>Limited quantities (LQ)<br>Excepted quantities (EQ)                                    | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml |
| Transport category<br>Tunnel restriction code   | Maximum net quantity per outer packaging: 1000 i<br>3<br>D/E      |





Page 10/11

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

### Trade name: P40 2K RAPID PRIMER BEIGE

(Contd. of page 9)

| <ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul> | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
|---|--|
| · UN "Model Regulation":  | UN 1263 PAINT, 3, III  |

### SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 20

· Regulation (EU) No 649/2012

77-58-7 dibutyltin dilaurate

Annex I Part 1

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 11)

- GB



Printing date 25.09.2019

Revision: 06.05.2019

Page 11/11

### Trade name: P40 2K RAPID PRIMER BEIGE

|    | (Contd. of page  |
|----|--|
| r  | Department issuing SDS: Dreduct selectu department   |
|    | Department issuing SDS: Product safety department  |
| _  | Contact: N/A   |
| A  | Abbreviations and acronyms:  |
|    | RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concern |
| ťł | he International Transport of Dangerous Goods by Rail)   |
| ю  | CAO: International Civil Aviation Organisation   |
| Α  | NDR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning              |
| lr | nternational Carriage of Dangerous Goods by Road)  |
|    | MDG: International Maritime Code for Dangerous Goods   |
|    | ATA: International Air Transport Association   |
|    | GHS: Globally Harmonised System of Classification and Labelling of Chemicals   |
|    | EINECS: European Inventory of Existing Commercial Chemical Substances  |
|    | ELINCS: European List of Notified Chemical Substances  |
|    | CAS: Chemical Abstracts Service (division of the American Chemical Society)  |
|    | /OC: Volatile Organic Compounds (USA, EU)  |
|    | C50: Lethal concentration, 50 percent  |
|    | D50: Lethal dose, 50 percent   |
|    | PBT: Persistent, Bioaccumulative and Toxic   |
|    | PvB: very Persistent and very Bioaccumulative  |
|    | Flam. Liq. 2: Flammable liquids – Category 2   |
|    | Flam. Liq. 3: Flammable liquids – Category 3   |
|    | Acute Tox. 3: Acute toxicity – Category 3  |
|    | Acute Tox. 4: Acute toxicity – Category 4  |
|    | Skin Irrit. 2: Skin corrosion/irritation – Category 2  |
|    | Auta. 2: Germ cell mutagenicity – Category 2   |
|    | Repr. 1B: Reproductive toxicity – Category 1B  |
|    | STOT SE 3: Specific target organ toxicity (single exposure) – Category 3   |
|    | STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1   |
|    | STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2   |
| A  | Asp. Tox. 1: Aspiration hazard – Category 1  |

