Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.01.2021

Revision: 20.08.2020

SECTION 1: Identification of the substance/mixture and of the company, undertaking

- · 1.1 Product identifier
- · Trade name: P420 HYFLASH 2K VOC PRIMER GREY
- · Article number: P420
- · UFI: 8184-U0PG-J006-HWDA
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available. use as industrial paint
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category
 PC9a Coatings and paints, thinners, paint removers
 PC9b Fillers, putties, plasters, modelling clay
 Application of the substance / the mixture refer to the relevant Technical Data Sheet

- \cdot 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Générale de Peinture,
 70 Rue Cortambert 75116 Paris, France info@hymax.biz
- · Further information obtainable from: Product Safety Department
- 1.4 Emergency telephone number: +33 (0)1 60 86 77 65

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Warning

(Contd. on page 2)

GB

Printing date 08.01.2021

HYMA

Revision: 20.08.2020

Trade name: P420 HYFLASH 2K VOC PRIMER GREY

	(Contd. of page 1)
 Hazard statemer 	nts
H226 Flammable	liquid and vapour.
 Precautionary st 	fatements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P35	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water [or shower].
P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.
· 2.3 Other hazard	ls
 Results of PBT a 	and vPvB assessment
· PBT: Not applical	ble.
D.D. Matamatia	

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures


· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural	>10- <i>≤</i> 25%
	substance with a Community workplace exposure limit	0.5.5100/
CAS: 1332-58-7	Kaolin substance with a Community workplace exposure limit	>2.5- <i>≤</i> 10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32	xylene	>2.5- <i>≤</i> 10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate � Flam. Liq. 3, H226; � STOT SE 3, H336	>2.5- <i>≤</i> 10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%

Printing date 08.01.2021

Revision: 20.08.2020

Trade name: P420 HYFLASH 2K VOC PRIMER GREY



· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 08.01.2021

Revision: 20.08.2020

Trade name: P420 HYFLASH 2K VOC PRIMER GREY

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling No special precautions are necessary if used correctly. • Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

7727	7-43-7 barium sulphate, natural	
WEL	Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust	
1332	2-58-7 Kaolin	
WEL	Long-term value: 2 mg/m ³	
1330	-20-7 xylene	
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV	
123-8	86-4 n-butyl acetate	
WEL	. Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
108-0	65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk	
112-0	07-2 2-butoxyethyl acetate	
WEL	Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk	



Printing date 08.01.2021

HYMA

Revision: 20.08.2020

Trade name: P420 HYFLASH 2K VOC PRIMER GREY

	(Contd. of page 4)
Ingred	ients with biological limit values:
1330-2	0-7 xylene
BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift Parameter: methyl hippuric acid
Additic	onal information: The lists valid during the making were used as basis.
	posure controls
	nal protective equipment:
	al protective and hygienic measures:
	iately remove all soiled and contaminated clothing
	nands before breaks and at the end of work.
Respir	atory protection: Not required.
Protec	tion of hands:
db	
-Ma	Protoctive player
	Protective gloves
The alc	ove material has to be impermeable and resistant to the product/ the substance/ the preparation.
	missing tests no recommendation to the glove material can be given for the product/ the
	ation/ the chemical mixture.
	on of the glove material on consideration of the penetration times, rates of diffusion and the
degrad	
	al of gloves
	lection of the suitable gloves does not only depend on the material, but also on further marks o
	and varies from manufacturer to manufacturer. As the product is a preparation of severa
• •	and valles from manufacturer to manufacturer. As the product is a preparation of severa

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 6)

GB

Printing date 08.01.2021

Revision: 20.08.2020

Trade name: P420 HYFLASH 2K VOC PRIMER GREY

(Contd. of page 5)

9.1 Information on basic physical and	chemical properties	
General Information		
Appearance:		
Form:	Liquid	
Colour:	Grey	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range		
Flash point:	25 ℃	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	370 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation of explosivative air/vapour mixtures are possible.	
Explosion limits:		
Lower:	1.1 Vol %	
Upper:	7 Vol %	
Vapour pressure at 20 °C:	6.7 hPa	
Density at 20 °C:	1.64 g/cm³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:	N	
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	28.2 %	
VOC (EC)	461.7 g/l	
Solids content:	75.3 %	

Printing date 08.01.2021

Trade name: P420 HYFLASH 2K VOC PRIMER GREY

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification: 64742-95-6 Solvent naphtha (petroleum), light arom. Oral LD50 >6.800 mg/kg (rat)

		/ 0.01 /
Dermal	LD50	>3,400 mg/kg (rab)

Inhalative	LC50/4 h	>10.2 mg/l (rat)
------------	----------	------------------

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

· Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- \cdot Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)

Page 7/10

Revision: 20.08.2020

(Contd. of page 6)

Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.01.2021

Revision: 20.08.2020

Trade name: P420 HYFLASH 2K VOC PRIMER GREY

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name		
ADR	1263 PAINT	
IMDG, IATA	PAINT	
14.3 Transport hazard class(es) ADR, IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	

Printing date 08.01.2021

Revision: 20.08.2020

Trade name: P420 HYFLASH 2K VOC PRIMER GREY

	(Contd. of page 8)
· 14.4 Packing group · ADR, IMDG, IATA	III
 14.5 Environmental hazards: Marine pollutant: 	No
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category 	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
 14.7 Transport in bulk according to Annex II o Marpol and the IBC Code 	f Not applicable.
· Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3
 Transport category Tunnel restriction code 	3 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
- None of the ingredients is listed.

(Contd. on page 10)

GB

Printing date 08.01.2021

· Relevant phrases

Revision: 20.08.2020

Trade name: P420 HYFLASH 2K VOC PRIMER GREY

(Contd. of page 9) • **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. · Department issuing SDS: Product safety department · Contact: N/A · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - inhalation - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 GB