Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

SECTION 1: Identification of the substance/mixture and of the company, undertaking

· 1.1 Product identifier

· Trade name: P82 2K EASY PRIMER

- · Article number: P82
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

use as industrial paint
• Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- **Product category** PC9a Coatings and paints, thinners, paint removers
- PC9b Fillers, putties, plasters, modelling clay

· Application of the substance / the mixture refer to the relevant Technical Data Sheet

 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559 info@hymax.biz

· Further information obtainable from: Product Safety Department

• 1.4 Emergency telephone number: +33 (0)6 07 87 13 41

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

С Снѕот

Skin Irrit. 2 H315 Causes skin irritation.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Page 2/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: P82 2K EASY PRIMER

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 · Signal word Warning · Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P501 Dispose of contents/container in accordance with local/regional/national/ international regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

	 Dangerous components: 		
ſ	CAS: 1330-20-7	xylene	>10- <i>≤</i> 25%
	EINECS: 215-535-7	🚸 Flam. Liq. 3, H226; 伙 Acute Tox. 4, H312; Acute Tox. 4,	
	Reg.nr.: 01-2119486136-34	H332; Skin Irrit. 2, H315	
	05-2116602925-45		
	01-2119488216-32		
ľ		(C	ontd. on page 3)
			00

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: P82 2K EASY PRIMER

	(C	ontd. of page 2)
CAS: 123-86-4	n-butyl acetate	>2.5- <i>≤</i> 10%
EINECS: 204-658-1	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
Reg.nr.: 01-2119485493-29		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	<i>≤</i> 2.5%
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226	
Reg.nr.: 01-2119475791-29		
05-2116413226-56		
CAS: 117-84-0	dioctyl phthalate	<i>≤</i> 2.5%
EINECS: 204-214-7	🗞 Repr. 2, H361	
CAS: 100-41-4	ethylbenzene	<i>≤</i> 2.5%
EINECS: 202-849-4	🚯 Flam. Liq. 2, H225; 🚸 STOT RE 2, H373; Asp. Tox. 1,	
Reg.nr.: 01-2119489370-35	♦ Flam. Liq. 2, H225; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H332	
	r the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Printing date 25.09.2019

Revision: 06.05.2019

Page 4/11

Trade name: P82 2K EASY PRIMER

(Contd. of page 3)

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose characterial as waste according to item 13.
- Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling No special precautions are necessary if used correctly.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters
Ingredients with limit values that require monitoring at the workplace:
1330-20-7 xylene
WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
123-86-4 n-butyl acetate
WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
108-65-6 2-methoxy-1-methylethyl acetate
WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm
(Contd. on page 5)

Printing date 25.09.2019

Revision: 06.05.2019

(Contd. of page 4)

Trade name: P82 2K EASY PRIMER

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

 General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

GB

Printing date 25.09.2019

Revision: 06.05.2019

(Contd. of page 5)

Trade name: P82 2K EASY PRIMER

· Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Liquid
Colour:	Grey
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	e: 124 °C
Flash point:	25 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
Vapour pressure at 20 °C:	6.7 hPa
Density at 20 °C:	1.663 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
	(Contd. on page

Page 6/11

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: P82 2K EASY PRIMER

	(Contd. of page 6
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	22.8 %	
VÕC (EC)	379.0 g/l	
Solids content:	75.3 %	
 9.2 Other information 	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

• STOT-single exposure Based on available data, the classification criteria are not met.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB

Page 7/11

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: P82 2K EASY PRIMER

· Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. of page 7)

Page 8/11

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name		
ADR	1263 PAINT	
IMDG, IATA	PAINT	

Page 9/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: P82 2K EASY PRIMER

	(Contd. of page
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	<i>III</i>
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E,S-E
Stowage Category	A
14.7 Transport in bulk according to Anr Marpol and the IBC Code	nex II of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
Transport optogory	Maximum net quantity per outer packaging: 1000 m 3
Transport category Tunnel restriction code	J D/E
IMDG Limited quantities (LQ)	54
Excepted quantities (EQ)	Code: E1
LAUGHEN YUANINES (LA)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 m

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: P82 2K EASY PRIMER

(Contd. of page 9)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 52c
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· Department issuing SDS: Product safety department

· Contact: N/A

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 11)

Printing date 25.09.2019

HYMA)

Revision: 06.05.2019

(Contd. of page 10)

Page 11/11

Trade name: P82 2K EASY PRIMER

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

GB