

Page 1/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier
· Trade name: <u>S19 P.U. THINNER FAST</u>
<ul> <li>Article number: S19</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint</li> <li>Sector of Use</li> <li>SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites</li> <li>SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)</li> <li>Product category</li> <li>PC9a Coatings and paints, thinners, paint removers</li> <li>PC9b Fillers, putties, plasters, modelling clay</li> <li>Application of the substance / the mixture refer to the relevant Technical Data Sheet</li> </ul>
<ul> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier:         <ul> <li>P.O. Box 7623</li> <li>Beirut LEBANON</li> <li>info@hymax.biz</li> <li>Générale de Peinture, 70 Rue Cortambert 75116 Paris, France</li> <li>Tel:+33(0)175293559</li> </ul> </li> </ul>
<ul> <li>Further information obtainable from: Product Safety Department</li> <li>1.4 Emergency telephone number: +33 (0)6 07 87 13 41</li> </ul>
SECTION 2: Hazards identification
• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 GHS02 flame
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
GHS08 health hazard
Repr. 2 H361d Suspected of damaging the unborn child.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. (Contd. on page 2)
(Conid. on page 2) 



Page 2/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

# Trade name: S19 P.U. THINNER FAST

•	(Contd. of page
GHS0	)7
Skin Irrit. 2 H.	315 Causes skin irritation.
STOT SE 3 H	
SIUI SE 3 H	336 May cause drowsiness or dizziness.
2.2 Label elem	
	ording to Regulation (EC) No 1272/2008 classified and labelled according to the CLP regulation.
Hazard pictog	
	$\mathbf{A}$
<u> </u>	
$\nabla$ $\nabla$	
GHS02 GHS	07 GHS08
Signal word D	anger
Hazard-detern	nining components of labelling:
toluene	
n-butyl acetate	
Hazard statem	
H225 Highly f	lammable liquid and vapour.
H315 Causes	skin irritation.
	ted of damaging the unborn child.
	use drowsiness or dizziness.
	use damage to organs through prolonged or repeated exposure.
	fatal if swallowed and enters airways.
Precautionary	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103 P301+P310	Read label before use. IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse si
	with water/shower.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/nation
	international regulations.
2.3 Other haza	
	T and vPvB assessment
PBT: Not appli	
	(Contd. on page

(Contd. on page 3)

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

### Trade name: S19 P.U. THINNER FAST

· vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

#### · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

<ul> <li>Dangerous components:</li> </ul>		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate � Flam. Liq. 3, H226; � STOT SE 3, H336	>25- <i>≤</i> 50%
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51	toluene	>25- <i>≤</i> 50%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56	2-methoxy-1-methylethyl acetate 🚸 Flam. Liq. 3, H226	>10- <i>≤</i> 25%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

# SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 4)



(Contd. of page 2)

Page 3/11



Page 4/11

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

### Trade name: S19 P.U. THINNER FAST

(Contd. of page 3)

# SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

# SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
   Protect against electrostatic charges.
   Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 5)

- GB

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

(Contd. of page 4)

Page 5/11

# Trade name: S19 P.U. THINNER FAST

• Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

#### · 8.1 Control parameters

· Ingre	dients with limit values that require monitoring at the workplace:
123-8	36-4 n-butyl acetate
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
108-8	38-3 toluene
WEL	Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk
108-6	5-6 2-methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk
· Addi	tional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

Personal protective equipment:

 General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.

• **Respiratory protection:** In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

(Contd. on page 6)



Page 6/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

#### Trade name: S19 P.U. THINNER FAST

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION	0. Dhycical	and chomical	nronortiae
SLUIUN	9. FIIVSIGAI	and chemical	

General Information Appearance:		
Form:	Liquid	
Colour:	Colourless	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : 110 °C	
Flash point:	4 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	315 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	



Page 7/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

### Trade name: S19 P.U. THINNER FAST

	(Contd. of page 6)
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<ul> <li>Explosion limits: Lower: Upper:</li> </ul>	1.2 Vol % 10.8 Vol %
· Vapour pressure at 20 °C:	29 hPa
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	0.88 g/cm <sup>3</sup> Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
<ul> <li>Solvent content:</li> <li>Organic solvents:</li> <li>VOC (EC)</li> <li>9.2 Other information</li> </ul>	100.0 % 880.0 g/l No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB



Page 8/11

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

### Trade name: S19 P.U. THINNER FAST

108-88-3	toluene	
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)
<ul> <li>Primary in</li> <li>Skin corr</li> <li>Causes slip</li> </ul>		ation
<ul> <li>Germ cell</li> <li>Carcinog</li> <li>Reproduct</li> <li>Suspected</li> <li>STOT-sin</li> <li>May cause</li> </ul>	I mutageni enicity Bas ctive toxic d of damag gle expos e drowsine peated exp	ing the unborn child. <b>ure</b> ss or dizziness.

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

(Contd. on page 9)

GB

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

# Trade name: S19 P.U. THINNER FAST

(Contd. of page 8)

Page 9/11

# SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

# · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information
-----------------------------------

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263	
<ul> <li>· 14.2 UN proper shipping name</li> <li>· ADR</li> <li>· IMDG, IATA</li> </ul>	1263 PAINT PAINT	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA		
· Class	3 Flammable liquids.	
· Label	3	
· 14.4 Packing group · ADR, IMDG, IATA	11	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
· 14.6 Special precautions for user	Warning: Flammable liquids.	
Danger code (Kemler):	33	
EMS Number:	F-E, <u>S-E</u>	
· Stowage Category	В	
· 14.7 Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
		(Contd. on page 10





Page 10/11

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S19 P.U. THINNER FAST

	(Contd. of page S
· Transport/Additional information:	
· ADR	
<ul> <li>Limited quantities (LQ)</li> </ul>	5L
<ul> <li>Excepted quantities (EQ)</li> </ul>	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

# SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

(Contd. on page 11)

GB



Г

Page 11/11

# **Safety data sheet** according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

	(Contd. of page	: 10
H373	May cause damage to organs through prolonged or repeated exposure.	
Departi Contac	nent issuing SDS: Product safety department +· N/A	
	iations and acronyms:	
RID: Règi the Intern	ement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concern ational Transport of Dangerous Goods by Rail) rmational Civil Aviation Organisation	nin
ADR: Acc Internatio	cord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning nal Carriage of Dangerous Goods by Road) ernational Maritime Code for Dangerous Goods	th
	rnational Air Transport Association	
GHS: Glo	bally Harmonised System of Classification and Labelling of Chemicals	
	European Inventory of Existing Commercial Chemical Substances	
	European List of Notified Chemical Substances	
	mical Abstracts Service (division of the American Chemical Society)	
	atile Organic Compounds (USA, EU)	
	hal concentration, 50 percent hal dose, 50 percent	
	istent, Bioaccumulative and Toxic	
	/ Persistent and very Bioaccumulative	
	2: Flammable liquids – Category 2	
	3: Flammable liquids – Category 3	
	2: Skin corrosion/irritation – Category 2	
	Peproductive toxicity – Category 2	
STOT SE	3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE	2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox.	1: Aspiration hazard – Category 1	