



Printing date 24.09.2019 Revision: 20.09.2019

# SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier THINNERS
- · Trade name: S241 GENCLEAN
- · Article number: S241
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

use as degreaser

· Product category

PC9a Coatings and paints, thinners, paint removers

PC9b Fillers, putties, plasters, modelling clay

- · Application of the substance / the mixture refer to the relevant Technical Data Sheet use by wiping
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

P.O. Box 7623

Beirut LEBANON

info@hymax.biz

Générale de Peinture, 70 Rue Cortambert 75116 Paris, France

Tel:+33(0)175293559

- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number:

+33 (0)6 07 87 13 41

During normal opening times:(961) 9 925990 /1/2

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Muta. 1B H340 May cause genetic defects.

(Contd. on page 2)





Printing date 24.09.2019 Revision: 20.09.2019

Trade name: S241 GENCLEAN

(Contd. of page 1)

Carc. 1B H350 May cause cancer.

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy Naphtha (petroleum), hydrodesulfurized heavy

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

(Contd. on page 3)



Page 3/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 20.09.2019

Trade name: S241 GENCLEAN

(Contd. of page 2)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous	components:	
64742-48-9	Naphtha (petroleum), hydrotreated heavy	>50-≤100%
	♦ Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304	
1330-20-7	xylene	>10- <i>≤</i> 25%
	<ul> <li>Flam. Liq. 3, H226;</li> <li>Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit.</li> <li>H315</li> </ul>	
67-63-0	propan-2-ol	>2.5-≤10%
	🚸 Flam. Liq. 2, H225; 🐠 Eye Irrit. 2, H319; STOT SE 3, H336	
123-86-4	n-butyl acetate	>2.5-≤10%
	🚸 Flam. Liq. 3, H226; ∿ STOT SE 3, H336	
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	>2.5- <i>≤</i> 10%
	🚸 Flam. Liq. 3, H226; 🚸 STOT RE 1, H372; Asp. Tox. 1, H304	
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
	♦ Acute Tox. 4, H332; STOT SE 3, H335	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)



Page 4/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 20.09.2019

Trade name: S241 GENCLEAN

(Contd. of page 3)

· **4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

  During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 5)



Page 5/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 20.09.2019

Trade name: S241 GENCLEAN

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

o. i Control para	O. I Control parameters		
· Ingredients with	· Ingredients with limit values that require monitoring at the workplace:		
1330-20-7 xylene	е		
IOELV (EU)	Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin		
-	htha (petroleum), hydrodesulfurized heavy		
TLV/TWA (Leban	non) Short-term value: 525 mg/m³ Long-term value: 525 mg/m³		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

- LB/AR -



Page 6/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 20.09.2019

Trade name: S241 GENCLEAN

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product the preparation the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Colour: According to product description

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 82 °C

· Flash point: 24 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 240 °C

· **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

(Contd. on page 7)

LB/AR





Printing date 24.09.2019 Revision: 20.09.2019

Trade name: S241 GENCLEAN

	(Contd. of page
Explosive properties:	Product is not explosive. However, formation of explosivair/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	7 Vol %
· Vapour pressure at 20 °C:	6.7 hPa
Density at 20 °C:	0.80735 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	807.3 g/l
· 9.2 Other information	No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)





Printing date 24.09.2019 Revision: 20.09.2019

Trade name: S241 GENCLEAN

		(Contd. of page 7)
· LD/LC50	values rel	evant for classification:
64742-48	·9 Naphtha	a (petroleum), hydrotreated heavy
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)
1330-20-7	xylene	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
64742-95	6 Solvent	naphtha (petroleum), light arom.
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- · Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity

May cause genetic defects.

· Carcinogenicity

May cause cancer.

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

May cause damage to the central nervous system through prolonged or repeated exposure.

· Aspiration hazard

May be fatal if swallowed and enters airways.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 9)





Printing date 24.09.2019 Revision: 20.09.2019

Trade name: S241 GENCLEAN

(Contd. of page 8)

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	on	
· 14.1 UN-Number · ADR, IMDG, IATA	1263 UN1263	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	un 1263 1263 PAINT PAINT	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA		
· Class	3 Flammable liquids.	
· Class · Label	3 Flammable liquids.	
· 14.4 Packing group · ADR, IMDG, IATA	III	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Warning: Flammable liquids.	
· Danger code (Kemler):	30	
EMS Number:	F-E, <u>S-E</u>	
· Stowage Category	$\boldsymbol{A}$	

ontd. on page 10



Page 10/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 20.09.2019

Trade name: S241 GENCLEAN

· 14.7 Transport in bulk according to Anno Marpol and the IBC Code	ex II of Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 n
Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 n
UN "Model Regulation":	UN 1263 PAINT, 3, III

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

LB/AR



Page 11/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 20.09.2019

Trade name: S241 GENCLEAN

(Contd. of page 10)

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

#### · Department issuing SDS: Product safety department

· Contact: N/A

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1B: Carcinogenicity - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

LB/AR