



S201 - 2K Blending Thinner

Description:

This product has been developed to assist the painter in the blending out process of 2K Colours.

Suitable: For Hyflow 2K systems

Mixing ratio by volume: Add 500% to ready to spray material. Reduce air pressure to 1.5 bars.

Application:

- Activate, thin and apply 2k colors and clears in medium coats to opacity with no flash between coats.
- Empty the spray gun leaving little amount of activated paint or clear, with no flash off between coats, add 100% of S201, shake and apply in light to medium coats to melt down the overspray on the edges.
- Add another 200% of S201 to spray gun, shake and melt down the remaining overspray with light to medium coats.
- Finally, add S201 to emptied spray gun and apply to the rest of scuffed mat area.
- For spot repair start and finish with 1.5Bar.
- For normal blending keep the air pressure to 2 bar and reduce to 1.5 when applying the S201.
- All application should be within the sanded/scuffed area.

Important Remarks:

For professional use only.

Cleaning of equipment:

Clean after use with HymaxCleaning thinner.



Wear suitable protection



S201 - 2K Blending Thinner

Flash Point: 14°C

Specific gravity: 0.88778 g/cm³

SDS: See the safety data sheet

The Warnings displayed on the product labels should be followed. The information contained here represents the current state of our knowledge and is intended as a guide to our products and their uses.

Product Data Sheet