



Printing date 24.09.2019 Revision: 19.09.2019

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier HARDENERS
- · Trade name: H051 P.U. HARDENER FAST
- · Article number: H051
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against use as paint hardener
- · Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet refer to the relevant Technical Data Sheet
- 1.3 Details of the supplier of the safety data sheet General Paint Co.

-Safety Department-

For additional information, please consult our Internet Site www.hymax.biz

· Manufacturer/Supplier:

P.O. Box 7623
Beirut LEBANON
info@hymax.biz
Générale de Peinture, 70 Rue Cortambert 75116 Paris, France
Tel:+33(0)175293559

- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number:

+33 (0)6 07 87 13 41

During normal opening times:(961) 9 925990 /1/2

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 2)





Printing date 24.09.2019 Revision: 19.09.2019

Trade name: H051 P.U. HARDENER FAST

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Aromatic Polyisocyanate

n-butyl acetate

m-tolylidene diisocyanate

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

(Contd. on page 3)



Page 3/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 19.09.2019

Trade name: H051 P.U. HARDENER FAST

(Contd. of page 2)

P501 Dispo

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
123-86-4	n-butyl acetate	>25- <i>≤</i> 50%	
	🚸 Flam. Liq. 3, H226; 🕠 STOT SE 3, H336		
528598-79-0	3598-79-0 Aromatic Polyisocyanate		
	🕸 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317		
53317-61-6	aromatic poliyisocyanate	>10- <i>≤</i> 25%	
	♦ Flam. Liq. 2, H225; ♦ Acute Tox. 4, H332; Eye Irrit. 2, H319		
1330-20-7	xylene	>2.5- <i>≤</i> 10%	
	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315		
108-65-6	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%	
	🚸 Flam. Liq. 3, H226		
28182-81-2	Homopolymer of hexamethylene diisocyanate	>2.5- <i>≤</i> 10%	
	♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335		
141-78-6	ethyl acetate	>2.5- <i>≤</i> 10%	
	🚸 Flam. Liq. 2, H225; 🐠 Eye Irrit. 2, H319; STOT SE 3, H336		
112-07-2	2-butoxyethyl acetate	<i>≤</i> 2.5%	
	♦ Acute Tox. 4, H312; Acute Tox. 4, H332		
26471-62-5	m-tolylidene diisocyanate	<i>≤</i> 2.5%	
	Acute Tox. 2, H330; & Resp. Sens. 1, H334; Carc. 2, H351; O Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412		
A delitie e e l'in	Aquatic Officials, 11412		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

LB/AR



Page 4/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 19.09.2019

Trade name: H051 P.U. HARDENER FAST

(Contd. of page 3)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full let
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)



Page 5/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 19.09.2019

Trade name: H051 P.U. HARDENER FAST

See Section 13 for disposal information.

(Contd. of page 4)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Skin

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control par	8.1 Control parameters Ingredients with limit values that require monitoring at the workplace:				
· Ingredients wit					
1330-20-7 xylene					
Lo	hort-term value: 442 mg/m³, 100 ppm ong-term value: 221 mg/m³, 50 ppm kin				
108-65-6 2-met	thoxy-1-methylethyl acetate				
Lo	hort-term value: 550 mg/m³, 100 ppm ong-term value: 275 mg/m³, 50 ppm kin				
141-78-6 ethyl	acetate				
	hort-term value: 1468 mg/m³, 400 ppm ong-term value: 734 mg/m³, 200 ppm				
112-07-2 2-but	toxyethyl acetate				
	hort-term value: 333 mg/m³, 50 ppm ong-term value: 133 mg/m³, 20 ppm				

(Contd. on page 6)



Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 19.09.2019

Trade name: H051 P.U. HARDENER FAST

(Contd. of page 5)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

(Contd. on page 7)





Printing date 24.09.2019 Revision: 19.09.2019

Trade name: H051 P.U. HARDENER FAST

	(Contd. of page
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	
Flash point:	5 ℃
Flammability (solid, gas):	Not applicable.
Ignition temperature:	315 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosi
	air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	1.02697 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	55.6 %
VOC (EC)	570.8 g/l
Solids content:	44.4 %
9.2 Other information	No further relevant information available.

LB/AR



Page 8/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 19.09.2019

Trade name: H051 P.U. HARDENER FAST

(Contd. of page 7)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 9)



Page 9/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 19.09.2019

Trade name: H051 P.U. HARDENER FAST

(Contd. of page 8)

- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA · Label	3	
· 14.4 Packing group · ADR, IMDG, IATA	11	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user · EMS Number:	Not applicable. F-E, <u>S-E</u>	
	(Contd. on page	

ontd. on page 10)





Printing date 24.09.2019 Revision: 19.09.2019

Trade name: H051 P.U. HARDENER FAST

	(Contd. of page
Stowage Category	В
· 14.7 Transport in bulk according to A Marpol and the IBC Code	Annex II of Not applicable.
Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

(Contd. on page 11)



Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019 Revision: 19.09.2019

Trade name: H051 P.U. HARDENER FAST

(Contd. of page 10)

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

· Contact: N/A

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

LB/AR