

Page 1/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.09.2019

Revision: 06.05.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier BASECOAT B-SERIES
· Trade name: <u>B180 REDDISH BLUE</u>
<ul> <li>Article number: B180</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. use as automotive refinish paint</li> <li>Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)</li> <li>Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay</li> <li>Application of the substance / the mixture refer to the relevant Technical Data Sheet refer to the relevant Technical Data Sheet</li> </ul>
<ul> <li>1.3 Details of the supplier of the safety data sheet General Paint Co. S.A.L.</li> <li>-Safety Department-</li> </ul>
For further information, please consult our Internet site www.hymax.biz • <i>Manufacturer/Supplier:</i> P.O. Box 7623 Beirut LEBANON info@hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559
<ul> <li>Further information obtainable from: Product Safety Department</li> <li>1.4 Emergency telephone number: +33 (0)6 07 87 13 41</li> <li>During normal opening times:(961) 9 925990 /1/2</li> </ul>
SECTION 2: Hazards identification • 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

(Contd. on page 2)



Page 2/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.09.2019

Revision: 06.05.2019

Trade name: B180 REDDISH BLUE

	(Contd. of page
$\mathbf{\Lambda}$	
	H315 Causes skin irritation.
S101 SE 3	H336 May cause drowsiness or dizziness.
· 2.2 Label el	
	ccording to Regulation (EC) No 1272/2008
	is classified and labelled according to the CLP regulation.
<ul> <li>Hazard pict</li> </ul>	ograms
$\wedge$	$\wedge$
	•
GHS02 G	HS07
G11302 G	1307
· Signal word	l Warning
Hazard-det	ermining components of labelling:
n-butyl aceta	
· Hazard stat	
	nable liquid and vapour.
	es skin irritation.
H336 May c	ause drowsiness or dizziness.
	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition source
P241	No smoking. Use explosion-proof electrical/ventilating/lighting equipment.
P241 P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse sk
1 30377 307	with water/shower.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national
	international regulations.
2.3 Other h	•
Results of I	PBT and vPvB assessment
· PBT: Not ap	pplicable.
• <b>vPvB:</b> Not a	

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 20.09.2019

Revision: 06.05.2019

Trade name: B180 REDDISH BLUE

(Contd. of page 2)

Page 3/11

## SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous	components:	
123-86-4	n-butyl acetate	>50- <i>≤</i> 100%
	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
1330-20-7	xylene	>10- <i>≤</i> 25%
	Flam. Liq. 3, H226; (1) Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
	Acute Tox. 4, H332; STOT SE 3, H335	
108-65-6	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%
	🚸 Flam. Liq. 3, H226	
100-41-4	ethylbenzene	<i>≤</i> 2.5%
	🚸 Flam. Liq. 2, H225; 🚸 STOT RE 2, H373; Asp. Tox. 1, H304; 🚸 Acute Tox. 4, H332	
123-42-2	diacetone alcohol, technical	<i>≤</i> 2.5%
	🔶 Eye Irrit. 2, H319	

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

according to 1907/2006/EC, Article 31

Printing date 20.09.2019

Revision: 06.05.2019

(Contd. of page 3)

Page 4/11

Trade name: B180 REDDISH BLUE

- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• **6.3** Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

# SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 20.09.2019

Revision: 06.05.2019

Page 5/11

#### Trade name: B180 REDDISH BLUE

	(Contd. of page 4)
· 8.1 Control	parameters
· Ingredients	with limit values that require monitoring at the workplace:
1330-20-7 x	ylene
IOELV (EU)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 221 mg/m³, 50 ppm Skin
108-65-6 2-	methoxy-1-methylethyl acetate
IOELV (EU)	Short-term value: 550 mg/m³, 100 ppm
. ,	Long-term value: 275 mg/m³, 50 ppm Skin
100-41-4 et	hylbenzene
IOELV (EU)	Short-term value: 884 mg/m³, 200 ppm
. ,	Long-term value: 442 mg/m³, 100 ppm Skin
· Additional i	<b>information:</b> The lists valid during the making were used as basis.
· 8.2 Exposu	re controls
	rotective equipment:
	otective and hygienic measures:
	from foodstuffs, beverages and feed.
Immediately	remove all soiled and contaminated clothing
Wash hands	s before breaks and at the end of work.
Avoid conta	ct with the skin.
	ct with the eyes and skin.
<ul> <li>Respiratory</li> </ul>	
	rief exposure or low pollution use respiratory filter device. In case of intensive or longe e self-contained respiratory protective device.
· Protection	of hands:





Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 20.09.2019

Trade name: B180 REDDISH BLUE

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

SI

Tightly sealed goggles

ECTION 9:	Physical	and ch	emical i	propert	ies

9.1 Information on basic physical and o General Information	nemical properties
· Appearance:	
Form:	Liquid
Colour:	Light blue
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 124 °C
· Flash point:	27 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	315 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	0.953 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
	(Contd. on page 7

Revision: 06.05.2019

(Contd. of page 5)

Page 6/11



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.09.2019

Revision: 06.05.2019

Page 7/11

#### Trade name: B180 REDDISH BLUE

	(Contd. of pag
· Evaporation rate	Not determined.
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
<ul> <li>Solvent content: Organic solvents: VOC (EC)</li> </ul>	76.1 % 725.3 g/l
Solids content: · 9.2 Other information	23.9 % No further relevant information available.

#### SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

1330-20-7	' xylene	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
64742-95-	6 Solvent	naphtha (petroleum), light arom.
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
		(Contd. on page 8



LB/AR -



Page 8/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.09.2019

Revision: 06.05.2019

(Contd. of page 7)

#### Trade name: B180 REDDISH BLUE

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 9)

LB/AR

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.09.2019

Revision: 06.05.2019

Trade name: B180 REDDISH BLUE

(Contd. of page 8)

Page 9/11

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids. F-E, <u>S-E</u> A
14.7 Transport in bulk according to Ann Marpol and the IBC Code	<b>ex II of</b> Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity par outer packaging: 1000 m
Transport category Tunnel restriction code	Maximum net quantity per outer packaging: 1000 n 3 D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
	(Contd. on page 1



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.09.2019

Revision: 06.05.2019

(Contd. of page 9)

Page 10/11

#### Trade name: B180 REDDISH BLUE

· UN "Model Regulation":

UN 1263 PAINT, 3, III

#### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- Abbreviations and acronyms:
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 11)



Printing date 20.09.2019

HYM

Revision: 06.05.2019

Page 11/11

## Trade name: B180 REDDISH BLUE

(Contd. of page 10)

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

LB/AR