

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier Basecoat B-series
· Trade name: B788 XIRALLIC BLUE
 Article number: B788 1.2 Relevant identified uses of the substance or mixture and uses advised against use as automotive refinish paint Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet refer to the Technical Data Sheet
 • 1.3 Details of the supplier of the safety data sheet General Paint Co. S.A.L -Safety Department-
For further information, please consult our Internet site www.hymax.biz • <i>Manufacturer/Supplier:</i> P.O. Box 7623 Beirut LEBANON info@hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559
 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 During normal opening times:(961) 9 925990 /1/2
SECTION 2: Hazards identification

· Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

(Contd. on page 2)




Page 2/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

Trade name: B788 XIRALLIC BLUE



(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

Trade name: B788 XIRALLIC BLUE

(Contd. of page 2)

Page 3/11

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous 	components:	
123-86-4	n-butyl acetate	>50- <i>≤</i> 100%
	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
1330-20-7	xylene	>2.5- <i>≤</i> 10%
64742-95-6	Solvent naphtha (petroleum), light arom. � Acute Tox. 4, H332; STOT SE 3, H335	>2.5- <i>≤</i> 10%
108-65-6	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	>2.5- <i>≤</i> 10%
100-41-4	ethylbenzene � Flam. Liq. 2, H225; � STOT RE 2, H373; Asp. Tox. 1, H304; � Acute Tox. 4, H332	<i>≤</i> 2.5%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

Printing date 23.09.2019

Revision: 06.05.2019

Trade name: B788 XIRALLIC BLUE

5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

ECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5) LB/AR



(Contd. of page 3)

Page 4/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

(Contd. of page 4)

Page 5/11

Trade name: B788 XIRALLIC BLUE

Ingredients with limit values that require monitoring at the workplace:				
1330-20-7 x	ylene			
IOELV (EU)	Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin			
108-65-6 2-ı	nethoxy-1-methylethyl acetate			
IOELV (EU)	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin			
100-41-4 etl	nylbenzene			
IOELV (EU)	Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Skin			

· 8.2 Exposure controls

- Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 23.09.2019

Revision: 06.05.2019

(Contd. of page 5)

Page 6/11

Trade name: B788 XIRALLIC BLUE

· Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information	
Appearance:	
Form:	Liquid
Colour:	Blue
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling rang	e : 124 °C
Flash point:	27 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosiv air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.962 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.



LB/AR

Printing date 23.09.2019

Revision: 06.05.2019

Page 7/11

Trade name: B788 XIRALLIC BLUE

	(Contd. of pa	ige (
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	74.3 %	
VÕC (EC)	714.5 g/l	
Solids content:	25.7 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
1330-20-7 xylene			
Oral	LD50	4,300 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)	
Dermal	LD50	>3,400 mg/kg (rab)	
Inhalative	LC50/4 h	>10.2 mg/l (rat)	
· Primary in	Primary irritant effect:		

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

(Contd. on page 8)

Printing date 23.09.2019

Revision: 06.05.2019

(Contd. of page 7)

Page 8/11

Trade name: B788 XIRALLIC BLUE

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 9)

LB/AR

Printing date 23.09.2019

Revision: 06.05.2019

Trade name: B788 XIRALLIC BLUE

(Contd. of page 8)

14.1 UN-Number ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT	
14.3 Transport hazard class(es)		
ADR		
Class	3 Flammable liquids.	
Label	3	
· IMDG, IATA · Label	3	
• 14.4 Packing group • ADR, IMDG, IATA		
· 14.5 Environmental hazards: · Marine pollutant:	No	
 14.6 Special precautions for user EMS Number: Stowage Category 	Warning: Flammable liquids. F-E, <u>S-E</u> A	
· 14.7 Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
 Transport/Additional information: 		
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 r	
· Transport category · Tunnel restriction code	3 D/E	
· IMDG · Limited quantities (LQ)	5L	
	(Contd. on page	



00.00.2019

Page 9/11



Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

(Contd. of page 9)

Trade name: B788 XIRALLIC BLUE

Excepted quantities (EQ)

Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to the hearing organs through prolonged or repeated exposure. · Department issuing SDS: Product safety department · Contact: N/A · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 11)

LB/AR

Printing date 23.09.2019

Revision: 06.05.2019

Trade name: B788 XIRALLIC BLUE

(Contd. of page 10)

LB/AR

Page 11/11

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

