Page 1/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2020

Revision: 11.03.2020

### SECTION 1: Identification of the substance/mixture and of the company undertaking

undertaking	
• 1.1 Product identifier GE	ENROCK BASECOAT
· Trade name: <u>B870 BASE</u>	ECOAT DEEP BLACK
No further relevant informuse as automotive refnish • Sector of Use SU3 Industrial Uses: Uses SU22 Professional us craftsmen) • Product category PC9a Coatings and pain PC9b Fillers, putties, pla	paint s of substances such as or in preparations at industrial sites es: Public domain (administration, education, entertainment, services, ts, thinners, paint removers
• <b>Manufacturer/Supplier:</b> P.O. Box 7623 Beirut LEBANON info@hymax.biz	er of the safety data sheet Rue Cortambert 75116 Paris, France
<ul> <li>Further information obta</li> <li>1.4 Emergency telephon</li> <li>Phone : +33 (0)6 07 87 13</li> <li>During normal opening tin</li> </ul>	3 41
SECTION 2: Hazards	s identification
· 2.1 Classification of the	
Classification according	to Regulation (EC) No 1272/2008
flame	
Flam. Liq. 3 H226 Flamn	nable liquid and vanour



STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

<sup>-</sup> LB/AR

Page 2/10

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2020

Revision: 11.03.2020

(Contd. of page 1)

### Trade name: B870 BASECOAT DEEP BLACK

· Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:
- n-butyl acetate

### Hazard statements

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

- · Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

123-86-4	n-butyl acetate	>50-≤100%
	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
64742-95-6	Solvent naphtha (petroleum), light arom. � Acute Tox. 4, H332; STOT SE 3, H335	>2.5- <i>≤</i> 10%
	🚸 Acute Tox. 4, H332; STOT SE 3, H335	
1330-20-7		>2.5- <i>≤</i> 10%
	Flam. Liq. 3, H226; (1) Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	

Printing date 21.04.2020

Revision: 11.03.2020

#### Trade name: B870 BASECOAT DEEP BLACK

	(0	Contd. of page 2)
108-65-6	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%
	🚸 Flam. Liq. 3, H226	
100-41-4	ethylbenzene	<i>≤</i> 2.5%
	� Flam. Liq. 2, H225; � STOT RE 2, H373; Asp. Tox. 1, H304; ॒ Acute Tox. 4, H332	
<ul> <li>Additional information: For the wording of the listed hazard phrases refer to section 16.</li> </ul>		

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.

(Contd. on page 4)

LB/AR

Printing date 21.04.2020

Revision: 11.03.2020

(Contd. of page 3)

#### Trade name: B870 BASECOAT DEEP BLACK

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

#### · 8.1 Control parameters

123-86-4 n-b	utyl acetate	
	Short-term value: 723 mg/m³, 150 ppm	
	Long-term value: 241 mg/m³, 50 ppm	
1330-20-7 xy	lene	
	Short-term value: 442 mg/m³, 100 ppm	
	Long-term value: 221 mg/m³, 50 ppm	
,	Skin	
108-65-6 2-m	ethoxy-1-methylethyl acetate	
	Short-term value: 550 mg/m³, 100 ppm	
	Long-term value: 275 mg/m³, 50 ppm	
,	Skin	
100-41-4 eth	ylbenzene	
	Short-term value: 884 mg/m³, 200 ppm	
	Long-term value: 442 mg/m³, 100 ppm	
	Skin	
Additional in	formation: The lists valid during the making were used as basis.	
		(Contd. on page

Printing date 21.04.2020

Revision: 11.03.2020

(Contd. of page 4)

#### Trade name: B870 BASECOAT DEEP BLACK

- · 8.2 Exposure controls
  - · Personal protective equipment:
  - General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
  - · Respiratory protection:
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
  - · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

- $\cdot$  9.1 Information on basic physical and chemical properties
- · General Information

· Appearance:		
Form:	Liquid	
Colour:	Black	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	

(Contd. on page 6)

Printing date 21.04.2020

HYMA

Revision: 11.03.2020

### Trade name: B870 BASECOAT DEEP BLACK

	(Contd. of page
<ul> <li>Change in condition Melting point/freezing point: Initial boiling point and boiling range</li> </ul>	Undetermined. : 124-128 °C
· Flash point:	27 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	315 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	0.938 g/cm <sup>3</sup> Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
<ul> <li>Solvent content: Organic solvents: VOC (EC)</li> </ul>	71.0 % 666.1 g/l
Solids content: • 9.2 Other information	25.3 % No further relevant information available.

### SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 7)

<sup>· 10.2</sup> Chemical stability

LB/AR

Printing date 21.04.2020

Revision: 11.03.2020

(Contd. of page 6)

Page 7/10

### Trade name: B870 BASECOAT DEEP BLACK

· 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)

Dermal LD50 >3,400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.

(Contd. on page 8)

Printing date 21.04.2020

Revision: 11.03.2020

### Trade name: B870 BASECOAT DEEP BLACK

· 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION	14: Trai	nsport ir	oformation

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · IMDG, IATA	<i>III</i>
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No
<ul> <li>14.6 Special precautions for user</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids. A
<ul> <li>14.7 Transport in bulk according to Annex II o Marpol and the IBC Code</li> </ul>	f Not applicable.
· Transport/Additional information:	
· IMDG	5L
<ul> <li>Limited quantities (LQ)</li> </ul>	



Page 8/10

(Contd. of page 7)

Page 9/10

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2020

Revision: 11.03.2020

(Contd. of page 8)

#### Trade name: B870 BASECOAT DEEP BLACK

· Excepted quantities (EQ)

Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3

#### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 10)

LB/AR

### Page 10/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2020

Revision: 11.03.2020

#### Trade name: B870 BASECOAT DEEP BLACK

(Contd. of page 9)

LB/AR

LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Lig. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity - inhalation – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) - Category	2
Asp. Tox. 1: Aspiration hazard – Category 1	

