

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier Basecoat B-series
· Trade name: B930 METALLIC BASE VERY COARSE
 Article number: B930 1.2 Relevant identified uses of the substance or mixture and uses advised against use as automotive refinish paint Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet refer to the relevant Technical Data Sheet
 • 1.3 Details of the supplier of the safety data sheet General Paint Co. S.A.L -Safety Department-
For further information, please consult our Internet site www.hymax.biz • <i>Manufacturer/Supplier:</i> P.O. Box 7623 Beirut LEBANON info@hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559
 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 During normal opening times:(961) 9 925990 /1/2
SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

(Contd. on page 2)



Page 2/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

Trade name: B930 METALLIC BASE VERY COARSE

•	(Contd. of page 1
he he	alth hazard
Muta. 1B	H340 May cause genetic defects.
Carc. 1B	H350 May cause cancer.
\wedge	
$\langle ! \rangle$	
	H315 Causes skin irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.
· 2.2 Label el	ements
	ccording to Regulation (EC) No 1272/2008
	is classified and labelled according to the CLP regulation.
 Hazard pict 	ograms
	$\land \land$
. No l	
<u> </u>	
	\vee \vee
GHS02 G	HS07 GHS08
- · ·	
· Signal word	a Danger
· Hazard-det	ermining components of labelling:
n-butyl aceta	
Naphtha (pe	troleum), hydrotreated heavy
· Hazard stat	
H226 Flamn	nable liquid and vapour.
H315 Cause	es skin irritation.
H340 May c	ause genetic defects.
	ause cancer.
	ause drowsiness or dizziness.
	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources
	No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse ski
	with water/shower.
	(Contd. on page 3



Page 3/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

Trade name: B930 METALLIC BASE VERY COARSE

P405 P501 (Contd. of page 2)

Store locked up. Dispose of contents/container in accordance with local/regional/national/ international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

123-86-4	n-butyl acetate	>25- <i>≤</i> 50%
	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
1330-20-7	xylene	>10- <i>≤</i> 25%
	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
	♦ Acute Tox. 4, H332; STOT SE 3, H335	
100-41-4	ethylbenzene	>2.5- <i>≤</i> 10%
64742-48-9	Naphtha (petroleum), hydrotreated heavy	<i>≤</i> 2.5%
	🗞 Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

Page 4/11

Trade name: B930 METALLIC BASE VERY COARSE

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available. (Contd. of page 3)

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 5)

⁻ LB/AR

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

(Contd. of page 4)

Trade name: B930 METALLIC BASE VERY COARSE

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

IOELV (EU) Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin

100-41-4 ethylbenzene

IOELV (EU) Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Skin

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.
- · Respiratory protection:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)







Page 6/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

(Contd. of page 5)

Trade name: B930 METALLIC BASE VERY COARSE

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Colour: Silver grey · Odour: Characteristic · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition *Melting point/freezing point:* Undetermined. Initial boiling point and boiling range: 124 °C 24 °C · Flash point: · Flammability (solid, gas): Not applicable. 370 °C · Ignition temperature: · Decomposition temperature: Not determined. · Auto-ignition temperature: Product is not selfigniting. Product is not explosive. However, formation of explosive · Explosive properties: air/vapour mixtures are possible. (Contd. on page 7) I B/AR

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

Page 7/11

Trade name: B930 METALLIC BASE VERY COARSE

	(Contd. of pa	age
· Explosion limits:		
Lower:	1.1 Vol %	
Upper:	7.5 Vol %	
· Vapour pressure at 20 °C:	10.7 hPa	
· Density at 20 °C:	0.975 g/cm ³	
· Relative density	Not determined.	
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	72.9 %	
VÕC (EC)	710.4 g/l	
Solids content:	27.1 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

LB/AR



Page 8/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

Trade name: B930 METALLIC BASE VERY COARSE

	<u> </u>	(Contd. of page
		evant for classification:
1330-20-7	-	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
		naphtha (petroleum), light arom.
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
Germ cell May cause Carcinoge May cause Reproduce STOT-sin May cause STOT-rep	I mutagen e genetic d enicity e cancer. ctive toxic gle expos e drowsine peated exp	efects. ity Based on available data, the classification criteria are not met.
 12.1 Toxic Aquatic to 12.2 Pers 12.3 Bioa 12.4 Mobic Additionation General no Water haz Do not alked 	city oxicity: No istence ar ccumulati ility in soil al ecologic notes: card class 2 ow product	ological information o further relevant information available. ad degradability No further relevant information available. ve potential No further relevant information available. No further relevant information available. al information: 2 (German Regulation) (Self-assessment): hazardous for water to reach ground water, water course or sewage system. ater if even small quantities leak into the ground.
 12.5 Results PBT: Not vPvB: Not 	applicable	<u>).</u>
		(Contd. on page

(Contd. on page 9) - LB/AR -

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

Trade name: B930 METALLIC BASE VERY COARSE

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
 Recommendation
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1263	
	011/203	
14.2 UN proper shipping name		
ADR	1263 PAINT	
IMDG, IATA	PAINT	
14.3 Transport hazard class(es)		
ADR, IATA		
Class	3 Flammable liquids.	
Label	3	
IMDG		
Label	3	
14.4 Packing group		
ADR, IMDG, IĂTA	<i>III</i>	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Warning: Flammable liquids.	
EMS Number:	F-E,S-E	
Stowage Category	A	
14.7 Transport in bulk according to Annex	c II of	
Marpol and the IBC Code	Not applicable.	

HYMAX

(Contd. of page 8)

Page 9/11



Page 10/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

Trade name: B930 METALLIC BASE VERY COARSE

	(Contd. of page
· Transport/Additional information:	
· ADR · Limited quantities (LQ)	51
• Excepted quantities (EQ)	Code: E1 Maximum pot quantity por inpor packaging: 20 ml
 Transport category Tunnel restriction code 	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m 3 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).
- Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

(Contd. on page 11)

LB/AR



Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2019

Revision: 06.05.2019

Trade name: B930 METALLIC BASE VERY COARSE

	(Contd. of page
H226 Flammable liquid and vapour.	
H304 May be fatal if swallowed and enters airways.	
H312 Harmful in contact with skin.	
H315 Causes skin irritation.	
H332 Harmful if inhaled.	
H335 May cause respiratory irritation.	
H336 May cause drowsiness or dizziness.	
H340 May cause genetic defects.	
H350 May cause cancer. H373 May cause damage to the hearing organs through prolonged or re	oposted exposure
	epealeu exposure.
Department issuing SDS: Product safety department	
Contact: N/A	
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par the International Transport of Dangerous Goods by Rail)	r chemin de fer (Regulations Concern
ICAO: International Civil Aviation Organisation	
ADR: Accord européen sur le transport des marchandises dangereuses par Route	(European Agreement concerning
International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Muta. 1B: Germ cell mutagenicity – Category 1B Carc. 1B: Carcinogenicity – Category 1B	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	