

Page 1/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking
· 1.1 Product identifier PRIMERS
· Trade name: P43 2K RAPID PRIMER BLACK
<ul> <li>Article number: P43</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against use as paint primer</li> <li>Sector of Use</li> <li>SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites</li> <li>SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)</li> <li>Product category</li> <li>PC9a Coatings and paints, thinners, paint removers</li> <li>PC9b Fillers, putties, plasters, modelling clay</li> <li>Application of the substance / the mixture refer to the relevant Technical Data Sheet</li> </ul>
<ul> <li>• 1.3 Details of the supplier of the safety data sheet General Paint Co. S.A.L</li> <li>-Safety Department-</li> </ul>
For further information, please consult our Inernet site www.hymax.biz • <i>Manufacturer/Supplier:</i> P.O. Box 7623 Beirut LEBANON info@hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559
<ul> <li>Further information obtainable from: Product Safety Department</li> <li>1.4 Emergency telephone number:</li> <li>+33 (0)6 07 87 13 41</li> <li>During normal opening times:(961) 9 925990 /1/2</li> </ul>
SECTION 2: Hazards identification

· Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

(Contd. on page 2)



Page 2/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

### Trade name: P43 2K RAPID PRIMER BLACK

	(Contd. of pa
$\wedge$	
$\langle \rangle$	
$\sim$	
Skin Irrit. 2	H315 Causes skin irritation.
2.2 Label ele	ments
Labelling ac	cording to Regulation (EC) No 1272/2008
	s classified and labelled according to the CLP regulation.
Hazard picto	grams
	▲ ▲
GHS02 GH	IS07
<ul> <li>Signal word</li> </ul>	
<ul> <li>Hazard state</li> </ul>	
	able liquid and vapour.
	s skin irritation.
	ry statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sour
	No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+	P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse
	with water/shower.
	Dispass of contents/container in second-use with level/and/or the the
P501	Dispose of contents/container in accordance with local/regional/natio
P501	Dispose of contents/container in accordance with local/regional/natio international regulations.
P501 <b>2.3 Other ha</b> a	international regulations.

• **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients** 

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3) LB/AR

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

### Trade name: P43 2K RAPID PRIMER BLACK

1330-20-7	xylene	>10- <i>≤</i> 25%
	Flam. Liq. 3, H226; () Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
123-86-4	n-butyl acetate	>2.5- <i>≤</i> 10%
	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
64742-95-6	Solvent naphtha (petroleum), light arom.	<i>≤</i> 2.5%
	🚸 Acute Tox. 4, H332; STOT SE 3, H335	
100-41-4	ethylbenzene	<i>≤</i> 2.5%
	🚸 Flam. Liq. 2, H225; 🚸 STOT RE 2, H373; Asp. Tox. 1, H304; 🚸 Acute Tox. 4, H332	
77-58-7	dibutyltin dilaurate	<i>≤</i> 2.5%

### SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- $\cdot$  5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 4)



Page 3/11

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

(Contd. of page 3)

Page 4/11

### Trade name: P43 2K RAPID PRIMER BLACK

### · 5.3 Advice for firefighters

· Protective equipment: No special measures required.

**SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3** Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly. • Information about fire - and explosion protection:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
   Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

<ul> <li>Ingredients with limit values that require monitoring at the workplace:</li> </ul>		
1330-20-7 xylene		
IOELV (EU) Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin		
(Contd. on page 5)		





Page 5/11

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

(Contd. of page 4)

### Trade name: P43 2K RAPID PRIMER BLACK

### 100-41-4 ethylbenzene

IOELV (EU) Short-term value: 884 mg/m<sup>3</sup>, 200 ppm Long-term value: 442 mg/m<sup>3</sup>, 100 ppm Skin

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.
- · Respiratory protection: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 6)

LB/AR

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

### Trade name: P43 2K RAPID PRIMER BLACK

(Contd. of page 5)

Page 6/11

<ul> <li>9.1 Information on basic physical and General Information</li> </ul>	chemical properties
· Appearance:	
Form:	Liquid
Colour:	Black
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 124 °C
· Flash point:	25 °C
· Flammability (solid, gas):	Not applicable.
Ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
• Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosival air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
· Vapour pressure at 20 °C:	6.7 hPa
· Density at 20 °C:	1.465 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	24.4 %





Page 7/11

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

### Trade name: P43 2K RAPID PRIMER BLACK

		(Contd. of page 6)
VOC (EC)	357.7 g/l	
Solids content: • 9.2 Other information	75.3 % No further relevant information available.	

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
1330-20-7	1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)	
Dermal	LD50	>3,400 mg/kg (rab)	
Inhalative	LC50/4 h	>10.2 mg/l (rat)	
77-58-7 di	77-58-7 dibutyltin dilaurate		
Oral	LD50	175 mg/kg (rat)	
Duting a m s to	Drimory invitant offacts		

### · Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

 $\cdot$  CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

### Trade name: P43 2K RAPID PRIMER BLACK

(Contd. of page 7)

Page 8/11

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.
- SECTION 13: Disposal considerations
- · 13.1 Waste treatment methods
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
ADR, IMDG, IATA	UN1263	
• 14.2 UN proper shipping name		
ADR	1263 PAINT	
· IMDG, IATA	PAINT	



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

HVM

Revision: 06.05.2019

Page 9/11

Trade name: P43 2K RAPID PRIMER BLACK

	(Contd. of page
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
· Class	3 Flammable liquids.
Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	A/-
· Marine pollutant:	No
<ul> <li>14.6 Special precautions for user</li> <li>Danger code (Kemler):</li> </ul>	Warning: Flammable liquids. 30
· EMS Number:	50 F-E,S-E
· Stowage Category	A
· 14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per niner packaging: 30 mi Maximum net quantity per outer packaging: 1000 n
· Transport category	3
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 n
· UN "Model Regulation":	UN 1263 PAINT, 3, III

(Contd. on page 10)



Page 10/11

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

### Trade name: P43 2K RAPID PRIMER BLACK

(Contd. of page 9)

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- · **Department issuing SDS:** Product safety department
- · Contact: N/A
- Abbreviations and acronyms:
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent

(Contd. on page 11)

LB/AR



Page 11/11

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.09.2019

Revision: 06.05.2019

(Contd. of page 10)

LB/AR

### Trade name: P43 2K RAPID PRIMER BLACK

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic VPVB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Muta. 2: Germ cell mutagenicity – Category 2 Repr. 1B: Reproductive toxicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1