

Page 1/11

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 09/01/2017

1 Identification

- · Product identifier
- · Trade name: <u>S688 ANTI-SILICONE</u>
- · Article number: S688
- · Details of the supplier of the safety data sheet
- *Manufacturer/Supplier:* General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz
- Information department: Product Safety Department
 Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



- · Signal word Warning
- Hazard-determining components of labeling: n-butyl acetate
- Hazard statements
 Flammable liquid and vapor.
 May cause drowsiness or dizziness.

(Contd. on page 2)

acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 09/01/2017

Page 2/11

Trade name: S688 ANTI-SILICONE

(Contd. of page 1) · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 0Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 0 Health = 0FIRE 3 Fire = 3Reactivity = 0REACTIVITY 0 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)



Page 3/11

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 09/01/2017

Trade name: S688 ANTI-SILICONE

· Dangerous components:

123-86-4 n-butyl acetate

(Contd. of page 2)

>50-*≤*100%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Environmental process and a protection of the process of a provide the persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

(Contd. on page 4)

– ÚS

acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 09/01/2017

Trade name: S688 ANTI-SILICONE

· Protective Action Criteria for Chemicals	(Contd. of page 3
· PAC-1:	
123-86-4 n-butyl acetate	5 ppm
· PAC-2:	
123-86-4 n-butyl acetate	200 ppm
· PAC-3:	
123-86-4 n-butyl acetate	3000* ppm

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

- PEL Long-term value: 710 mg/m³, 150 ppm
- REL Short-term value: 950 mg/m³, 200 ppm
- Long-term value: 710 mg/m³, 150 ppm
- TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

US







Page 5/11

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 09/01/2017

Trade name: S688 ANTI-SILICONE

(Contd. of page 4)

- Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

General Information		
Appearance:	Linuid	
Form:	Liquid	
Color:	Clear	
Odor:	Characteristic	

Safety Data Sheet acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 09/01/2017

Trade name: S688 ANTI-SILICONE

	(Contd. of page
· Odor threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 124 °C (255.2 °F)
· Flash point:	27 °C (80.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive an vapor mixtures are possible.
· Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
 Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate 	0.88 g/cm ³ (7.3436 lbs/gal) Not determined. Not determined. Not determined.
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.
 Solvent content: Organic solvents: Coating VOC content: Material VOC content: 	90.9 % 90.91 % 800.0 g/l / 6.68 lb/gal 800.0 g/l / 6.68 lb/gal
Solids content: • Other information	0.0 % No further relevant information available.

Page 6/11



(Contd. on page 7)

acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 09/01/2017

Trade name: S688 ANTI-SILICONE

(Contd. of page 6)

Page 7/11

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

(Contd. on page 8)



Page 8/11

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 09/01/2017

Trade name: S688 ANTI-SILICONE

(Contd. of page 7) Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1123
· UN proper shipping name	
DOT	Butyl acetates solution
ADR	1123 Butyl acetates solution
· IMDG, IATA	BUTYL ACETATES solution
· Transport hazard class(es)	
DOT	
N MAN T I GEN	
Class	3 Flammable liquids
· Label	3
· ADR, IMDG, IATA	
2	

acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 09/01/2017

Page 9/11

Trade name: S688 ANTI-SILICONE

	(Contd. of page
· Label	3
· Packing group · DOT, ADR, IMDG, IATA	<i>III</i>
 Environmental hazards: Marine pollutant: 	No
 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category 	Warning: Flammable liquids 30 F-E,S-D A
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	Il of Not applicable.
 Transport/Additional information: DOT Quantity limitations 	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1123 BUTYL ACETATES SOLUTION, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

- · Section 355 (extremely hazardous substances):
- None of the ingredients is listed.
- · Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 10)

US



Page 10/11

(Contd. of page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 09/01/2017

Trade name: S688 ANTI-SILICONE

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Warning

- Hazard-determining components of labeling: n-butyl acetate
- Hazard statements

Flammable liquid and vapor.

May cause drowsiness or dizziness.

Precautionary statements
 If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.

(Contd. on page 11)

US



acc. to OSHA HCS

Printing date 03/01/2019

Reviewed on 09/01/2017

Trade name: S688 ANTI-SILICONE

(Contd. of page 10)

Page 11/11

Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

Take precautionary measures against static discharge.

- · Contact: Ms. Topaljikian
- · Date of preparation / last revision 03/01/2019 / -

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Lig. 3: Flammable liquids - Category 3 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

