

Page 1/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/22/2023

1 Identification

- · Product identifier
- · Trade name: C030LV VOC SMOOTH CLEAR
- · Article number: C030LV
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. SAL

P.O. Box 7623

Beirut

LEBANON

info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number:

1-800-535-5053 contract number (89244)

departamento de seguridad de los productos

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Page 2/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

4-chloro-alpha, alpha, alpha-trifluorotoluene

acetone

n-butyl acetate

methyl methacrylate

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

2,3-epoxypropyl neodecanoate

s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxyphenyl

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

(Contd. on page 3)



Page 3/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 2)

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>25- <i>≤</i> 50%
67-64-1	acetone	>10- <i>≤</i> 25%
	n-butyl acetate	>10- <i>≤</i> 25%
	methyl methacrylate	<i>≤</i> 2.5%
• •	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	<i>≤</i> 2.5%
	2,3-epoxypropyl neodecanoate	<i>≤</i> 2.5%
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	<i>≤</i> 2.5%

115



Page 4/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 3)

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2. extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 5)



Page 5/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

Protective Action C	riteria for Chemicals	(Contd. of page 4
PAC-1:		
67-64-1 acetone		200 ppm
123-86-4 n-butyl ace	etate	5 ppm
80-62-6 methyl me	thacrylate	17 ppm
79-41-4 methacryli	c acid	6.7 ppm
868-77-9 2-hydroxye	ethyl methacrylate	1.9 mg/m ²
77-58-7 dibutyltin d	lilaurate	1.1 mg/m ³
556-67-2 octamethy	lcyclotetrasiloxane	30 ppm
PAC-2:		
67-64-1 acetone		3200* ppm
123-86-4 n-butyl ace	etate	200 ppm
80-62-6 methyl me	thacrylate	120 ppm
79-41-4 methacryli	c acid	61 ppm
868-77-9 2-hydroxye	ethyl methacrylate	21 mg/m³
77-58-7 dibutyltin d	lilaurate	8 mg/m³
556-67-2 octamethy	lcyclotetrasiloxane	68 ppm
PAC-3:		·
67-64-1 acetone		5700* ppm
123-86-4 n-butyl ace	etate	3000* ppm
80-62-6 methyl me	thacrylate	570 ppm
79-41-4 methacryli	c acid	220 ppm
868-77-9 2-hydroxye	ethyl methacrylate	1,000 mg/m ³
77-58-7 dibutyltin d	lilaurate	48 mg/m³
556-67-2 octamethy	lcyclotetrasiloxane	130 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 6)



Page 6/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 5)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

67-64-1 acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm TLV | Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV Short-term value: 150 ppm Long-term value: 50 ppm 80-62-6 methyl methacrylate PEL Long-term value: 410 mg/m³, 100 ppm REL Long-term value: 410 mg/m³, 100 ppm TLV Short-term value: 100 ppm Long-term value: 50 ppm DSEN, A4

(Contd. on page 7)



Page 7/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 6)

· Ingredients with biological limit values:

67-64-1 acetone

BEI 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)



Page 8/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 7)

· Eye protection:



Tightly sealed goggles

0 Phycical	and	chamical	nron	artiae
9 Physical		7115111115611		

· Information on basic physi	cai and chemical properties
0 (1	

· General Information

· Appearance:

Form: Liquid Color: Clear

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:55 °C (131 °F)

· Flash point: -5 °C (23 °F)

· Flammability (solid, gaseous): Highly flammable.

· Auto igniting: 370 °C (698 °F)

Decomposition temperature: Not determined.

· **Ignition temperature:** Product is not selfigniting.

• **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 1.2 Vol % **Upper:** 13 Vol %

· Vapor pressure at 20 °C (68 °F): 233 hPa (174.8 mm Hg)

• **Density at 20 °C (68 °F):** 1.1 g/cm³ (9.1795 lbs/gal)

Relative density
Vapor density
Evaporation rate
Not determined.
Not determined.
Not determined.

(Contd. on page 9)



Page 9/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

	(Contd.	of page
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/w	vater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	73.2 %	
Coating VOC content:	10.05 %	
•	280.7 g/l / 2.34 lb/gal	
Material VOC content:	110.6 g/l / 0.92 lb/gal	
Solids content:	26.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

. Irritant

(Contd. on page 10)



Page 10/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 9)

· Carcinogenic categories

· Carcino	genic categories	
· IARC (International Agency for Research on Cancer)		
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
80-62-6	methyl methacrylate	3
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of	the ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

ıs



Page 11/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 10)

UN-Number	UN1263
DOT, ADR, IMDG, IATA	UNIZUS
UN proper shipping name	Doint
DOT ADR	Paint 1263 PAINT
IMDG, IATA	PAINT
Transport hazard class(es)	NOT APPLICABLE
DOT	
LANGE LANGE	
Class	3 Flammable liquids
Label	3
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	II .
Environmental hazards:	.,
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number: Stowage Category	F-E, <u>S-E</u> B
• • •	<u> </u>
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L

(Contd. on page 12)



Page 12/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 11)

· ADR

• Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· IMDG

· Limited quantities (LQ) 5L

Excepted quantities (EQ)
 Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1263 PAINT, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

80-62-6 methyl methacrylate

- · Proposition 65
- Chemicals known to cause cancer:

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 13)



Page 13/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 12)

· Carcinogenic categories

· EPA (En	vironmental Protection Agency)	
67-64-1	acetone	1
80-62-6	methyl methacrylate	E, NL
· TLV (Th	reshold Limit Value)	
67-64-1	acetone	A4
80-62-6	methyl methacrylate	A4
77-58-7	dibutyltin dilaurate	A4
· NIOSH-0	Ca (National Institute for Occupational Safety and Health)	
None of	the ingredients is listed.	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

Hazard-determining components of labeling:

4-chloro-alpha,alpha,alpha-trifluorotoluene

acetone

n-butyl acetate

methyl methacrylate

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

2,3-epoxypropyl neodecanoate

s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxyphenyl

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

(Contd. on page 14)



Page 14/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 13)

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 06/22/2023
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 15)



Page 15/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023

Trade name: C030LV VOC SMOOTH CLEAR

(Contd. of page 14)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1
Carcinogenicity 2: Carcinogenicity - Category 2
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.