

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

### 1 Identification

- **Product identifier**
- **Trade name:** C030 2K SMOOTH CLEAR
- **Article number:** C030
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. SAL  
P.O. Box 7623  
Beirut LEBANON  
info@hymax.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

acetone

n-butyl acetate

(Contd. on page 2)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 1)

methyl methacrylate  
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate  
2,3-epoxypropyl neodecanoate  
s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-

· **Hazard statements**

Highly flammable liquid and vapor.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Call a poison center/doctor if you feel unwell.  
Specific treatment (see on this label).  
Take off contaminated clothing and wash it before reuse.  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use for extinction: CO2, powder or water spray.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2  
Fire = 3  
Reactivity = 0

(Contd. on page 3)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

67-64-1	acetone	>10-≤25%
110-43-0	2-Heptanone	>10-≤25%
1330-20-7	xylene	>10-≤25%
123-86-4	n-butyl acetate	>10-≤25%
80-62-6	methyl methacrylate	≤2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	≤2.5%
26761-45-5	2,3-epoxypropyl neodecanoate	≤2.5%
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol- ohydroxypoly(oxyethylene);a-3-(3-(2h-	≤2.5%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.

(Contd. on page 4)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

67-64-1	acetone	200 ppm
110-43-0	2-Heptanone	150 ppm
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
80-62-6	methyl methacrylate	17 ppm
79-41-4	methacrylic acid	6.7 ppm
868-77-9	2-hydroxyethyl methacrylate	1.9 mg/m <sup>3</sup>
78-83-1	butanol	150 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m <sup>3</sup>
556-67-2	octamethylcyclotetrasiloxane	30 ppm
100-41-4	ethylbenzene	33 ppm

(Contd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 4)

· <b>PAC-2:</b>		
67-64-1	acetone	3200* ppm
110-43-0	2-Heptanone	670 ppm
1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
80-62-6	methyl methacrylate	120 ppm
79-41-4	methacrylic acid	61 ppm
868-77-9	2-hydroxyethyl methacrylate	21 mg/m <sup>3</sup>
78-83-1	butanol	1,300 ppm
77-58-7	dibutyltin dilaurate	8 mg/m <sup>3</sup>
556-67-2	octamethylcyclotetrasiloxane	68 ppm
100-41-4	ethylbenzene	1100* ppm
· <b>PAC-3:</b>		
67-64-1	acetone	5700* ppm
110-43-0	2-Heptanone	4000* ppm
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
80-62-6	methyl methacrylate	570 ppm
79-41-4	methacrylic acid	220 ppm
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m <sup>3</sup>
78-83-1	butanol	8000* ppm
77-58-7	dibutyltin dilaurate	48 mg/m <sup>3</sup>
556-67-2	octamethylcyclotetrasiloxane	130 ppm
100-41-4	ethylbenzene	1800* ppm

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 6)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 5)

- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

#### 67-64-1 acetone

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm Long-term value: 594 mg/m <sup>3</sup> , 250 ppm BEI

#### 110-43-0 2-Heptanone

PEL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 233 mg/m <sup>3</sup> , 50 ppm

#### 1330-20-7 xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

#### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

#### 80-62-6 methyl methacrylate

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
-----	--

(Contd. on page 7)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 6)

REL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 410 mg/m <sup>3</sup> , 100 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm DSEN

**· Ingredients with biological limit values:**

**67-64-1 acetone**

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 7)

**· Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

**· Information on basic physical and chemical properties**

**· General Information**

**· Appearance:**

**Form:** Liquid

**Color:** Clear

**· Odor:** Characteristic

**· Odor threshold:** Not determined.

**· pH-value:** Not determined.

**· Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 55.8-56.6 °C (132.4-69.9 °F)

**· Flash point:** -5 °C (23 °F)

**· Flammability (solid, gaseous):** Not applicable.

**· Ignition temperature:** 370 °C (698 °F)

**· Decomposition temperature:** Not determined.

**· Auto igniting:** Product is not selfigniting.

**· Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

**· Explosion limits:**

**Lower:** 1 Vol %

**Upper:** 13 Vol %

**· Vapor pressure at 20 °C (68 °F):** 233 hPa (174.8 mm Hg)

**· Density at 20 °C (68 °F):** 0.93111 g/cm<sup>3</sup> (7.77011 lbs/gal)

**· Relative density** Not determined.

**· Vapor density** Not determined.

**· Evaporation rate** Not determined.

**· Solubility in / Miscibility with**

**Water:** Not miscible or difficult to mix.

**· Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 9)



## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 8)

- |                              |  |
|------------------------------|--|
| <b>· Viscosity:</b>          |  |
| <b>Dynamic:</b>              | Not determined.                            |
| <b>Kinematic:</b>            | Not determined.                            |
| <b>· Solvent content:</b>    |  |
| <b>Organic solvents:</b>     | 65.0 %                                     |
| <b>Coating VOC content:</b>  | 43.27 %                                    |
| <b>Material VOC content:</b> | 541.4 g/l / 4.52 lb/gal                    |
|                              | 402.9 g/l / 3.36 lb/gal                    |
| <b>Solids content:</b>       | 34.0 %                                     |
| <b>· Other information</b>   | No further relevant information available. |

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

#### 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

(Contd. on page 10)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 9)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
80-62-6	methyl methacrylate	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

· **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

US

(Contd. on page 11)

## Safety Data Sheet

acc. to OSHA HCS



Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 10)

### 14 Transport information

<ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>	<p>UN1263</p>
<ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul>	<p>Paint 1263 PAINT PAINT</p>
<ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p>3 Flammable liquids 3</p>
<ul style="list-style-type: none"> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p>3 Flammable liquids 3</p>
<ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>	<p>II</p>
<ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>	<p>No</p>
<ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul>	<p>Warning: Flammable liquids 33 F-E, S-E B</p>
<ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b></li> </ul>	<p>Not applicable.</p>
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> <li>· <b>DOT</b></li> <li>· <b>Quantity limitations</b></li> </ul>	<p>On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L</p>

(Contd. on page 12)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 11)

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>· <b>ADR</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>  | <p>Code: E2<br/>                 Maximum net quantity per inner packaging: 30 ml<br/>                 Maximum net quantity per outer packaging: 500 ml</p>                         |
| <ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul> | <p>5L<br/>                 Code: E2<br/>                 Maximum net quantity per inner packaging: 30 ml<br/>                 Maximum net quantity per outer packaging: 500 ml</p> |
| <ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>  | <p>UN 1263 PAINT, 3, II</p>  |

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
80-62-6	methyl methacrylate
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

67-64-1	acetone	ACTIVE
110-43-0	2-Heptanone	ACTIVE
1330-20-7	xylene	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
80-62-6	methyl methacrylate	ACTIVE
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	ACTIVE
26761-45-5	2,3-epoxypropyl neodecanoate	ACTIVE
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	ACTIVE
79-41-4	methacrylic acid	ACTIVE
868-77-9	2-hydroxyethyl methacrylate	ACTIVE
82919-37-7	methyl 1,2,2,6,6pntamethyl-4-piperidyl sebacate	ACTIVE
78-83-1	butanol	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
556-67-2	octamethylcyclotetrasiloxane	ACTIVE

(Contd. on page 13)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 12)

100-41-4 ethylbenzene	ACTIVE
-----------------------	--------

· **Hazardous Air Pollutants**

1330-20-7	xylene	
80-62-6	methyl methacrylate	
100-41-4	ethylbenzene	

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene	
----------	--------------	--

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
1330-20-7	xylene	I
80-62-6	methyl methacrylate	E, NL
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
1330-20-7	xylene	A4
80-62-6	methyl methacrylate	A4
77-58-7	dibutyltin dilaurate	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

(Contd. on page 14)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 13)

**· Hazard-determining components of labeling:**

acetone  
n-butyl acetate  
methyl methacrylate  
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate  
2,3-epoxypropyl neodecanoate  
s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-

**· Hazard statements**

Highly flammable liquid and vapor.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.

**· Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Call a poison center/doctor if you feel unwell.  
Specific treatment (see on this label).  
Take off contaminated clothing and wash it before reuse.  
If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 15)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2020

Reviewed on 05/07/2020

**Trade name: C030 2K SMOOTH CLEAR**

(Contd. of page 14)

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Product safety department
- **Contact:** N/A
- **Date of preparation / last revision** 05/07/2020 / -
- **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*NIOSH: National Institute for Occupational Safety*

*OSHA: Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit*

*BEI: Biological Exposure Limit*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*

*Skin Sens. 1: Skin sensitisation – Category 1*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*