



Printing date 02/18/2020

Reviewed on 02/18/2020

#### 1 Identification

- · Product identifier
- · Trade name: C071 VOC SUPERIOR CLEAR
- · Article number: C071
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. SAL

P.O. Box 7623

Beirut

**LEBANON** 

info@hymax.biz

- · Information department: Product Safety Department
- · Emergency telephone number: 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxyphenyl

methyl methacrylate

2-hydroxyethyl methacrylate

(Contd. on page 2)





Printing date 02/18/2020 Reviewed on 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

(Contd. of page 1)

methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate

· Hazard statements

Flammable liquid and vapor.

May cause an allergic skin reaction.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



1 Health = 1 3 Fire = 3

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

123-86-4 n-butyl acetate

>10-*≤*25%

(Contd. on page 3)



Printing date 02/18/2020 Reviewed on 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

		Contd. of page 2)
	2-Heptanone	>10- <i>≤</i> 25%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5-≤10%
	pentane-2,4-dione	≤2.5%
	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	≤2.5%
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	≤2.5%
	methyl methacrylate	≤2.5%
	2-hydroxyethyl methacrylate	<i>≤</i> 2.5%
82919-37-7	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate	<i>≤</i> 2.5%

#### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)





Reviewed on 02/18/2020 Printing date 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

(Contd. of page 3)

#### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### · Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

#### · Protective Action Criteria for Chemicals

123-86-4	n-butyl acetate	5 pp	m
110-43-0	2-Heptanone	150	орт
123-54-6	pentane-2,4-dione	75 p <sub>l</sub>	рт
80-62-6	methyl methacrylate	17 pj	рт
868-77-9	2-hydroxyethyl methacrylate	1.9 n	ng/m³
77-58-7	dibutyltin dilaurate	1.1 n	ng/m <sup>:</sup>
57-55-6	Propylene glycol	30 m	ig/m³
280-57-9	triethylenediamine	5.1 n	ng/m <sup>:</sup>
556-67-2	octamethylcyclotetrasiloxane	30 p <sub>l</sub>	от
PAC-2:			
123-86-4	n-butyl acetate	200 ppi	m
110-43-0	2-Heptanone	670 ppi	m
123-54-6	pentane-2,4-dione	110 ppi	m
80-62-6	methyl methacrylate	120 ppi	m
868-77-9	2-hydroxyethyl methacrylate	21 mg/i	m³
77-58-7	dibutyltin dilaurate	8 mg/m	
57-55-6	Propylene glycol	1,300 n	ng/m
280-57-9	triethylenediamine	56 mg/l	m³
556-67-2	octamethylcyclotetrasiloxane	68 ppm	)
PAC-3:		•	
123-86-4	n-butyl acetate	3000* µ	рт
110-43-0	2-Heptanone	4000* µ	рт
123-54-6	pentane-2,4-dione	200 ppi	m
80-62-6	methyl methacrylate	570 ppi	m
868-77-9	2-hydroxyethyl methacrylate	1,000 n	ng/m
77-58-7	dibutyltin dilaurate	48 mg/i	m³
57-55-6	Propylene glycol	7,900 n	ng/m
280-57-9	triethylenediamine	340 mg	ı/m³





Printing date 02/18/2020 Reviewed on 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

556-67-2 octamethylcyclotetrasiloxane

(Contd. of page 4)

130 ppm

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits

At this time, the other constituents have no known exposure limits.			
123-	86-4 n-butyl acetate		
PEL	Long-term value: 710 mg/m³, 150 ppm		
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm		
TLV	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm		
110-	43-0 2-Heptanone		
PEL	Long-term value: 465 mg/m³, 100 ppm		
REL	Long-term value: 465 mg/m³, 100 ppm		
TLV	Long-term value: 233 mg/m³, 50 ppm		
123-54-6 pentane-2,4-dione			
TLV	Long-term value: 102 mg/m³, 25 ppm Skin		
-	(Contd. on page 6)		





Printing date 02/18/2020 Reviewed on 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

(Contd. of page 5)

## 80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm
REL Long-term value: 410 mg/m³, 100 ppm
TLV Short-term value: 410 mg/m³, 100 ppm
Long-term value: 205 mg/m³, 50 ppm
DSEN

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

US





Printing date 02/18/2020 Reviewed on 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

(Contd. of page 6)

Information on basic physical and o	chemical properties			
· General Information				
· Appearance:				
Form:	Liquid			
Color:	Clear			
Odor:	Characteristic			
Odor threshold:	Not determined.			
pH-value:	Not determined.			
Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	127 °C (260.6 °F)			
Flash point:	27 °C (80.6 °F)			
Flammability (solid, gaseous):	Not applicable.			
Ignition temperature:	370 °C (698 °F)			
Decomposition temperature:	Not determined.			
Auto igniting:	Product is not selfigniting.			
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.			
Explosion limits:				
Lower:	1 Vol %			
Upper:	7.5 Vol %			
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)			
Density at 20 °C (68 °F):	0.993 g/cm³ (8.28659 lbs/gal)			
Relative density	Not determined.			
Vapor density	Not determined.			
Evaporation rate	Not determined.			
Solubility in / Miscibility with				
Water:	Not miscible or difficult to mix.			
Partition coefficient (n-octanol/water	er): Not determined.			
Viscosity:				
Dynamic:	Not determined.			
Kinematic:	Not determined.			
Solvent content:				
Organic solvents:	43.1 %			
Coating VOC content:	43.05 %			

(Contd. on page 8)





Printing date 02/18/2020 Reviewed on 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

(Contd. of page 7)

	( 1-3-	,
Material VOC content:	427.5 g/l / 3.57 lb/gal	
Solids content:  Other information	55.6 % No further relevant information available.	

#### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values	that are	relevant for	classification:
------------------	----------	--------------	-----------------

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

#### · IARC (International Agency for Research on Cancer)

80-62-6 methyl methacrylate

3

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 9)





Printing date 02/18/2020 Reviewed on 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

(Contd. of page 8)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

· **DOT** Paint

· **ADR** 1263 PAINT · **IMDG, IATA** PAINT

(Contd. on page 10)





Printing date 02/18/2020 Reviewed on 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

(Contd. of page 9) · Transport hazard class(es) · DOT · Class 3 Flammable liquids · Label · ADR, IMDG, IATA · Class 3 Flammable liquids · Label · Packing group III· DOT, ADR, IMDG, IATA · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids Danger code (Kemler): 30 F-E,S-E · EMS Number: · Stowage Category · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · DOT · Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L · ADR · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 11)





Printing date 02/18/2020 Reviewed on 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

(Contd. of page 10)

· UN "Model Regulation": UN 1263 PAINT, 3, III

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

· TSCA (	Toxic	Substances	Control	Act):
----------	-------	------------	---------	-------

•	Substances Control Acty.	
123-86-4	n-butyl acetate	ACTIVE
110-43-0	2-Heptanone	ACTIVE
123-54-6	pentane-2,4-dione	ACTIVE
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	ACTIVE
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-	ACTIVE
80-62-6	methyl methacrylate	ACTIVE
868-77-9	2-hydroxyethyl methacrylate	ACTIVE
82919-37-7	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
57-55-6	Propylene glycol	ACTIVE
280-57-9	triethylenediamine	ACTIVE
556-67-2	octamethylcyclotetrasiloxane	ACTIVE

#### · Hazardous Air Pollutants

80-62-6 methyl methacrylate

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 12)





Printing date 02/18/2020 Reviewed on 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

(Contd. of page 11)

#### · Carcinogenic categories

· EPA (Er	nvironmental Protection Agency)	
80-62-6	methyl methacrylate	E, NL
· TLV (Th	reshold Limit Value established by ACGIH)	
80-62-6	methyl methacrylate	A4
77-58-7	dibutyltin dilaurate	A4
· NIOSH-	Ca (National Institute for Occupational Safety and Health)	
None of	the ingredients is listed.	

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

#### · Signal word Warning

#### · Hazard-determining components of labeling:

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxyphenyl

methyl methacrylate

2-hydroxyethyl methacrylate

methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate

#### · Hazard statements

Flammable liquid and vapor.

May cause an allergic skin reaction.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

(Contd. on page 13)





Printing date 02/18/2020 Reviewed on 02/18/2020

Trade name: C071 VOC SUPERIOR CLEAR

(Contd. of page 12)

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- Date of preparation / last revision 02/18/2020 / -
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Sens. 1: Skin sensitisation - Category 1

US