



# C070LV – Ultra Performance Clear


## Description:

C070LV is a VOC compliant high quality clearcoat that is easy to apply with excellent finishing properties whilst focusing on the efficiency of the bodyshop. A simple, half + full coat application process with no flash off, allows a repair to be ready to sand & polish in only an hour.

“It uses the same hardener range as other premium clearcoats in the HyVida line, providing a complete and compact offer.”

## Suitable Substrates:

- “Hymax” HyVida Basecoat.



Mix 1:1 with H015, H022, H036 hardener  
Potlife: 35 minutes at 20°C



13-15 s / DIN 4 mm / 20°C



Compliant 1.3 – 1.4 mm (1/2 + full spray passes)  
2.0 – 2.5 bar inlet pressure  
0.7 bar at the air-cap



½ + 1 full = 40 – 50 micron

## Air Dry Time:



	20°C
Dust free	15-20 min
Tack free	25-30 min
Dry for sanding & polishing	60-70 min

Product Data Sheet



## C070LV – Ultra Performance Clear

### Force Dry Time:



15 min. @ 40-45 °C panel temperature.  
5 min. @ 60-65 °C panel temperature



Wear suitable protection

### VOC

**Regulatory VOC** 241.7 gr/lit (2.01 lbs/gal)  
**Regulatory VOC** ready to spray < 250.0 gr/lit (2.08 lbs/gal)

### Flash Point:

-4°C (24.8 °F)

### Solids Content:

77.3 % by weight

### Coverage:

10 m<sup>2</sup>/l at 45 micron film thickness (theoretical)

### Specific Gravity:

1.05 kg/cm<sup>3</sup>

### SDS:

Refer to the safety data sheet

Product Data Sheet