

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

### 1 Identification

- **Product identifier**
- **Trade name:** H020 2K HARDENER SUPER FAST
- **Article number:** H020
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. SAL  
P.O. Box 7623  
Beirut  
LEBANON  
info@hymax.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** During normal opening times: 1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3    H226    Flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1    H334    May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2    H351    Suspected of causing cancer.



GHS07

Acute Tox. 4    H332    Harmful if inhaled.

Skin Irrit. 2    H315    Causes skin irritation.

Eye Irrit. 2A    H319    Causes serious eye irritation.

STOT SE 3    H335-H336    May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 1)

### · Hazard pictograms



GHS02 GHS07 GHS08

### · Signal word Danger

### · Hazard-determining components of labeling:

Homopolymer of hexamethylene diisocyanate

Isophorone Diisocyanate homopolymer

xylene

n-butyl acetate

### · Hazard statements

Flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Suspected of causing cancer.

May cause respiratory irritation. May cause drowsiness or dizziness.

### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

(Contd. on page 3)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 2)

*If experiencing respiratory symptoms: Call a poison center/doctor.*

*In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.*

*Store in a well-ventilated place. Keep container tightly closed.*

*Store in a well-ventilated place. Keep cool.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*2

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1330-20-7	xylene	>25-≤50%
28182-81-2	Homopolymer of hexamethylene diisocyanate	>25-≤50%
123-86-4	n-butyl acetate	>10-≤25%
53880-05-0	Isophorone Diisocyanate homopolymer	>2.5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
100-41-4	ethylbenzene	≤2.5%

US

(Contd. on page 4)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 3)

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.

(Contd. on page 5)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 4)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**· Protective Action Criteria for Chemicals**
**· PAC-1:**

1330-20-7	xylene	130 ppm
28182-81-2	Homopolymer of hexamethylene diisocyanate	7.8 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	5 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
100-41-4	ethylbenzene	33 ppm
822-06-0	hexamethylene-di-isocyanate	0.018 ppm
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	0.02 ppm

**· PAC-2:**

1330-20-7	xylene	920* ppm
28182-81-2	Homopolymer of hexamethylene diisocyanate	86 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
100-41-4	ethylbenzene	1100* ppm
822-06-0	hexamethylene-di-isocyanate	0.2 ppm
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	0.14 ppm

**· PAC-3:**

1330-20-7	xylene	2500* ppm
28182-81-2	Homopolymer of hexamethylene diisocyanate	510 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	3000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
100-41-4	ethylbenzene	1800* ppm
822-06-0	hexamethylene-di-isocyanate	3 ppm
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	0.6 ppm

### 7 Handling and storage

**· Handling:**
**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

**· Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

(Contd. on page 6)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 5)

Protect against electrostatic charges.  
Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

#### 1330-20-7 xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

#### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

#### 100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI

(Contd. on page 7)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 6)

· **Ingredients with biological limit values:**

**1330-20-7 xylene**

BEI 1.5 g/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Methylhippuric acids

**100-41-4 ethylbenzene**

BEI 0.7 g/g creatinine  
Medium: urine  
Time: end of shift at end of workweek  
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
Medium: end-exhaled air  
Time: not critical  
Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 8)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 7)

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Liquid

**Color:** Clear

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 124 °C (255.2 °F)

- **Flash point:** 25 °C (77 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 370 °C (698 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

**Lower:** 1.1 Vol %

**Upper:** 7.5 Vol %

- **Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)

- **Density at 20 °C (68 °F):** 0.99652 g/cm<sup>3</sup> (8.31596 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

(Contd. on page 9)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 8)

· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	60.6 %
<b>Coating VOC content:</b>	60.64 %
	604.3 g/l / 5.04 lb/gal
<b>Material VOC content:</b>	604.3 g/l / 5.04 lb/gal
· <b>Solids content:</b>	40.1 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

#### 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through inhalation.

(Contd. on page 10)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 9)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful  
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019



Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 10)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>  | <p style="margin-top: 0;">UN1263</p>   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul>                                      | <p style="margin-top: 0;">Paint</p> <p style="margin-top: 0;">1263 PAINT</p> <p style="margin-top: 0;">PAINT</p>   |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>  | <div style="text-align: center; margin-top: 10px;">  </div>                   |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>   | <p style="margin-top: 0;">3 Flammable liquids</p> <p style="margin-top: 0;">3</p>  |
| <ul style="list-style-type: none"> <li>· <b>ADR, IMDG, IATA</b></li> </ul>   | <div style="text-align: center; margin-top: 10px;">  </div>                   |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>   | <p style="margin-top: 0;">3 Flammable liquids</p> <p style="margin-top: 0;">3</p>  |
| <ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>  | <p style="margin-top: 0;">III</p>  |
| <ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>  | <p style="margin-top: 0;">No</p>   |
| <ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Danger code (Kemler):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul> | <p style="margin-top: 0;">Warning: Flammable liquids</p> <p style="margin-top: 0;">30</p> <p style="margin-top: 0;">F-E, S-E</p> <p style="margin-top: 0;">A</p> |
| <ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b></li> </ul>  | <p style="margin-top: 0;">Not applicable.</p>  |

(Contd. on page 12)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 11)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 60 L  
On cargo aircraft only: 220 L

· **ADR**

· **Excepted quantities (EQ)**

Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· **IMDG**

· **Limited quantities (LQ)**

· **Excepted quantities (EQ)**

5L  
Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, III

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
· **Sara**

· **Section 355 (extremely hazardous substances):**

4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
-----------	---

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
100-41-4	ethylbenzene
822-06-0	hexamethylene-di-isocyanate
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

· **TSCA (Toxic Substances Control Act):**

1330-20-7	xylene	ACTIVE
28182-81-2	Homopolymer of hexamethylene diisocyanate	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
53880-05-0	Isophorone Diisocyanate homopolymer	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
100-41-4	ethylbenzene	ACTIVE
822-06-0	hexamethylene-di-isocyanate	ACTIVE
4083-64-1	4-isocyanatosulphonyltoluene	ACTIVE

(Contd. on page 13)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 12)

4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	ACTIVE
-----------	---	--------

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
822-06-0	hexamethylene-di-isocyanate

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.	
------------------------------------	--

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.	
------------------------------------	--

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.	
------------------------------------	--

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.	
------------------------------------	--

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Homopolymer of hexamethylene diisocyanate  
Isophorone Diisocyanate homopolymer  
xylene

(Contd. on page 14)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 13)

*n*-butyl acetate**• Hazard statements***Flammable liquid and vapor.**Harmful if inhaled.**Causes skin irritation.**Causes serious eye irritation.**May cause allergy or asthma symptoms or breathing difficulties if inhaled.**Suspected of causing cancer.**May cause respiratory irritation. May cause drowsiness or dizziness.***• Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Avoid breathing dust/fume/gas/mist/vapors/spray**Wash thoroughly after handling.**Use only outdoors or in a well-ventilated area.**Wear protective gloves/protective clothing/eye protection/face protection.**[In case of inadequate ventilation] wear respiratory protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**IF exposed or concerned: Get medical advice/attention.**Call a poison center/doctor if you feel unwell.**Specific treatment (see on this label).**Take off contaminated clothing and wash it before reuse.**If skin irritation occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**If experiencing respiratory symptoms: Call a poison center/doctor.**In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.**Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***• Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

(Contd. on page 15)

US

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

**Trade name: H020 2K HARDENER SUPER FAST**

(Contd. of page 14)

• **Department issuing SDS:** Product safety department

• **Contact:** N/A

• **Date of preparation / last revision** 05/06/2019 / -

• **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*NIOSH: National Institute for Occupational Safety*

*OSHA: Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit*

*BEI: Biological Exposure Limit*

*Flam. Liq. 3: Flammable liquids – Category 3*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*

*Resp. Sens. 1: Respiratory sensitisation – Category 1*

*Carc. 2: Carcinogenicity – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*