

Page 1/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

1 Identification

- · Product identifier
- · Trade name: W100 SHADOW WHITE
- · Article number: W100
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz

· Information department: Product Safety Department

• Emergency telephone number: During normal opening times:1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- Signal word Warning
- Hazard statements
 Combustible liquid.
- · Precautionary statements

Keep away from flames and hot surfaces. – No smoking. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)

 $\begin{array}{c} 2\\ 0\\ 0\\ 0\\ 0\\ \end{array}$ Health = 0 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



(Contd. on page 2)

⁻ US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W100 SHADOW WHITE

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

111-76-2 2-butoxyethanol

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



(Contd. of page 1)

>2.5-*≤*10%

Page 2/10

acc. to OSHA HCS

Reviewed on 05/06/2019

(Contd. of page 2) · Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. · Reference to other sections No dangerous substances are released. See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. · Protective Action Criteria for Chemicals · PAC-1: 111-76-2 2-butoxyethanol 60 ppm 67-63-0 propan-2-ol 400 ppm 108-01-0 2-dimethylaminoethanol 3.7 ppm 140-88-5 ethyl acrylate 8.3 ppm · PAC-2: 111-76-2 2-butoxyethanol 120 ppm 2000* ppm 67-63-0 propan-2-ol 108-01-0 2-dimethylaminoethanol 40 ppm 140-88-5 ethyl acrylate 36 ppm · PAC-3; 111-76-2 2-butoxyethanol 700 ppm 67-63-0 propan-2-ol 12000** ppm 108-01-0 2-dimethylaminoethanol 72 ppm 140-88-5 ethyl acrylate 240 ppm 7 Handling and storage · Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10

(Contd. on page 4)





Trade name: W100 SHADOW WHITE

US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W100 SHADOW WHITE

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

| 111-76-2 | 2-butoxyethanol |
|----------|-----------------|
|----------|-----------------|

- PEL Long-term value: 240 mg/m³, 50 ppm Skin
- REL Long-term value: 24 mg/m³, 5 ppm Skin
- TLV Long-term value: 97 mg/m³, 20 ppm BEI

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

(Contd. of page 3)

Page 4/10

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W100 SHADOW WHITE

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

| Appearance: Form: | Fluid | |
|--------------------------------------|-----------------------------------|--|
| Color: | According to product description | |
| Odor: | Characteristic | |
| Odor threshold: | Not determined. | |
| pH-value: | Not determined. | |
| Change in condition | | |
| Melting point/Melting range: | Undetermined. | |
| Boiling point/Boiling range: | 100 °C (212 °F) | |
| Flash point: | 68 °C (154.4 °F) | |
| Flammability (solid, gaseous): | Not applicable. | |
| Ignition temperature: | 240 °C (464 °F) | |
| Decomposition temperature: | Not determined. | |
| Auto igniting: | Product is not selfigniting. | |
| Danger of explosion: | Not determined. | |
| Explosion limits: | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| Vapor pressure at 20 °C (68 °F): | 23 hPa (17.3 mm Hg) | |
| Density at 20 °C (68 °F): | 1.05 g/cm³ (8.76225 lbs/gal) | |
| Relative density | Not determined. | |
| Vapor density | Not determined. | |
| Evaporation rate | Not determined. | |
| Solubility in / Miscibility with | | |
| Water: | Not miscible or difficult to mix. | |
| Partition coefficient (n-octanol/wat | er): Not determined. | |



(Contd. of page 4)

Page 5/10

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 6/10

Trade name: W100 SHADOW WHITE

| | | (Contd. of page 5 |
|-----------------------|--|-------------------|
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| · Solvent content: | | |
| Organic solvents: | 8.2 % | |
| Water: | 63.5 % | |
| Coating VOC content: | 8.16 % | |
| Ū | 257.1 g/l / 2.15 lb/gal | |
| Material VOC content: | 85.7 g/l / 0.72 lb/gal | |
| Solids content: | 27.3 % | |
| · Other information | No further relevant information available. | |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

| · IARC (Int | ternational Agency for Research on Cancer) | | |
|-------------|--|---------------|--------|
| 111-76-2 | 2-butoxyethanol | | 3 |
| 67-63-0 | propan-2-ol | | 3 |
| 140-88-5 | ethyl acrylate | | 2B |
| | | (Contd. on pa | age 7) |
| | | | US |



acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W100 SHADOW WHITE

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| NOT APPLICABLE | |
|----------------|----------------|
| NOT APPLICABLE | |
| NOT APPLICABLE | |
| | NOT APPLICABLE |



Page 7/10

(Contd. of page 6)



acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W100 SHADOW WHITE

Packing group
 Environmental hazards:

No

· Marine pollutant:

· Special precautions for user

Not applicable.

Not applicable.

NOT APPLICABLE

 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

| Section 355 (extremely hazardous substances): | |
|---|-------------------------|
| None of the ingredients is listed. | |
| · Section 313 (Specific toxic chemical listings): | |
| 111-76-2 2-butoxyethanol | |
| 67-63-0 propan-2-ol | |
| 140-88-5 ethyl acrylate | |
| · TSCA (Toxic Substances Control Act): | |
| 111-76-2 2-butoxyethanol | ACTIVE |
| 67-63-0 propan-2-ol | ACTIVE |
| 108-01-0 2-dimethylaminoethanol | ACTIVE |
| 140-88-5 ethyl acrylate | ACTIVE |
| 7732-18-5 water, distilled, conductivity or of similar purity | ACTIVE |
| · Hazardous Air Pollutants | |
| 140-88-5 ethyl acrylate | |
| Proposition 65 | |
| · Chemicals known to cause cancer: | |
| 140-88-5 ethyl acrylate | |
| · Chemicals known to cause reproductive toxicity for females: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause reproductive toxicity for males: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause developmental toxicity: | |
| None of the ingredients is listed. | |
| | (Contd. on page 9) U |



Page 8/10

(Contd. of page 7)

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W100 SHADOW WHITE

(Contd. of page 8)

Page 9/10

| (Conic | . of page of |
|---|--------------|
| · Carcinogenic categories | |
| · EPA (Environmental Protection Agency) | |
| 111-76-2 2-butoxyethanol | NL |
| · TLV (Threshold Limit Value established by ACGIH) | |
| 111-76-2 2-butoxyethanol | A3 |
| 67-63-0 propan-2-ol | A4 |
| 140-88-5 ethyl acrylate | A4 |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | |
| 140-88-5 ethyl acrylate | |
| GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms Void Signal word Warning Hazard statements Combustible liquid. Precautionary statements Keep away from flames and hot surfaces. – No smoking. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulation. Chemical safety assessment: A Chemical Safety Assessment has not been carried out. | ns. |

6 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/06/2019 / -
- Abbreviations and acronyms:
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit

(Contd. on page 10)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W100 SHADOW WHITE

REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 4: Flammable liquids – Category 4



US

Page 10/10

HYMA