

Page 1/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

1 Identification

- · Product identifier
- · Trade name: W210 LUMINOUS GREEN
- · Article number: W210
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz

· Information department: Product Safety Department

• Emergency telephone number: During normal opening times: 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- · Signal word Warning
- Hazard statements
 Combustible liquid.
- · Precautionary statements

Keep away from flames and hot surfaces. – No smoking. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 4)

 $\begin{array}{c} 2\\ 0\\ 0\\ 0\\ 0\\ \end{array}$ Health = 0 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



(Contd. on page 2)

⁻ US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W210 LUMINOUS GREEN

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:
- 111-76-2 2-butoxyethanol
- 67-63-0 propan-2-ol

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

US



(Contd. of page 1)

Page 2/10

>2.5-*≤*10% *≤*2.5%

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019	
J	

Trade name: W210 LUMINOUS GREEN

Reviewed on 05/06/2019

Page 3/10

Methods Absorb wi Dispose c Ensure ac Referenc No dange See Secti See Secti See Secti	nental precautions: Do not allow to enter sewers/ surface or ground water. and material for containment and cleaning up: th liquid-binding material (sand, diatomite, acid binders, universal binders, saw ontaminated material as waste according to item 13. lequate ventilation. e to other sections rous substances are released. on 7 for information on safe handling. on 8 for information on personal protection equipment. on 13 for disposal information. e Action Criteria for Chemicals	(Contd. of page
PAC-1:		
111-76-2	2-butoxyethanol	60 ppm
67-63-0	propan-2-ol	400 ppr
108-01-0	2-dimethylaminoethanol	3.7 ppm
104-76-7	2-Ethyl-1-hexanol	0.1 ppm
140-88-5	ethyl acrylate	8.3 ppm
PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
67-63-0	propan-2-ol	2000* ppn
108-01-0	2-dimethylaminoethanol	40 ppm
104-76-7	2-Ethyl-1-hexanol	100 ppm
140-88-5	ethyl acrylate	36 ppm
PAC-3:		
111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** ppm
108-01-0	2-dimethylaminoethanol	72 ppm
104-76-7	2-Ethyl-1-hexanol	200 ppm
4 40 00 5	ethyl acrylate	240 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling No special precautions are necessary if used correctly.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

US



acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W210 LUMINOUS GREEN

(Contd. of page 3)

Page 4/10

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

Com	ponents with limit values that require monitoring at the workplac	e:
111-	76-2 2-butoxyethanol	
PEL	Long-term value: 240 mg/m³, 50 ppm Skin	
REL	Long-term value: 24 mg/m³, 5 ppm Skin	
TLV	Long-term value: 97 mg/m³, 20 ppm BEI	
67-6	3-0 propan-2-ol	
PEL	Long-term value: 980 mg/m³, 400 ppm	
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm	
TLV	Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI	
Ingre	dients with biological limit values:	
111-	76-2 2-butoxyethanol	
	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis	
67-6	3-0 propan-2-ol	
	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)	

1



Page 5/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W210 LUMINOUS GREEN

- (Contd. of page 4) **Additional information:** The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

Information on basic physical and General Information Appearance:	l chemical properties	
Form:	Fluid	
Color:	According to product description	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	68 °C (154.4 °F)	

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 6/10

Trade name: W210 LUMINOUS GREEN

	(Contd. of	page
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Not determined.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.06 g/cm³ (8.8457 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	8.0 %	
Water:	66.2 %	
Coating VOC content:	7.96 %	
	282.4 g/l / 2.36 lb/gal	
Material VOC content:	84.3 g/l / 0.70 lb/gal	
Solids content:	24.4 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.

(Contd. on page 7)

US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 7/10

(Contd. of page 6)

3

3 2B

Trade name: W210 LUMINOUS GREEN

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)
- 111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

140-88-5 ethyl acrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

• General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W210 LUMINOUS GREEN

· Other adverse effects No further relevant information available.

(Contd. of page 7)

Page 8/10

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

NOT APPLICABLE
NOT APPLICABLE
NOT APPLICABLE
NOT APPLICABLE
No
Not applicable.
l of Not applicable.

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 3	355 (extremely hazardous substances):
None of t	he ingredients is listed.
· Section 3	13 (Specific toxic chemical listings):
111-76-2	2-butoxyethanol
67-63-0	propan-2-ol
140-88-5	ethyl acrylate
	(Contd. on page 9)
	US



1

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 9/10

Trade name: W210 LUMINOUS GREEN

TOOM /T-	(Contd. of page	
•	xic Substances Control Act): 2-butoxyethanol	ACTI
	propan-2-ol	ACTI
	2-dimethylaminoethanol	ACTI
	2-Ethyl-1-hexanol	ACTI
	ethyl acrylate	ACTI
	water, distilled, conductivity or of similar purity	ACTI
	s Air Pollutants	
	ethyl acrylate	
· Propositio		
•	s known to cause cancer:	
	ethyl acrylate	
	s known to cause reproductive toxicity for females:	
	e ingredients is listed.	
	s known to cause reproductive toxicity for males:	
	e ingredients is listed.	
· Chemical	s known to cause developmental toxicity:	
None of th	e ingredients is listed.	
· Carcinoge	enic categories	
· EPA (Env	ironmental Protection Agency)	
111-76-2	2-butoxyethanol	
· TLV (Thre	shold Limit Value established by ACGIH)	
111-76-2	2-butoxyethanol	/
67-63-0	propan-2-ol	/
140-88-5	ethyl acrylate	/
NIOSH-Ca	(National Institute for Occupational Safety and Health)	·
140-88-5	ethyl acrylate	
 Hazard pi Signal wo Hazard st Combustik Precautio Keep away 	ct is classified and labeled according to the Globally Harmonized Sys c tograms Void rd Warning atements	stem (GHS).
	fire: Use for extinction: CO2, powder or water spray.	
0000 01		(Contd. on page



US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W210 LUMINOUS GREEN

(Contd. of page 9)

Page 10/10

Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

<u>6 Other information</u>

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/06/2019 / -
- · Abbreviations and acronyms: ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 4: Flammable liquids - Category 4