

Page 1/10

### Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

#### 1 Identification

- · Product identifier
- · Trade name: W360 MIXING YELLOW
- · Article number: W360
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. SAL

P.O. Box 7623 Beirut LEBANON info@hymax.biz

· Information department: Product Safety Department

• Emergency telephone number: During normal opening times:1-800-535-5053

#### 2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- Signal word Warning
- Hazard statements
   Combustible liquid.
- · Precautionary statements

Keep away from flames and hot surfaces. – No smoking. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)

 $\begin{array}{c} 2\\ 0\\ 0\\ 0\\ \end{array} \begin{array}{c} \text{Health} = 0\\ \text{Fire} = 2\\ \text{Reactivity} = 0 \end{array}$ 

· HMIS-ratings (scale 0 - 4)



(Contd. on page 2)

<sup>-</sup> US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W360 MIXING YELLOW

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

#### Chemical characterization: Mixtures

- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:
- 111-76-2 2-butoxyethanol
- 67-63-0 propan-2-ol

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

US



(Contd. of page 1)

Page 2/10

>2.5-*≤*10% *≤*2.5%

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019	
--------------------------	--

Trade name: W360 MIXING YELLOW

Reviewed on 05/06/2019

Page 3/10

<ul> <li>Methods a Absorb with Dispose co Ensure add</li> <li>Reference No dangen See Sectio See Sectio See Sectio</li> </ul>	ental precautions: Do not allow to enter sewers/ surface or ground water. and material for containment and cleaning up: h liquid-binding material (sand, diatomite, acid binders, universal binders, sa ontaminated material as waste according to item 13. equate ventilation. • to other sections ous substances are released. on 7 for information on safe handling. on 8 for information on personal protection equipment. on 13 for disposal information.	(Contd. of page 2) wdust).
· PAC-1:		
	2-butoxyethanol	60 ppm
67-63-0	propan-2-ol	400 ppm
108-01-0	2-dimethylaminoethanol	3.7 ppm
140-88-5	ethyl acrylate	8.3 ppm
104-76-7	2-Ethyl-1-hexanol	0.1 ppm
7447-41-8	lithium chloride	2.3 mg/m <sup>3</sup>
· PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
67-63-0	propan-2-ol	2000* ppm
108-01-0	2-dimethylaminoethanol	40 ppm
140-88-5	ethyl acrylate	36 ppm
104-76-7	2-Ethyl-1-hexanol	100 ppm
7447-41-8	lithium chloride	25 mg/m³
· PAC-3:	•	
111-76-2	2-butoxyethanol	700 ppm
	propan-2-ol	12000** ppm
	2-dimethylaminoethanol	72 ppm
	ethyl acrylate	240 ppm
104-76-7	2-Ethyl-1-hexanol	200 ppm
7447-41-8	lithium chloride	150 mg/m <sup>3</sup>

#### 7 Handling and storage

#### · Handling:

· Precautions for safe handling No special precautions are necessary if used correctly.

(Contd. on page 4)

US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 4/10

(Contd. of page 3)

#### Trade name: W360 MIXING YELLOW

- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Com	ponents with limit values that require monitoring at the workplace:
111-	76-2 2-butoxyethanol
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 97 mg/m³, 20 ppm BEI
67-6	3-0 propan-2-ol
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI
· Ingre	dients with biological limit values:
111-	76-2 2-butoxyethanol
	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
67-6	3-0 propan-2-ol
	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
	(Contd. on page 5)





Page 5/10

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

#### Trade name: W360 MIXING YELLOW

(Contd. of page 4) • **Additional information:** The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

Information on basic physical and General Information Appearance:	l chemical properties	
Form:	Fluid	
Color:	According to product description	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	68 °C (154.4 °F)	

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 6/10

#### Trade name: W360 MIXING YELLOW

	(Contd. o	of page
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Not determined.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.05157 g/cm³ (8.77535 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	8.6 %	
Water:	64.6 %	
Coating VOC content:	8.60 %	
	281.7 g/l / 2.35 lb/gal	
Material VOC content:	90.4 g/l / 0.75 lb/gal	
Solids content:	25.8 %	
· Other information	No further relevant information available.	

#### 10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.

(Contd. on page 7)

US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W360 MIXING YELLOW

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

· Information on toxicological effects

#### · Acute toxicity:

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)
- 111-76-2 2-butoxyethanol
- 67-63-0 propan-2-ol

140-88-5 ethyl acrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

• General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)



(Contd. of page 6)

3

3 2B

Page 7/10

<sup>-</sup> US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

#### Trade name: W360 MIXING YELLOW

· Other adverse effects No further relevant information available.

# 13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number	NOT APPLICABLE
· UN proper shipping name	NOT APPLICABLE
· Transport hazard class(es)	NOT APPLICABLE
· Packing group	NOT APPLICABLE
<ul> <li>Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No
· Special precautions for user	Not applicable.
<ul> <li>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</li> <li>Not applicable.</li> </ul>	

#### 15 Regulatory information

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

<ul> <li>Section 3</li> </ul>	355 (extremely hazardous substances):
None of t	he ingredients is listed.
· Section 3	313 (Specific toxic chemical listings):
111-76-2	2-butoxyethanol
	propan-2-ol
140-88-5	ethyl acrylate
	(Contd. on page 9)
	US



Page 8/10

(Contd. of page 7)

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

HYMA

Reviewed on 05/06/2019

Page 9/10

### Trade name: W360 MIXING YELLOW

<b></b>		(Contd. of page
-	xic Substances Control Act):	
	2-butoxyethanol	ACTIV
	propan-2-ol	ACTIV
	2-dimethylaminoethanol	ACTIV
	ethyl acrylate	ACTIV
	2-Ethyl-1-hexanol	ACTIV
-	lithium chloride	ACTIV
	water, distilled, conductivity or of similar purity	ACTIV
	s Air Pollutants	
	ethyl acrylate	
· Propositic		
	s known to cause cancer:	
140-88-5	ethyl acrylate	
	s known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause developmental toxicity:	
None of the	e ingredients is listed.	
· Carcinoge	enic categories	
•	ronmental Protection Agency)	
111-76-2	2-butoxyethanol	N
· TLV (Thre	shold Limit Value established by ACGIH)	
111-76-2	2-butoxyethanol	A
67-63-0 J	propan-2-ol	A
140-88-5	ethyl acrylate	A
NIOSH-Ca	(National Institute for Occupational Safety and Health)	· ·
140-88-5	ethyl acrylate	
GHS label		
	ct is classified and labeled according to the Globally Harmonized System (GF	IS).
	ctograms Void	
Signal wo		
· Hazard sta		
Combustib	nary statements	
	<i>r from flames and hot surfaces. – No smoking.</i>	
	ective gloves/protective clothing/eye protection/face protection.	
		(Contd. on page

#### US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

#### Trade name: W360 MIXING YELLOW

(Contd. of page 9)

Page 10/10

In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/06/2019 / -

· Abbreviations and acronyms: ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 4: Flammable liquids - Category 4

US -