

Page 1/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

1 Identification

- · Product identifier
- · Trade name: <u>W510 LEMON YELLOW</u>
- · Article number: W510
- · Details of the supplier of the safety data sheet
- *Manufacturer/Supplier:* General Paint Co. SAL

P.O. Box 7623 Beirut LEBANON info@hymax.biz

· Information department: Product Safety Department

• Emergency telephone number: During normal opening times:1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- Signal word Warning
- Hazard statements
 Combustible liquid.
- · Precautionary statements

Keep away from flames and hot surfaces. – No smoking. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)

 $\begin{array}{c} 2\\ 0\\ 0\\ 0\\ \end{array} \begin{array}{c} \text{Health} = 0\\ \text{Fire} = 2\\ \text{Reactivity} = 0 \end{array}$

· HMIS-ratings (scale 0 - 4)



(Contd. on page 2)

⁻ US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W510 LEMON YELLOW

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:
- 111-76-2 2-butoxyethanol
- 67-63-0 propan-2-ol

4 First-aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

- US



(Contd. of page 1)

Page 2/10

>2.5-≤10%

*≤*2.5%

wiewed on 05/06/2010

acc. to OSHA HCS

Reviewed on 05/06/2019

Trade name: W510 LEMON YELLOW (Contd. of page 2) · Environmental precautions: Do not allow to enter sewers/ surface or ground water. Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. · Reference to other sections No dangerous substances are released. See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. · Protective Action Criteria for Chemicals · PAC-1: 111-76-2 2-butoxyethanol 60 ppm 67-63-0 propan-2-ol 400 ppm 108-01-0 2-dimethylaminoethanol 3.7 ppm 140-88-5 ethyl acrylate 8.3 ppm · PAC-2: 111-76-2 2-butoxyethanol 120 ppm 67-63-0 propan-2-ol 2000* ppm 108-01-0 2-dimethylaminoethanol 40 ppm 140-88-5 ethyl acrylate 36 ppm · PAC-3; 111-76-2 2-butoxyethanol 700 ppm 67-63-0 propan-2-ol 12000** ppm 108-01-0 2-dimethylaminoethanol 72 ppm 140-88-5 ethyl acrylate 240 ppm 7 Handling and storage

· Handling:

- Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- · Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

· Storage class: 10

(Contd. on page 4)



Page 3/10

⁻ US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 4/10

(Contd. of page 3)

Trade name: W510 LEMON YELLOW

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters	meters
----------------------	--------

	76-2 2-butoxyethanol
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 97 mg/m³, 20 ppm BEI
67-6	3-0 propan-2-ol
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI
Ingre	edients with biological limit values:
111-:	76-2 2-butoxyethanol
	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
67-6	3-0 propan-2-ol
	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
	tional information: The lists that were valid during the creation were used as basis.

· General protective and hygienic measures: Wash hands before breaks and at the end of work.

· Breathing equipment: Not required.

(Contd. on page 5)

US



Page 5/10

(Contd. of page 4)

115

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W510 LEMON YELLOW

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

General Information		
Appearance: Form:	Fluid	
Color:	According to product description	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	68 °C (154.4 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W510 LEMON YELLOW

		(Contd. of page
Danger of explosion:	Not determined.	
• Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.032 g/cm³ (8.61204 lbs/gal)	
Relative density	Not determined.	
· Vapor density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	8.0 %	
Water:	64.0 %	
Coating VOC content:	8.05 %	
	244.6 g/l / 2.04 lb/gal	
Material VOC content:	83.0 g/l / 0.69 lb/gal	
Solids content:	26.9 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US



Page 6/10

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W510 LEMON YELLOW

(Contd. of page 6)

Page 7/10

11 Toxicological information · Information on toxicological effects · Acute toxicity: · Primary irritant effect: · on the skin: No irritant effect. · on the eye: No irritating effect. · Sensitization: No sensitizing effects known. · Additional toxicological information: · Carcinogenic categories · IARC (International Agency for Research on Cancer) 111-76-2 2-butoxyethanol 3 3 67-63-0 propan-2-ol 140-88-5 ethyl acrylate 2B · NTP (National Toxicology Program) None of the ingredients is listed. · OSHA-Ca (Occupational Safety & Health Administration) None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 8)

115

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W510 LEMON YELLOW

(Contd. of page 7)

Page 8/10

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number	NOT APPLICABLE
· UN proper shipping name	NOT APPLICABLE
· Transport hazard class(es)	NOT APPLICABLE
· Packing group	NOT APPLICABLE
 Environmental hazards: Marine pollutant: 	No
· Special precautions for user	Not applicable.
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	t II of Not applicable.

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

	855 (extremely hazardous substances):	
None of t	he ingredients is listed.	
· Section :	313 (Specific toxic chemical listings):	
111-76-2	2-butoxyethanol	
67-63-0	propan-2-ol	
140-88-5	ethyl acrylate	
· TSCA (T	oxic Substances Control Act):	
111-76-	2 2-butoxyethanol	ACTIVE
67-63-) propan-2-ol	ACTIVE
		(Contd. on page 9)



Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

HYMA

Reviewed on 05/06/2019

Page 9/10

Trade name: W510 LEMON YELLOW

		td. of page
	2-dimethylaminoethanol	ACTIV
	ethyl acrylate	ACTIV
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVI
	s Air Pollutants	
140-88-5 e	ethyl acrylate	
· Propositio		
	known to cause cancer:	
140-88-5 e	ethyl acrylate	
	known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
	known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
	known to cause developmental toxicity:	
None of the	e ingredients is listed.	
Carcinoge	nic categories	
•	ronmental Protection Agency)	
111-76-2 2	2-butoxyethanol	N
	shold Limit Value established by ACGIH)	
	2-butoxyethanol	A
	propan-2-ol	A
140-88-5 e	ethyl acrylate	A
NIOSH-Ca	(National Institute for Occupational Safety and Health)	
	ethyl acrylate	
Hazard pic Signal wor Hazard sta Combustib Precaution Keep away	et is classified and labeled according to the Globally Harmonized System (GHS). Stograms Void rd Warning Intements le liquid. Inary statements r from flames and hot surfaces. – No smoking.	
	ctive gloves/protective clothing/eye protection/face protection. ire: Use for extinction: CO2, powder or water spray.	
	vell-ventilated place. Keep cool.	
	contents/container in accordance with local/regional/national/international regulati	<i>ons.</i> . on page 1
	(Cond	. on page



Page 10/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W510 LEMON YELLOW

(Contd. of page 9) • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/06/2019 / -

· Abbreviations and acronyms: ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 4: Flammable liquids - Category 4

US -