



Printing date 05/06/2019

Reviewed on 05/06/2019

1 Identification

· Product identifier

· Trade name: W700 PEARL COPPER

· Article number: W700

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: General Paint Co. SAL P.O. Box 7623

Beirut LEBANON info@hymax.biz

- · Information department: Product Safety Department
- · Emergency telephone number: During normal opening times:1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard statements

Combustible liquid.

Causes serious eye irritation.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)





Printing date 05/06/2019 Reviewed on 05/06/2019

Trade name: W700 PEARL COPPER

(Contd. of page 1)

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



 $\frac{2}{100}$ Health = 2 Fire = 2

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangero	us components:	
111-76-2	2-butoxyethanol	>2.5- <i>≤</i> 10%
67-63-0	propan-2-ol	<i>≤</i> 2.5%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)





Printing date 05/06/2019 Reviewed on 05/06/2019

Trade name: W700 PEARL COPPER

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:	
111-76-2 2-butoxyethanol	60 ppm
67-63-0 propan-2-ol	400 ppm
108-01-0 2-dimethylaminoethanol	3.7 ppm
108-65-6 2-methoxy-1-methylethyl acetate	50 ppm
1330-20-7 xylene	130 ppm
100-41-4 ethylbenzene	33 ppm
140-88-5 ethyl acrylate	8.3 ppm
PAC-2:	
111-76-2 2-butoxyethanol	120 ppm
67-63-0 propan-2-ol	2000* ppm
108-01-0 2-dimethylaminoethanol	40 ppm

ÚS





Printing date 05/06/2019 Reviewed on 05/06/2019

Trade name: W700 PEARL COPPER

		(Contd. of page 3)
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
140-88-5	ethyl acrylate	36 ppm
· PAC-3:		
111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** ppm
108-01-0	2-dimethylaminoethanol	72 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
140-88-5	ethyl acrylate	240 ppm

7 Handling and storage

- · Handling:
- Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm Skin

(Contd. on page 5)





Printing date 05/06/2019 Reviewed on 05/06/2019

Trade name: W700 PEARL COPPER

(Contd. of page 4)

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 97 mg/m³, 20 ppm

BEI[°]

67-63-0 propan-2-ol

PEL Long-term value: 980 mg/m³, 400 ppm

REL Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm

RFI`

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid with hydrolysis

67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)





Printing date 05/06/2019 Reviewed on 05/06/2019

Trade name: W700 PEARL COPPER

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and c	hemical properties
· General Information	member properties
· Appearance:	
Form:	Fluid
Color:	According to product description
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 100°C (212°F)
· Flash point:	68 °C (154.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits: Lower:	Not determined.

(Contd. on page 7)





Printing date 05/06/2019 Reviewed on 05/06/2019

Trade name: W700 PEARL COPPER

		(Contd. of page
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.075 g/cm³ (8.97088 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	11.6 %	
Water:	64.9 %	
Coating VOC content:	11.58 %	
 	411.8 g/l / 3.44 lb/gal	
Material VOC content:	124.5 g/l / 1.04 lb/gal	
Solids content:	23.2 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.

(Contd. on page 8)



Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019 Reviewed on 05/06/2019

Trade name: W700 PEARL COPPER

(Contd. of page 7)

- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
111-76-2	2-butoxyethanol	3
	propan-2-ol	3
1330-20-7		3
	ethylbenzene	2B
140-88-5	ethyl acrylate	2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

US





Printing date 05/06/2019 Reviewed on 05/06/2019

Trade name: W700 PEARL COPPER

(Contd. of page 8)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	NOT APPLICABLE
UN proper shipping name	NOT APPLICABLE
Transport hazard class(es)	NOT APPLICABLE
Packing group	NOT APPLICABLE
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable.

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):	
111-76-2	2-butoxyethanol
	propan-2-ol
1330-20-7	
	ethylbenzene
140-88-5	ethyl acrylate
	(Contd. on page 10)

(Contd. on page 10)





Printing date 05/06/2019 Reviewed on 05/06/2019

Trade name: W700 PEARL COPPER

		(Contd. of page
-	xic Substances Control Act):	
	2-butoxyethanol	ACTIV
	propan-2-ol	ACTIV
	2-dimethylaminoethanol	ACTIV
	2-methoxy-1-methylethyl acetate	ACTIV
1330-20-7		ACTIV
	ethylbenzene	ACTIV
	ethyl acrylate	ACTIV
7732-18-5	water, distilled, conductivity or of similar purity	ACTIV
Hazardou	s Air Pollutants	
1330-20-7		
100-41-4	ethylbenzene	
	ethyl acrylate	
Proposition	n 65	
	s known to cause cancer:	
	ethylbenzene	
140-88-5	ethyl acrylate	
Chemicals	s known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
Chemicals	s known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
Chemicals	s known to cause developmental toxicity:	
None of the	e ingredients is listed.	
Carcinoge	enic categories	
•	ronmental Protection Agency)	
111-76-2	2-butoxyethanol	N
1330-20-7	xylene	1
100-41-4	ethylbenzene	D
· TLV (Thre	shold Limit Value established by ACGIH)	
111-76-2	2-butoxyethanol	A
	propan-2-ol	A
1330-20-7	xylene	A
100-41-4	ethylbenzene	A



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019 Reviewed on 05/06/2019

Trade name: W700 PEARL COPPER

(Contd. of page 10)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

140-88-5 ethyl acrylate

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Warning

· Hazard statements

Combustible liquid.

Causes serious eve irritation.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/06/2019 / -
- · Abbreviations and acronyms:

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

(Contd. on page 12)



Page 12/12

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019 Reviewed on 05/06/2019

Trade name: W700 PEARL COPPER

(Contd. of page 11)

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 4: Flammable liquids – Category 4
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A