

Page 1/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

1 Identification

- · Product identifier
- · Trade name: W703 XIRALLIC COPPER
- · Article number: W703
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz

· Information department: Product Safety Department

• Emergency telephone number: During normal opening times:1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- · Signal word Warning
- Hazard statements
 Combustible liquid.
- · Precautionary statements

Keep away from flames and hot surfaces. – No smoking. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)

· HMIS-ratings (scale 0 - 4)



(Contd. on page 2)

⁻ US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W703 XIRALLIC COPPER

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

111-76-2 2-butoxyethanol

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Dilute with plenty of water.

(Contd. on page 3)





(Contd. of page 1)

Page 2/10

>2.5-≤10%

Safety Data Sheet acc. to OSHA HCS

Printing date	05/06/2019
---------------	------------

Reviewed on 05/06/2019

		(Co	ntd. of page
 Methods a Absorb with Dispose co Ensure ade Reference No dangero See Sectio See Sectio 	w to enter sewers/ surface or ground water. nd material for containment and cleaning up: I liquid-binding material (sand, diatomite, acid binders, univ ntaminated material as waste according to item 13. equate ventilation. to other sections bus substances are released. n 7 for information on safe handling. n 8 for information on personal protection equipment. n 12 for dianage.		
	n 13 for disposal information. Action Criteria for Chemicals		
· PAC-1:			
111-76-2	2-butoxyethanol		60 ppm
	propan-2-ol		400 ppn
108-01-0	2-dimethylaminoethanol		3.7 ppm
108-65-6	2-methoxy-1-methylethyl acetate		50 ppm
1330-20-7	xylene		130 ppn
100-41-4	ethylbenzene		33 ppm
140-88-5	ethyl acrylate		8.3 ppm
PAC-2:			
111-76-2	2-butoxyethanol	1	20 ppm
67-63-0	propan-2-ol		2000* ppn
108-01-0	2-dimethylaminoethanol	4	10 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1	,000 ppn
1330-20-7	xylene	S	920* ppm
100-41-4	ethylbenzene	1	100* ppn
140-88-5	ethyl acrylate	3	36 ppm
PAC-3:			
111-76-2	2-butoxyethanol	70) ррт
	propan-2-ol	120	000** ppn
108-01-0	2-dimethylaminoethanol	72	ррт
108-65-6	2-methoxy-1-methylethyl acetate	500	00* ppm
1330-20-7			00* ppm
	ethylbenzene		00* ppm
140-88-5	ethyl acrylate	24) ppm

(Contd. on page 4)

Page 3/10





Page 4/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W703 XIRALLIC COPPER

(Contd. of page 3)

7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values	that require monitoring at the workplace:	

111-76-2 2-butoxyethanol

- PEL Long-term value: 240 mg/m³, 50 ppm
- Skin REL Long-term value: 24 mg/m³, 5 ppm Skin
- TLV Long-term value: 97 mg/m³, 20 ppm BEI

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.

(Contd. on page 5)



Page 5/10

(Contd. of page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W703 XIRALLIC COPPER

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

General Information		
Appearance: Form:	Fluid	
Color:	According to product description	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	68 °C (154.4 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W703 XIRALLIC COPPER

	(C	ontd. of page
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.095 g/cm³ (9.13778 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	8.1 %	
Water:	71.3 %	
Coating VOC content:	8.11 %	
-	405.0 g/l / 3.38 lb/gal	
Material VOC content:	88.8 g/l / 0.74 lb/gal	
Solids content:	20.3 %	
Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US



Page 6/10

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W703 XIRALLIC COPPER

(Contd. of page 6)

Page 7/10

11 Toxicol	ogical information			
Acute tox Primary if on the sk on the ey Sensitiza Additiona	on on toxicological effects ricity: rritant effect: in: No irritant effect. e: No irritating effect. tion: No sensitizing effects known. Il toxicological information: enic categories			
	ernational Agency for Research on Cancer)			
111-76-2	2-butoxyethanol	3		
67-63-0	propan-2-ol	3		
1330-20-7	' xylene	3		
100-41-4	ethylbenzene	2B		
140-88-5	140-88-5 ethyl acrylate 2B			
· NTP (Nati	ional Toxicology Program)	i		
None of th	ne ingredients is listed.			
· OSHA-Ca	(Occupational Safety & Health Administration)			
	ne ingredients is listed.			

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)

US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W703 XIRALLIC COPPER

· Other adverse effects No further relevant information available.

(Contd. of page 7)

Page 8/10

3 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

1		14.0		014		19tion	
	 		P. T V.		 	nation	

· UN-Number	NOT APPLICABLE
· UN proper shipping name	NOT APPLICABLE
· Transport hazard class(es)	NOT APPLICABLE
· Packing group	NOT APPLICABLE
 Environmental hazards: Marine pollutant: 	No
· Special precautions for user	Not applicable.
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	Il of Not applicable.

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
 Sara

		55 (extremely hazardous substances):
	None of the	e ingredients is listed.
	· Section 31	3 (Specific toxic chemical listings):
	111-76-2	2-butoxyethanol
	67-63-0	propan-2-ol
	1330-20-7	xylene
	100-41-4	ethylbenzene
1		(Contd. on page 9)



Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 9/10

US

Trade name: W703 XIRALLIC COPPER

140-88-5	ethyl acrylate	(Contd. of page
	kic Substances Control Act):	
•	2-butoxyethanol	ACTIV
	propan-2-ol	ACTIV
	2-dimethylaminoethanol	ACTIV
	2-methoxy-1-methylethyl acetate	ACTIV
1330-20-7		ACT/V
	ethylbenzene	ACT/V
	ethyl acrylate	ACT/V
	water, distilled, conductivity or of similar purity	ACTIV
	s Air Pollutants	I
1330-20-7	xylene	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	
Propositio	n 65	
Chemicals	s known to cause cancer:	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	
Chemicals	known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
Chemicals	known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
Chemicals	known to cause developmental toxicity:	
None of the	e ingredients is listed.	
Carcinoge	nic categories	
EPA (Envi	ronmental Protection Agency)	
111-76-2	2-butoxyethanol	Λ
1330-20-7	xylene	1
100-41-4	ethylbenzene	Ľ
TLV (Thre	shold Limit Value established by ACGIH)	
111-76-2	2-butoxyethanol	A
	propan-2-ol	A
1330-20-7	xylene	A
100-41-4	ethylbenzene	A
4 40 00 5	ethyl acrylate	A





Page 10/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W703 XIRALLIC COPPER

	(Contd. of page 9)
· NIOSH-Ca (Na	onal Institute for Occupational Safety and Health)
140-88-5 ethyl	orylate
GHS label elei The product is Hazard pictog Signal word W	assified and labeled according to the Globally Harmonized System (GHS). ms Void
• Hazard statem Combustible lic	d.
Wear protective In case of fire:	flames and hot surfaces. – No smoking. Joves/protective clothing/eye protection/face protection. e for extinction: CO2, powder or water spray.
Dispose of con	ntilated place. Keep cool. nts/container in accordance with local/regional/national/international regulations. assessment: A Chemical Safety Assessment has not been carried out.
16 Other inforr	ation
	is based on our present knowledge. However, this shall not constitute a guarantee for uct features and shall not establish a legally valid contractual relationship.
· Contact: N/A	iing SDS: Product safety department ion / last revision 05/06/2019 / - nd acronyms:

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 4: Flammable liquids – Category 4

us -