HYMAX

Page 1/10

Safety Data Sheet acc. to OSHA HCS


Printing date 05/06/2019

Reviewed on 05/06/2019

1 Identification

- · Product identifier
- · Trade name: W723 XIRALLIC WHITE
- · Article number: W723
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz
- · Information department: Product Safety Department
- Emergency telephone number: During normal opening times:1-800-535-5053

2 Hazard(s) identification



Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W723 XIRALLIC WHITE

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:
- 111-76-2 2-butoxyethanol

4 First-aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

(Contd. on page 3)

US

Page 2/10

(Contd. of page 1)

>2.5-*≤*10%

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W723 XIRALLIC WHITE

Ensure ade	equate ventilation.	Contd. of page 2)		
No dangero See Sectio See Sectio See Sectio	<i>to other sections</i> ous substances are released. n 7 for information on safe handling. n 8 for information on personal protection equipment. n 13 for disposal information. Action Criteria for Chemicals			
· PAC-1:				
111-76-2	2-butoxyethanol	60 ppm		
67-63-0	propan-2-ol	400 ppm		
108-01-0	2-dimethylaminoethanol	3.7 ppm		
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm		
1330-20-7	xylene	130 ppm		
100-41-4	ethylbenzene	33 ppm		
140-88-5	ethyl acrylate	8.3 ppm		
· PAC-2:	• PAC-2:			
111-76-2	2-butoxyethanol	120 ppm		
67-63-0	propan-2-ol	2000* ppm		
108-01-0	2-dimethylaminoethanol	40 ppm		
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm		
1330-20-7	xylene	920* ppm		
100-41-4	ethylbenzene	1100* ppm		
140-88-5	ethyl acrylate	36 ppm		
PAC-3:				
111-76-2	2-butoxyethanol	700 ppm		
67-63-0	propan-2-ol	12000** ppm		
108-01-0	2-dimethylaminoethanol	72 ppm		
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm		
1330-20-7		2500* ppm		
	-	1800* ppm		
140-88-5	ethyl acrylate 2	2 <i>40 ppm</i>		

7 Handling and storage

· Handling:

· Precautions for safe handling No special precautions are necessary if used correctly.

• Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

(Contd. on page 4)

US -

Page 3/10

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W723 XIRALLIC WHITE

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

-			
· Com	\cdot Components with limit values that require monitoring at the workplace:		
111-:	76-2 2-butoxyethanol		
PEL	Long-term value: 240 mg/m³, 50 ppm Skin		
REL	Long-term value: 24 mg/m³, 5 ppm Skin		
TLV	Long-term value: 97 mg/m³, 20 ppm BEI		
·Ingre	· Ingredients with biological limit values:		

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

US

Printing date 05/06/2019

HYMA

Reviewed on 05/06/2019

Trade name: W723 XIRALLIC WHITE

· Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

Appearance:		
Form:	Fluid	
Color:	According to product description	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	68 °C (154.4 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	240 °C (464 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.095 g/cm³ (9.13778 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	



Page 5/10

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W723 XIRALLIC WHITE

Solubility in / Miscibility with	(Contd. o	
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/	water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	8.1 %	
Water:	71.4 %	
Coating VOC content:	8.09 %	
Ū	405.4 g/l / 3.38 lb/gal	
Material VOC content:	88.6 g/l / 0.74 lb/gal	
Solids content:	20.3 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

(Contd. on page 7)

3

3

Page 6/10

HYMAX

Page 7/10

(Contd. of page 6)

3

2B

2B

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W723 XIRALLIC WHITE

1330-20-7 xylene

100-41-4 ethylbenzene 140-88-5 ethyl acrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 I ra	nennrt	Into	rmation
17 I G	Πορυιι		IIIIauvii

· UN-Number

NOT APPLICABLE

· UN proper shipping name

(Contd. on page 8)

_____ ÚS

Printing date 05/06/2019

HYMA

Reviewed on 05/06/2019

Trade name: W723 XIRALLIC WHITE

		(Contd. of page 7)	
· Transport hazard class(es)	NOT APPLICABLE		
· Packing group	NOT APPLICABLE		
 Environmental hazards: Marine pollutant: 	No		
 Special precautions for user 	Not applicable.		
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.			

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

None of the ingredients is listed.		
Section 313 (Specific toxic che	emical listings):	
111-76-2 2-butoxyethanol		
67-63-0 propan-2-ol		
1330-20-7 xylene		
100-41-4 ethylbenzene		
140-88-5 ethyl acrylate	0-88-5 ethyl acrylate	
TSCA (Toxic Substances Cont	trol Act):	
111-76-2 2-butoxyethanol		ACTIVI
67-63-0 propan-2-ol		ACTIVI
108-01-0 2-dimethylaminoetha	nol	ACTIVI
108-65-6 2-methoxy-1-methyle	ethyl acetate	ACTIVI
1330-20-7 xylene		ACTIVI
100-41-4 ethylbenzene		ACTIVI
140-88-5 ethyl acrylate		ACTIV
7732-18-5 water, distilled, cond	uctivity or of similar purity	ACTIVI
Hazardous Air Pollutants		
1330-20-7 xylene		
100-41-4 ethylbenzene		
140-88-5 ethyl acrylate		



Page 8/10

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W723 XIRALLIC WHITE

· Proposition 65

· Chemicals known to cause cancer:

100-41-4 ethylbenzene

140-88-5 ethyl acrylate

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Envi	ronmental Protection Agency)	
111-76-2	2-butoxyethanol	NL
1330-20-7	•	1
100-41-4	ethylbenzene	D
· TLV (Thre	shold Limit Value established by ACGIH)	
111-76-2	2-butoxyethanol	A3
67-63-0	propan-2-ol	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
140-88-5	ethyl acrylate	A4
NIOSH-Ca	(National Institute for Occupational Safety and Health))

140-88-5 ethyl acrylate

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms Void

· Signal word Warning

· Hazard statements

Combustible liquid.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

US

Page 9/10

(Contd. of page 8)

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W723 XIRALLIC WHITE

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/06/2019 / -

 Abbreviations and acronyms: ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 4: Flammable liquids – Category 4

us.



Page 10/10