

Page 1/11

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

1 Identification

- · Product identifier
- · Trade name: W730 PEARL GOLD
- · Article number: W730
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. SAL P.O. Box 7623

Beirut LEBANON info@hymax.biz

· Information department: Product Safety Department

• Emergency telephone number: During normal opening times:1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- Signal word Warning
- Hazard statements
 Combustible liquid.
- · Precautionary statements

Keep away from flames and hot surfaces. – No smoking. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)

 $\begin{array}{c} 2\\ 0\\ 0\\ 0\\ \end{array} \begin{array}{c} \text{Health} = 0\\ \text{Fire} = 2\\ \text{Reactivity} = 0 \end{array}$

· HMIS-ratings (scale 0 - 4)



(Contd. on page 2)

⁻ US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W730 PEARL GOLD

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:
- 111-76-2 2-butoxyethanol
- 67-63-0 propan-2-ol

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

US



(Contd. of page 1)

Page 2/11

>2.5-*≤*10% *≤*2.5%

acc. to OSHA HCS

Printing date	05/06/2019
---------------	------------

Trade name: W730 PEARL GOLD

100-41-4 ethylbenzene 140-88-5 ethyl acrylate

Reviewed on 05/06/2019

	nd material for containment and cleaning up:	1 - ()
	h liquid-binding material (sand, diatomite, acid binders, universal binders, saw ontaminated material as waste according to item 13.	dust).
	equate ventilation.	
	to other sections	
No danger	ous substances are released.	
	n 7 for information on safe handling.	
See Sectio	n 8 for information on personal protection equipment.	
See Sectio	n 13 for disposal information. Action Criteria for Chemicals	
· Protective	Action Criteria for Chemicals	
-	2-butoxyethanol	60 ppm
	propan-2-ol	400 ppm
	2-dimethylaminoethanol	3.7 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
140-88-5	ethyl acrylate	8.3 ppm
· PAC-2:		
	2-butoxyethanol	120 ppm
	propan-2-ol	2000* ppm
	2-dimethylaminoethanol	40 ppm
	2-methoxy-1-methylethyl acetate	1,000 ppm
1330-20-7		920* ppm
	ethylbenzene	1100* ppm
140-88-5	ethyl acrylate	36 ppm
· PAC-3:		
	2-butoxyethanol	700 ppm
	propan-2-ol	12000** ppm
	2-dimethylaminoethanol	72 ppm
	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

US

1800* ppm

240 ppm

Page 3/11

(Contd. of page 2)





Page 4/11

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W730 PEARL GOLD

(Contd. of page 3)

7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

111-	76-2 2-butoxyethanol	
PEL	Long-term value: 240 mg/m³, 50 ppm Skin	
REL	Long-term value: 24 mg/m³, 5 ppm Skin	
TLV	Long-term value: 97 mg/m³, 20 ppm BEI	
67-6	3-0 propan-2-ol	
PEL	Long-term value: 980 mg/m³, 400 ppm	
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm	
TLV	Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI	
Ingre	edients with biological limit values:	
111-	76-2 2-butoxyethanol	
	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis	



Page 5/11

(Contd. of page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W730 PEARL GOLD

67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

 Information on basic physic General Information 	cal and chemical properties	
· Appearance:		
Form:	Fluid	
Color:	According to product description	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

HYM

Reviewed on 05/06/2019

Trade name: W730 PEARL GOLD

	(Contd. of p	bage 5
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 100 °C (212 °F)	
· Flash point:	68 °C (154.4 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Not determined.	
· Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
 Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate 	1.108 g/cm³ (9.24626 lbs/gal) Not determined. Not determined. Not determined.	
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.	
 Solvent content: Organic solvents: Water: Coating VOC content: 	8.5 % 68.0 % 8.54 % 384.7 g/l / 3.21 lb/gal	
Material VOC content: Solids content: • Other information	94.7 g/l / 0.79 lb/gal 23.1 % No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 7) US



acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W730 PEARL GOLD

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

· Carcinogenic categories

•	rnational Agency for Research on Cancer)	
111-76-2	2-butoxyethanol	3
	propan-2-ol	3
1330-20-7		3
	ethylbenzene	2B
140-88-5	ethyl acrylate	2B
	onal Toxicology Program)	
None of the	e ingredients is listed.	

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

(Contd. on page 8)



(Contd. of page 6)

Page 7/11

US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W730 PEARL GOLD

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number	NOT APPLICABLE
· UN proper shipping name	NOT APPLICABLE
· Transport hazard class(es)	NOT APPLICABLE
· Packing group	NOT APPLICABLE
 Environmental hazards: Marine pollutant: 	No
· Special precautions for user	Not applicable.
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	t II of Not applicable.







(Contd. of page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W730 PEARL GOLD

(Contd. of page 8)

US

Page 9/11

15 Regulatory information

Section 3	55 (extremely hazardous substances):	
None of th	ne ingredients is listed.	
Section 3	13 (Specific toxic chemical listings):	
111-76-2	2-butoxyethanol	
67-63-0	propan-2-ol	
1330-20-7	' xylene	
	t ethylbenzene	
140-88-5	ethyl acrylate	
TSCA (To	exic Substances Control Act):	
111-76-2	2-butoxyethanol	ACTIV
67-63-0	propan-2-ol	ACTIV
	2-dimethylaminoethanol	ACTIV
108-65-6	2-methoxy-1-methylethyl acetate	ACTIV
1330-20-7	•	ACTIV
	t ethylbenzene	ACTIV
	ethyl acrylate	ACTIV
7732-18-5	water, distilled, conductivity or of similar purity	ACTIV
Hazardou	is Air Pollutants	
1330-20-7	' xylene	
100-41-4	t ethylbenzene	
	ethyl acrylate	
Propositi	on 65	
	's known to cause cancer:	
	ethylbenzene	
140-88-5	ethyl acrylate	
	s known to cause reproductive toxicity for females:	
None of th	ne ingredients is listed.	
Chemical	s known to cause reproductive toxicity for males:	
None of th	ne ingredients is listed.	
Chomica	s known to cause developmental toxicity:	



acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 10/11

Trade name: W730 PEARL GOLD

	ironmental Protection Agency)	
	2-butoxyethanol	N
1330-20-7		1
100-41-4	ethylbenzene	D
· TLV (Thre	shold Limit Value established by ACGIH)	
111-76-2	2-butoxyethanol	A
67-63-0	propan-2-ol	A
1330-20-7	xylene	A
100-41-4	ethylbenzene	A
140-88-5	ethyl acrylate	A
	ct is classified and labeled according to the Globally Harmonized System (GH ctograms Void rd Warning	S).
 Hazard st Combustik Precautio Keep awa Wear prote In case of Store in a 		

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/06/2019 / -
- · Abbreviations and acronyms:

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 11)

⁻ US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W730 PEARL GOLD

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 4: Flammable liquids – Category 4 (Contd. of page 10)

Page 11/11

US

