

Page 1/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

1 Identification

- · Product identifier
- · Trade name: W753 XIRALLIC RED
- · Article number: W753
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. SAL

P.O. Box 7623 Beirut LEBANON info@hymax.biz

· Information department: Product Safety Department

• Emergency telephone number: During normal opening times:1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- Signal word Warning
- Hazard statements
 Combustible liquid.
- · Precautionary statements

Keep away from flames and hot surfaces. – No smoking. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)

 $\begin{array}{c} 2\\ 0\\ 0\\ 0\\ \end{array} \begin{array}{c} \text{Health} = 0\\ \text{Fire} = 2\\ \text{Reactivity} = 0 \end{array}$

· HMIS-ratings (scale 0 - 4)



(Contd. on page 2)

⁻ US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W753 XIRALLIC RED

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

111-76-2 2-butoxyethanol

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



(Contd. of page 1)

>2.5-*≤*10%

Page 2/10

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W753 XIRALLIC RED

		(Contd. of pag
Absorb with Dispose co Ensure ade Reference No dangero See Sectio See Sectio See Sectio	nd material for containment and cleaning up: In liquid-binding material (sand, diatomite, acid binders, un Intaminated material as waste according to item 13. Equate ventilation. To other sections Sous substances are released. In 7 for information on safe handling. In 8 for information on personal protection equipment. In 13 for disposal information. Action Criteria for Chemicals	universal binders, sawdust).
PAC-1:		
111-76-2	2-butoxyethanol	60 ppn
67-63-0	propan-2-ol	400 pp
108-01-0	2-dimethylaminoethanol	3.7 ppr
108-65-6	2-methoxy-1-methylethyl acetate	50 ppn
1330-20-7	xylene	130 pp
100-41-4	ethylbenzene	33 ppn
140-88-5	ethyl acrylate	8.3 ppr
· PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
67-63-0	propan-2-ol	2000* pp
108-01-0	2-dimethylaminoethanol	40 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 pp
1330-20-7	xylene	920* ppn
100-41-4	ethylbenzene	1100* pp
140-88-5	ethyl acrylate	36 ppm
PAC-3:		<u>.</u>
111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** pp
108-01-0	2-dimethylaminoethanol	72 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
	ethyl acrylate	240 ppm

(Contd. on page 4)



Page 3/10



Page 4/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W753 XIRALLIC RED

(Contd. of page 3)

7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values	that require monitoring at the workplace:

111-76-2 2-butoxyethanol

- PEL Long-term value: 240 mg/m³, 50 ppm
- Skin REL Long-term value: 24 mg/m³, 5 ppm Skin
- TLV Long-term value: 97 mg/m³, 20 ppm BEI

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.

(Contd. on page 5)

US



Page 5/10

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W753 XIRALLIC RED

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

Physical and chemical properties

General Information		
Appearance: Form:	Fluid	
Color:	According to product description	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	68 °C (154.4 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W753 XIRALLIC RED

		(Contd. of page 5
· Danger of explosion:	Not determined.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.085 g/cm³ (9.05433 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
 Evaporation rate 	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	8.4 %	
Water:	70.3 %	
Coating VOC content:	8.40 %	
	383.7 g/l / 3.20 lb/gal	
Material VOC content:	91.1 g/l / 0.76 lb/gal	
Solids content:	21.0 %	
 Other information 	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US



Page 6/10

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W753 XIRALLIC RED

(Contd. of page 6)

Page 7/10

· Informatio	on on toxicological effects	
Acute tox		
	ritant effect:	
	n: No irritant effect.	
	e: No irritating effect.	
	ion: No sensitizing effects known.	
Additiona	toxicological information:	
· Carcinoge	nic categories	
· IARC (Inte	rnational Agency for Research on Cancer)	
444 70 0	2-butoxyethanol	
111-76-2	2-buloxyelhanoi	3
	propan-2-ol	3
	propan-2-ol	
67-63-0 1330-20-7	propan-2-ol	3
67-63-0 1330-20-7 100-41-4	propan-2-ol xylene	3
67-63-0 1330-20-7 100-41-4 140-88-5	propan-2-ol xylene ethylbenzene	3 3 2E
67-63-0 1330-20-7 100-41-4 140-88-5 • NTP (Natio	propan-2-ol xylene ethylbenzene ethyl acrylate	3 3 2E

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.

(Contd. on page 8)

US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 8/10

(Contd. of page 7)

Trade name: W753 XIRALLIC RED

· Other adverse effects No further relevant information available.

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

4 A	Tropo	no vt	infor	motion
14	Trans	ροπ	ΠΙΟΓ	mation

· UN-Number	NOT APPLICABLE
· UN proper shipping name	NOT APPLICABLE
· Transport hazard class(es)	NOT APPLICABLE
· Packing group	NOT APPLICABLE
 Environmental hazards: Marine pollutant: 	No
· Special precautions for user	Not applicable.
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

· Section 35	55 (extremely hazardous substances):
None of the	e ingredients is listed.
· Section 31	13 (Specific toxic chemical listings):
111-76-2	2-butoxyethanol
	propan-2-ol
1330-20-7	
100-41-4	ethylbenzene
	(Contd. on page 9)
	US



Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 9/10

US

Trade name: W753 XIRALLIC RED

140-88-5	ethyl acrylate	(Contd. of page
	kic Substances Control Act):	
•	2-butoxyethanol	ACTIV
	propan-2-ol	ACTIV
	2-dimethylaminoethanol	ACTIV
	2-methoxy-1-methylethyl acetate	ACTIV
1330-20-7		ACTIV
	ethylbenzene	ACTIV
	ethyl acrylate	ACTIV
7732-18-5	water, distilled, conductivity or of similar purity	ACTIV
Hazardous	Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	
Propositio	n 65	
Chemicals	known to cause cancer:	
100-41-4 🤅	ethylbenzene	
140-88-5	ethyl acrylate	
Chemicals	s known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
Chemicals	known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
Chemicals	known to cause developmental toxicity:	
	e ingredients is listed.	
Carcinoge	nic categories	
	ronmental Protection Agency)	
-	2-butoxyethanol	Λ
1330-20-7	-	1
	ethylbenzene	D
	shold Limit Value established by ACGIH)	
	2-butoxyethanol	A
	propan-2-ol	A
1330-20-7		A
	ethylbenzene	A
100-41-4		





Page 10/10

us –

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: W753 XIRALLIC RED

	(Contd. of page
 NIOSH-Ca (National Institute for Occupational Safety and Healt) 	ı)
140-88-5 ethyl acrylate	
 GHS label elements The product is classified and labeled according to the Globally Harm. Hazard pictograms Void Signal word Warning Hazard statements Combustible liquid. Precautionary statements Keep away from flames and hot surfaces. – No smoking. Wear protective gloves/protective clothing/eye protection/face protection In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national	ction. onal/international regulations.
· Chemical safety assessment: A Chemical Safety Assessment has	
6 Other information	
This information is based on our present knowledge. However, this any specific product features and shall not establish a legally valid c	
 Department issuing SDS: Product safety department Contact: N/A 	
• Date of preparation / last revision 05/06/2019 / -	
· Abbreviations and acronyms:	
ACGIH: American Conference of Governmental Industrial Hygienists	
EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	