



Printing date 03/03/2020

Reviewed on 09/28/2019

1 Identification

- · Product identifier
- · Trade name: W940 METALLIC COARSE
- · Article number: W940
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. SAL

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

General Paint Co. SAL

P.O. Box 7623

Beirut

LEBANON

info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Lig. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

Combustible liquid.

Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



(Contd. on page 2)





Printing date 03/03/2020 Reviewed on 09/28/2019

Trade name: W940 METALLIC COARSE

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 2 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerou	s components:	
111-76-2	2-butoxyethanol	>2.5-≤10%
7429-90-5	aluminium powder (stabilised)	>2.5-≤10%
67-63-0	propan-2-ol	<i>≤</i> 2.5%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)





Printing date 03/03/2020 Reviewed on 09/28/2019

Trade name: W940 METALLIC COARSE

(Contd. of page 2)

- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

7 70000170	Action official for officialidats		
· PAC-1:			
111-76-2	2-butoxyethanol		60 ppm
67-63-0	propan-2-ol		400 ppm
108-01-0	2-dimethylaminoethanol		3.7 ppm
108-65-6	2-methoxy-1-methylethyl acetate		50 ppm
1330-20-7	xylene		130 ppn
100-41-4	ethylbenzene		33 ppm
140-88-5	ethyl acrylate		8.3 ppm
· PAC-2:			
111-76-2	2-butoxyethanol	1	20 ppm
67-63-0	propan-2-ol	2	000* ppn
108-01-0	2-dimethylaminoethanol	4	0 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1	,000 ppm
1330-20-7	xylene	9	20* ppm
100-41-4	ethylbenzene	1	100* ppn
140-88-5	ethyl acrylate	3	6 ррт
· PAC-3:			
111-76-2	2-butoxyethanol	700) ррт
67-63-0	propan-2-ol	120	000** ppn
108-01-0	2-dimethylaminoethanol		ррт
		(Conf	td. on page





Printing date 03/03/2020 Reviewed on 09/28/2019

Trade name: W940 METALLIC COARSE

		(Contd. of page 3)
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm
	ethylbenzene	1800* ppm
140-88-5	ethyl acrylate	240 ppm

7 Handling and storage

- Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

Atu	is unie, the remaining constituent has no known exposure innits.
111-	76-2 2-butoxyethanol
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 97 mg/m³, 20 ppm BEI
67-6	3-0 propan-2-ol
PEL	Long-term value: 980 mg/m³, 400 ppm

(Contd. on page 5)





Printing date 03/03/2020 Reviewed on 09/28/2019

Trade name: W940 METALLIC COARSE

(Contd. of page 4)

REL Short-term value: 1225 mg/m³, 500 ppm

Long-term value: 980 mg/m³, 400 ppm TLV Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm

BEI

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid with hydrolysis

67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)





Printing date 03/03/2020 Reviewed on 09/28/2019

Trade name: W940 METALLIC COARSE

· Eye protection: Goggles recommended during refilling.

(Contd. of page 5)

Information on basic physical and	chemical properties	
General Information		
Appearance: Form:	Fluid	
Color:	According to product description	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value at 20 °C (68 °F):	7.4-8.4	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	68 °C (154.4 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	240 °C (464 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.049 g/cm³ (8.75391 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	'er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	

(Contd. on page 7)





Printing date 03/03/2020 Reviewed on 09/28/2019

Trade name: W940 METALLIC COARSE

(Contd. of page 6)

· Solvent content:

Organic solvents: 8.8 % Water: 74.2 % Coating VOC content: 8.77 %

416.0 g/l / 3.47 lb/gal 92.0 g/l / 0.77 lb/gal

Solids content: 18.8 %

· Other information No further relevant information available.

10 Stability and reactivity

Material VOC content:

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
111-76-2	2-butoxyethanol	3
	propan-2-ol	3
1330-20-7		3
	ethylbenzene	2B
140-88-5	ethyl acrylate	2B
	(Contd. on p	age 8)

- US





Printing date 03/03/2020 Reviewed on 09/28/2019

Trade name: W940 METALLIC COARSE

(Contd. of page 7)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number	NOT APPLICABLE	
· UN proper shipping name	NOT APPLICABLE	
		(Contd. on page 9)

110





Printing date 03/03/2020 Reviewed on 09/28/2019

Trade name: W940 METALLIC COARSE

		(Contd. of page 8)
· Transport hazard class(es)	NOT APPLICABLE NOT APPLICABLE	
· Packing group	NOT APPLICABLE	
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	t II of Not applicable.	

15 Regulatory information

 $\cdot \ Safety, \ health \ and \ environmental \ regulations/legislation \ specific \ for \ the \ substance \ or \ mixture$

Section 35	55 (extremely hazardous substances):	
None of the	e ingredients is listed.	
Section 31	13 (Specific toxic chemical listings):	
111-76-2	2-butoxyethanol	
67-63-0	propan-2-ol	
1330-20-7	xylene	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	
TSCA (To	xic Substances Control Act):	
111-76-2	2-butoxyethanol	ACTIV
67-63-0	propan-2-ol	ACTIV
108-01-0	2-dimethylaminoethanol	ACTIV
108-65-6	2-methoxy-1-methylethyl acetate	ACTIV
1330-20-7	xylene	ACTIV
100-41-4	ethylbenzene	ACTIV
140-88-5	ethyl acrylate	ACTIV
7732-18-5	water, distilled, conductivity or of similar purity	ACTIV
Hazardous	s Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	

(Contd. on page 10)





Printing date 03/03/2020 Reviewed on 09/28/2019

Trade name: W940 METALLIC COARSE

(Contd. of page 9) · Proposition 65 · Chemicals known to cause cancer: 100-41-4 ethylbenzene 140-88-5 ethyl acrylate · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. Carcinogenic categories · EPA (Environmental Protection Agency) 111-76-2 2-butoxyethanol NL 1330-20-7 xylene 100-41-4 ethylbenzene D · TLV (Threshold Limit Value established by ACGIH) 111-76-2 2-butoxyethanol А3 67-63-0 propan-2-ol A4 1330-20-7 xylene Α4 *A*3 100-41-4 ethylbenzene A4 140-88-5 ethyl acrylate · NIOSH-Ca (National Institute for Occupational Safety and Health) 140-88-5 ethyl acrylate

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

Combustible liquid.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Page 11/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/03/2020 Reviewed on 09/28/2019

Trade name: W940 METALLIC COARSE

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 03/03/2020 / -
- Abbreviations and acronyms:

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flam. Liq. 4: Flammable liquids - Category 4