

Reviewed on 07/27/2021



Safety Data Sheet acc. to OSHA HCS

Printing date 10/01/2021

1 Identification

· Product identifier

· Trade name: W973 METALLIC MEDIUM COARSE

· Article number: W973

- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. SAL

P.O. Box 7623

Beirut

LEBANON

info@hymax.biz

- · Information department: Product Safety Department
- · Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

Combustible liquid.

Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 0 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *0 Fire = 2 Reactivity = 0

(Contd. on page 2)





Printing date 10/01/2021 Reviewed on 07/27/2021

Trade name: W973 METALLIC MEDIUM COARSE

(Contd. of page 1)

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
111-76-2	2-butoxyethanol	>2.5- <i>≤</i> 10%
71-36-3	butan-1-ol	>2.5-≤10%
7429-90-5	aluminium powder (stabilised)	>2.5-≤10%
107-98-2	1-methoxy-2-propanol	<i>≤</i> 2.5%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
 - CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)





Printing date 10/01/2021 Reviewed on 07/27/2021

Trade name: W973 METALLIC MEDIUM COARSE

(Contd. of page 2)

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

111-76-2	2-butoxyethanol	60 ppm
71-36-3	butan-1-ol	60 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
24937-78-8	Ethyl vinyl acetate copolymer	30 mg/m
67-63-0	propan-2-ol	400 ppm
78-83-1	butanol	150 ppm
108-01-0	2-dimethylaminoethanol	3.7 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
71-36-3	butan-1-ol	800 ppm
107-98-2	1-methoxy-2-propanol	160 ppm
24937-78-8	Ethyl vinyl acetate copolymer	330 mg/m
67-63-0	propan-2-ol	2000* ppr
78-83-1	butanol	1,300 ppr
108-01-0	2-dimethylaminoethanol	40 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppr
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppr
PAC-3:		
111-76-2	2-butoxyethanol	700 ppm
71-36-3	butan-1-ol	8000** ppm
107-98-2	1-methoxy-2-propanol	660 ppm
24937-78-8	Ethyl vinyl acetate copolymer	2,000 mg/m
67-63-0	propan-2-ol	12000** ppr





Printing date 10/01/2021 Reviewed on 07/27/2021

Trade name: W973 METALLIC MEDIUM COARSE

		(Contd. of page 3)
78-83-1	butanol	8000* ppm
108-01-0	2-dimethylaminoethanol	72 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.				
111-76-2 2-butoxyethanol				
PEL	Long-term value: 240 mg/m³, 50 ppm Skin			
REL	Long-term value: 24 mg/m³, 5 ppm Skin			
TLV	Long-term value: 20 ppm BEI, A3			
71-36-3 butan-1-ol				
PEL	Long-term value: 300 mg/m³, 100 ppm			
REL	Ceiling limit value: 150 mg/m³, 50 ppm Skin			
TLV	Long-term value: 20 ppm			

(Contd. on page 5)





Printing date 10/01/2021 Reviewed on 07/27/2021

Trade name: W973 METALLIC MEDIUM COARSE

(Contd. of page 4)

107-98-2 1-methoxy-2-propanol

REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm

TLV Short-term value: 100 ppm Long-term value: 50 ppm

A4

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

HS





Printing date 10/01/2021 Reviewed on 07/27/2021

Trade name: W973 METALLIC MEDIUM COARSE

(Contd. of page 5)

Information on basic physical and	chemical properties	
General Information		
Appearance: Form:	Fluid	
Color:	According to product description	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value at 20 °C (68 °F):	7.4-8.4	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	68 °C (154.4 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	240 °C (464 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.023 g/cm³ (8.53694 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with	Al a state of the	
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:	Net determine d	
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:	40.7.0/	
Organic solvents:	10.7 %	
Water: Coating VOC content:	72.0 % 10.72 %	





Printing date 10/01/2021 Reviewed on 07/27/2021

Trade name: W973 METALLIC MEDIUM COARSE

(Contd. of page 6)

Material VOC content:	109.7 g/l / 0.92 lb/gal	
Solids content:	17.5 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.





Printing date 10/01/2021 Reviewed on 07/27/2021

Trade name: W973 METALLIC MEDIUM COARSE

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

4 Transport information		
· UN-Number	NOT APPLICABLE	
· UN proper shipping name	NOT APPLICABLE	
· Transport hazard class(es)	NOT APPLICABLE NOT APPLICABLE	
· Packing group	NOT APPLICABLE	
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
	(0)	

(Contd. on page 9)





Printing date 10/01/2021 Reviewed on 07/27/2021

Trade name: W973 METALLIC MEDIUM COARSE

(Contd. of page 8)

• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Sara		
	5 (extremely hazardous substances):	
None of the	e ingredients is listed.	
· Section 31	3 (Specific toxic chemical listings):	
111-76-2	2-butoxyethanol	
71-36-3	butan-1-ol	
	propan-2-ol	
1330-20-7		
	ethylbenzene	
52-51-7	bronopol (INN)	
· TSCA (Tox	ric Substances Control Act):	
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
	2-butoxyethanol	ACTIVE
71-36-3	B butan-1-ol	ACTIVE
	1-methoxy-2-propanol	ACTIVE
	Ethyl vinyl acetate copolymer	ACTIVE
	propan-2-ol	ACTIVE
	Silicic acid, lithium magnesium sodium salt	ACTIVE
	butanol	ACTIVE
	2-dimethylaminoethanol	ACTIVE
	2-methoxy-1-methylethyl acetate	ACTIVE
1330-20-7		ACTIVE
	ethylbenzene ethylbenzene	ACTIVE
	bronopol (INN)	ACTIVE
2634-33-5	1,2-benzisothiazol-3(2H)-one	ACTIVE

· Haz	ardous	Air F	Pollutants
400			

2682-20-4 2-methyl-2H-isothiazol-3-one

1330-20-7 xylene 100-41-4 ethylbenzene

(Contd. on page 10)

ACTIVE





Printing date 10/01/2021 Reviewed on 07/27/2021

Trade name: W973 METALLIC MEDIUM COARSE

(Contd. of page 9)

· Proposition 65

· Chemicals known to cause cancer:

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Envi	ironmental Protection Agency)			
	2-butoxyethanol	NL		
	butan-1-ol	D		
1330-20-7		1		
100-41-4	ethylbenzene	D		
•	TLV (Threshold Limit Value)			
	2-butoxyethanol	<i>A</i> 3		
	propan-2-ol	A4		
1330-20-7	xylene	A4		
100-41-4	ethylhenzene	Δ 3		

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

Combustible liquid.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

US



Page 11/11

Safety Data Sheet acc. to OSHA HCS

Printing date 10/01/2021 Reviewed on 07/27/2021

Trade name: W973 METALLIC MEDIUM COARSE

(Contd. of page 10)

6 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 10/01/2021 / -
- · Abbreviations and acronyms:

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flam. Liq. 4: Flammable liquids - Category 4