

Page 1/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

1 Identification

- · Product identifier
- · Trade name: <u>B240 GOLDEN GREEN</u>
- · Article number: B240
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. SAL

P.O. Box 7623 Beirut LEBANON info@hymax.biz

· Information department: Product Safety Department

• Emergency telephone number: During normal opening times:1-800-535-5053

2 Hazard(s) identification

Classification of the substance or mixture GHS02 Flame Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

H351 Suspected of causing cancer.



Carc. 2

Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • **Hazard pictograms**



(Contd. on page 2)

US



Page 2/14

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B240 GOLDEN GREEN

· Signal word Warning	(Contd. of page 1)
· Hazard-determining components of labeling:	
n-butyl acetate	
Hazard statements	
Flammable liquid and vapor.	
Causes skin irritation.	
Suspected of causing cancer.	
May cause drowsiness or dizziness.	
· Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understoo	od.
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection).
If on skin (or hair): Take off immediately all contaminated clothing. Rinse	e skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breat	thing.
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/	/international regulations.
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 1	
$\frac{3}{\text{Fire}} = 3$	
$\frac{1}{1} = 0$ Reactivity = 0	
HMIS-ratings (scale 0 - 4)	
HEALTH 1 Health = 1	
FIRE 3 Fire = 3	
$\frac{1}{1} = 0$	

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B240 GOLDEN GREEN

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

 Dangerous 	components:	
	n-butyl acetate	>25- <i>≤</i> 50%
1330-20-7	•	>10- <i>≤</i> 25%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%
100-41-4	ethylbenzene	<i>≤</i> 2.5%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)



(Contd. of page 2)

Page 3/14

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B240 GOLDEN GREEN

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:		
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
100-41-4	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
PAC-2:		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
100-41-4	ethylbenzene	1100* ppm
107-98-2	1-methoxy-2-propanol	160 ppm
PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm

(Contd. on page 5)

US



Page 4/14

(Contd. of page 3)



Page 5/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B240 GOLDEN GREEN

(Contd. of page 4)

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

123-8	6-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m ³ , 150 ppm	
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm	
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm	
1330-	20-7 xylene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm	
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm	
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI	
		(Contd. on page 6)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B240 GOLDEN GREEN

108-	(Contd. of pag 65-6 2-methoxy-1-methylethyl acetate
	L Long-term value: 50 ppm
100-	41-4 ethylbenzene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m³, 20 ppm BEI
Ingre	edients with biological limit values:
1330	-20-7 xylene
	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
100-	41-4 ethylbenzene
	Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)
Addi	tional information: The lists that were valid during the creation were used as basis.
Pers Gen Keep Imme Was Store Avoid Avoid	osure controls onal protective equipment: eral protective and hygienic measures: o away from foodstuffs, beverages and feed. ediately remove all soiled and contaminated clothing. h hands before breaks and at the end of work. e protective clothing separately. d contact with the skin. d contact with the eyes and skin.
In ca	<i>thing equipment:</i> se of brief exposure or low pollution use respiratory filter device. In case of intensive or long sure use respiratory protective device that is independent of circulating air.
	(Contd. on pag



Page 6/14



Page 7/14

(Contd. of page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B240 GOLDEN GREEN

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and General Information	chemical properties	
Appearance:		
Form:	Liquid	
Color:	Green	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	120 °C (248 °F)	
Flash point:	27 °C (80.6 °F)	
Flammability (solid, gaseous):	Not applicable.	

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 8/14

Trade name: B240 GOLDEN GREEN

	(Contd. of page
Ignition temperature:	370 °C (698 °F)
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	1 g/cm³ (8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	72.8 %
Coating VOC content:	72.83 %
-	728.3 g/l / 6.08 lb/gal
Material VOC content:	728.3 g/l / 6.08 lb/gal
Solids content:	27.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 9)

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 9/14

(Contd. of page 8)

Trade name: B240 GOLDEN GREEN

· Hazardous decomposition products: No dangerous decomposition products known.

11	Toxicological	information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat) Dermal

LD50 2,000 mg/kg (rabbit)

- 64742-95-6 Solvent naphtha (petroleum), light arom.
 - Oral LD50 >6,800 mg/kg (rat)
 - LD50 Dermal >3,400 mg/kg (rab)
- Inhalative LC50/4 h >10.2 mg/l (rat)
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

Carcinoge	and categories	
· IARC (Inte	rnational Agency for Research on Cancer)	
1330-20-7	•	3
100-41-4	ethylbenzene	2B
· NTP (Natio	onal Toxicology Program)	
None of th	e ingredients is listed.	
· OSHA-Ca	(Occupational Safety & Health Administration)	
None of th	e ingredients is listed.	

12 Ecological information

· Toxicitv

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.

(Contd. on page 10)

US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B240 GOLDEN GREEN

- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

3 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADR, IMDG, IATA	UN1263	
· UN proper shipping name		
DOT	Paint	
ADR	1263 PAINT	
· IMDG, IATA	PAINT	
· Transport hazard class(es)		
·DOT		
R AMAND F LIGUR		
×		
· Class	3 Flammable liquids	



(Contd. of page 9)

Page 10/14


Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name:	B240 GOLDEN GREEN
made name.	

	(Contd. of page
Label	3
ADR, IMDG, IATA	
3	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, ADR, IMDG, IATA	<i>III</i>
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
EMS Number: Stowage Category	<i>F-E,<u>S-E</u> A</i>
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
ADR	
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 30 mi Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml



Page 11/14



Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B240 GOLDEN GREEN

(Contd. of page 11)

Page 12/14

15 Regulatory information

Section 3	55 (extremely hazardous substances):	
None of th	e ingredients is listed.	
Section 3	13 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
TSCA (To	xic Substances Control Act):	
123-86-4	n-butyl acetate	ACTIV
1330-20-7	xylene	ACTIV
108-65-6	2-methoxy-1-methylethyl acetate	ACTIV
	ethylbenzene	ACTIV
107-98-2	1-methoxy-2-propanol	ACTIV
Hazardou	s Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
Propositio	on 65	
Chemical	s known to cause cancer:	
100-41-4	ethylbenzene	
Chemical	s known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
Chemical	s known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
	s known to cause developmental toxicity:	
Chemical	e ingredients is listed.	
None of th	nic categories	
None of th	enic categories ironmental Protection Agency)	
None of th Carcinoge EPA (Env	ronmental Protection Agency)	
None of th Carcinoge EPA (Env 1330-20-7	ronmental Protection Agency)	
None of th Carcinoge EPA (Env 1330-20-7 100-41-4	ronmental Protection Agency) xylene ethylbenzene	
None of th Carcinoge EPA (Env 1330-20-7 100-41-4	ironmental Protection Agency) xylene ethylbenzene shold Limit Value established by ACGIH)	





Page 13/14

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B240 GOLDEN GREEN

NIOS	(Contd. of page) Contd. of page (Contd. of page) CH-Ca (National Institute for Occupational Safety and Health)
	of the ingredients is listed.
	label elements
	broduct is classified and labeled according to the Globally Harmonized System (GHS).
	rd pictograms
naza	
/ *	
<u> </u>	
GHS	602 GHS07 GHS08
Sign	al word Warning
Haza	rd-determining components of labeling:
	yl acetate
	rd statements
	mable liquid and vapor.
	es skin irritation.
	ected of causing cancer.
	cause drowsiness or dizziness.
	autionary statements
	in special instructions before use.
	ot handle until all safety precautions have been read and understood.
	away from heat/sparks/open flames/hot surfaces No smoking.
	nd/bond container and receiving equipment.
	explosion-proof electrical/ventilating/lighting/equipment.
	only non-sparking tools. precautionary measures against static discharge.
	l breathing dust/fume/gas/mist/vapors/spray
	h thoroughly after handling.
	only outdoors or in a well-ventilated area.
vveal	r protective gloves/protective clothing/eye protection/face protection.
	skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	HALED: Remove person to fresh air and keep comfortable for breathing.
	posed or concerned: Get medical advice/attention.
	a poison center/doctor if you feel unwell.
	ific treatment (see on this label).
	off contaminated clothing and wash it before reuse.
	n irritation occurs: Get medical advice/attention.
	se of fire: Use for extinction: CO2, powder or water spray.
	in a well-ventilated place. Keep container tightly closed.
	in a well-ventilated place. Keep cool.
	e locked up.
Dispo	ose of contents/container in accordance with local/regional/national/international regulations.
	(Contd. on page



Page 14/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B240 GOLDEN GREEN

(Contd. of page 13)

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/06/2019 / -

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 3: Flammable liquids - Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Carc. 2: Carcinogenicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 US