

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

1 Identification

- **Product identifier**
- **Trade name:** B728 XIRALLIC WHITE
- **Article number:** B728
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
info@hymax.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** During normal opening times: 1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 1)

· Hazard pictograms

GHS02 GHS07 GHS08

· Signal word Warning**· Hazard-determining components of labeling:***n*-butyl acetate
ethylbenzene**· Hazard statements***Flammable liquid and vapor.*
Suspected of causing cancer.
May cause drowsiness or dizziness.
*May cause damage to the hearing organs through prolonged or repeated exposure.***· Precautionary statements***Obtain special instructions before use.*
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
*Dispose of contents/container in accordance with local/regional/national/international regulations.***· Classification system:****· NFPA ratings (scale 0 - 4)**Health = 0
Fire = 3
Reactivity = 0

(Contd. on page 3)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: **B728 XIRALLIC WHITE**

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

123-86-4	n-butyl acetate	>50-≤100%
1330-20-7	xylene	>2.5-≤10%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
100-41-4	ethylbenzene	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

US

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
100-41-4	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
7664-38-2	phosphoric acid	3 mg/m ³
70657-70-4	2-methoxypropyl acetate	50 ppm

· **PAC-2:**

123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
100-41-4	ethylbenzene	1100* ppm

(Contd. on page 5)



Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 4)		
107-98-2	1-methoxy-2-propanol	160 ppm
7664-38-2	phosphoric acid	30 mg/m ³
70657-70-4	2-methoxypropyl acetate	1,000 ppm
· PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
7664-38-2	phosphoric acid	150 mg/m ³
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

(Contd. on page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 5)

At this time, the remaining constituent has no known exposure limits.

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

Ingredients with biological limit values:

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

100-41-4 ethylbenzene

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 6)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
*Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.*
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Color:	White

(Contd. on page 8)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 7)

· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	120 °C (248 °F)
· Flash point:	27 °C (80.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	0.962 g/cm ³ (8.02789 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	74.3 %
Coating VOC content:	74.27 %
	714.5 g/l / 5.96 lb/gal
Material VOC content:	714.5 g/l / 5.96 lb/gal
· Solids content:	25.7 %

(Contd. on page 9)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 8)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

(Contd. on page 10)



Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 9)

- **NTP (National Toxicology Program)**
None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name	
· DOT	Paint

(Contd. on page 11)



Safety Data Sheet
acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 10)

<ul style="list-style-type: none"> · ADR · IMDG, IATA 	<p>1263 PAINT PAINT</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	
<div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label 	<p>3 Flammable liquids 3</p>
<ul style="list-style-type: none"> · ADR, IMDG, IATA 	
<div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label 	<p>3 Flammable liquids 3</p>
<ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA 	<p>III</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	<p>No</p>
<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category 	<p>Warning: Flammable liquids 86 F-E, S-E A</p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: · DOT · Quantity limitations 	<p>On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L</p>
<ul style="list-style-type: none"> · ADR · Excepted quantities (EQ) 	<p>Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>

(Contd. on page 12)



Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 11)

<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 1263 PAINT, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
100-41-4	ethylbenzene
7664-38-2	phosphoric acid

· **TSCA (Toxic Substances Control Act):**

123-86-4	n-butyl acetate	ACTIVE
1330-20-7	xylene	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
100-41-4	ethylbenzene	ACTIVE
107-98-2	1-methoxy-2-propanol	ACTIVE
7664-38-2	phosphoric acid	ACTIVE

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**
100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

(Contd. on page 13)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 12)

· **Chemicals known to cause developmental toxicity:**
None of the ingredients is listed.

· **Carcinogenic categories**


· EPA (Environmental Protection Agency)		
1330-20-7	xylene	I
100-41-4	ethylbenzene	D


· TLV (Threshold Limit Value established by ACGIH)		
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3


· **NIOSH-Ca (National Institute for Occupational Safety and Health)**
None of the ingredients is listed.

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**


GHS02


GHS07


GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

n-butyl acetate
ethylbenzene

· **Hazard statements**
Flammable liquid and vapor.
Suspected of causing cancer.
May cause drowsiness or dizziness.
May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 14)
US



Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: B728 XIRALLIC WHITE

(Contd. of page 13)

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:** N/A
- **Date of preparation / last revision** 05/06/2019 / -
- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2