

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

### 1 Identification

- **Product identifier**
- **Trade name:** T330 2K MEDIUM YELLOW
- **Article number:** T330
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. SAL  
P.O. Box 7623  
Beirut LEBANON  
info@hymax.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

*n*-butyl acetate

methyl methacrylate

2,3-epoxypropyl neodecanoate

(Contd. on page 2)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 1)

· **Hazard statements**

*Flammable liquid and vapor.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.*

· **Precautionary statements**

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a poison center/doctor if you feel unwell.  
Specific treatment (see on this label).  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use for extinction: CO2, powder or water spray.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

US

(Contd. on page 3)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 2)

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

123-86-4	n-butyl acetate	>25-≤50%
1330-20-7	xylene	>2.5-≤10%
110-43-0	2-Heptanone	>2.5-≤10%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤2.5%
123-54-6	pentane-2,4-dione	≤2.5%
80-62-6	methyl methacrylate	≤2.5%
26761-45-5	2,3-epoxypropyl neodecanoate	≤2.5%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

US

(Contd. on page 4)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 3)

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

123-86-4	<i>n</i> -butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
110-43-0	2-Heptanone	150 ppm
123-54-6	pentane-2,4-dione	75 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
67-64-1	acetone	200 ppm
75-65-0	2-methylpropan-2-ol	150 ppm
80-62-6	methyl methacrylate	17 ppm
57-55-6	Propylene glycol	30 mg/m <sup>3</sup>
7664-38-2	phosphoric acid	3 mg/m <sup>3</sup>
100-41-4	ethylbenzene	33 ppm
79-41-4	methacrylic acid	6.7 ppm
868-77-9	2-hydroxyethyl methacrylate	1.9 mg/m <sup>3</sup>
77-58-7	dibutyltin dilaurate	1.1 mg/m <sup>3</sup>
280-57-9	triethylenediamine	5.1 mg/m <sup>3</sup>
122-99-6	2-Phenoxyethanol	1.5 ppm
872-50-4	<i>N</i> -methyl-2-pyrrolidone	30 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm
78-83-1	butanol	150 ppm
7447-41-8	lithium chloride	2.3 mg/m <sup>3</sup>
556-67-2	octamethylcyclotetrasiloxane	30 ppm

· **PAC-2:**

123-86-4	<i>n</i> -butyl acetate	200 ppm
1330-20-7	xylene	920* ppm

(Contd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 4)

110-43-0	2-Heptanone	670 ppm
123-54-6	pentane-2,4-dione	110 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
67-64-1	acetone	3200* ppm
75-65-0	2-methylpropan-2-ol	1,300 ppm
80-62-6	methyl methacrylate	120 ppm
57-55-6	Propylene glycol	1,300 mg/m <sup>3</sup>
7664-38-2	phosphoric acid	30 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1100* ppm
79-41-4	methacrylic acid	61 ppm
868-77-9	2-hydroxyethyl methacrylate	21 mg/m <sup>3</sup>
77-58-7	dibutyltin dilaurate	8 mg/m <sup>3</sup>
280-57-9	triethylenediamine	56 mg/m <sup>3</sup>
122-99-6	2-Phenoxyethanol	16 ppm
872-50-4	N-methyl-2-pyrrolidone	32 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm
78-83-1	butanol	1,300 ppm
7447-41-8	lithium chloride	25 mg/m <sup>3</sup>
556-67-2	octamethylcyclotetrasiloxane	68 ppm

**· PAC-3:**

123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
110-43-0	2-Heptanone	4000* ppm
123-54-6	pentane-2,4-dione	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
67-64-1	acetone	5700* ppm
75-65-0	2-methylpropan-2-ol	8000* ppm
80-62-6	methyl methacrylate	570 ppm
57-55-6	Propylene glycol	7,900 mg/m <sup>3</sup>
7664-38-2	phosphoric acid	150 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1800* ppm
79-41-4	methacrylic acid	220 ppm
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m <sup>3</sup>
77-58-7	dibutyltin dilaurate	48 mg/m <sup>3</sup>
280-57-9	triethylenediamine	340 mg/m <sup>3</sup>
122-99-6	2-Phenoxyethanol	97 ppm
872-50-4	N-methyl-2-pyrrolidone	190 ppm

(Contd. on page 6)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

		(Contd. of page 5)
70657-70-4	2-methoxypropyl acetate	5,000 ppm
78-83-1	butanol	8000* ppm
7447-41-8	lithium chloride	150 mg/m <sup>3</sup>
556-67-2	octamethylcyclotetrasiloxane	130 ppm

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

#### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

#### 1330-20-7 xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
-----	--

(Contd. on page 7)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 6)

REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

**110-43-0 2-Heptanone**

PEL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 465 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 233 mg/m <sup>3</sup> , 50 ppm

**123-54-6 pentane-2,4-dione**

TLV	Long-term value: 102 mg/m <sup>3</sup> , 25 ppm Skin
-----	---

**80-62-6 methyl methacrylate**

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 410 mg/m <sup>3</sup> , 100 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm DSEN

**· Ingredients with biological limit values:**

**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 8)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 7)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	White
· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	124 °C (255.2 °F)

· **Flash point:** 25 °C (77 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C (698 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	7.5 Vol %

(Contd. on page 9)



## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 8)

· <b>Vapor pressure at 20 °C (68 °F):</b>	10.7 hPa (8 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.02 g/cm <sup>3</sup> (8.5119 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	41.9 %
<b>Coating VOC content:</b>	41.50 %
	425.8 g/l / 3.55 lb/gal
<b>Material VOC content:</b>	423.3 g/l / 3.53 lb/gal
<b>Solids content:</b>	69.7 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**1330-20-7 xylene**

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

(Contd. on page 10)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 9)

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

· **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer)</b>		
1330-20-7	xylene	3
80-62-6	methyl methacrylate	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 10)

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |  |                            |
|--|----------------------------|
| · <b>UN-Number</b>                                   |                            |
| · <b>DOT, ADR, IMDG, IATA</b>                        | UN1263                     |
| · <b>UN proper shipping name</b>                     |                            |
| · <b>DOT</b>   | Paint                      |
| · <b>ADR</b>   | 1263 PAINT                 |
| · <b>IMDG, IATA</b>                                  | PAINT                      |
| · <b>Transport hazard class(es)</b>                  |                            |
| · <b>DOT</b>   |                            |
|  |                            |
| · <b>Class</b>                                       | 3 Flammable liquids        |
| · <b>Label</b>                                       | 3                          |
|  |                            |
| · <b>ADR, IMDG, IATA</b>                             |                            |
|  |                            |
| · <b>Class</b>                                       | 3 Flammable liquids        |
| · <b>Label</b>                                       | 3                          |
| · <b>Packing group</b>                               |                            |
| · <b>DOT, ADR, IMDG, IATA</b>                        | III                        |
| · <b>Environmental hazards:</b>                      |                            |
| · <b>Marine pollutant:</b>                           | No                         |
| · <b>Special precautions for user</b>                | Warning: Flammable liquids |
| · <b>Hazard identification number (Kemler code):</b> | 30                         |
| · <b>EMS Number:</b>                                 | F-E,S-E                    |

(Contd. on page 12)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 11)

· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
-----	
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
-----	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
75-65-0	2-methylpropan-2-ol
80-62-6	methyl methacrylate
7664-38-2	phosphoric acid
100-41-4	ethylbenzene
122-99-6	2-Phenoxyethanol
872-50-4	N-methyl-2-pyrrolidone
104-68-7	Diethylene glycol monophenyl ether

· **TSCA (Toxic Substances Control Act):**

123-86-4	n-butyl acetate	ACTIVE
1330-20-7	xylene	ACTIVE
110-43-0	2-Heptanone	ACTIVE

(Contd. on page 13)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 12)

123-54-6	pentane-2,4-dione	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
67-64-1	acetone	ACTIVE
75-65-0	2-methylpropan-2-ol	ACTIVE
80-62-6	methyl methacrylate	ACTIVE
26761-45-5	2,3-epoxypropyl neodecanoate	ACTIVE
57-55-6	Propylene glycol	ACTIVE
7664-38-2	phosphoric acid	ACTIVE
100-41-4	ethylbenzene	ACTIVE
79-41-4	methacrylic acid	ACTIVE
868-77-9	2-hydroxyethyl methacrylate	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
280-57-9	triethylenediamine	ACTIVE
122-99-6	2-Phenoxyethanol	ACTIVE
872-50-4	N-methyl-2-pyrrolidone	ACTIVE
78-83-1	butanol	ACTIVE
7447-41-8	lithium chloride	ACTIVE
104-68-7	Diethylene glycol monophenyl ether	ACTIVE
556-67-2	octamethylcyclotetrasiloxane	ACTIVE

**· Hazardous Air Pollutants**

1330-20-7	xylene
80-62-6	methyl methacrylate
100-41-4	ethylbenzene

**· Proposition 65**

**· Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

872-50-4	N-methyl-2-pyrrolidone
----------	------------------------

**· Carcinogenic categories**

**· EPA (Environmental Protection Agency)**

1330-20-7	xylene	/
67-64-1	acetone	/

(Contd. on page 14)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 13)

80-62-6	methyl methacrylate	E, NL
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
67-64-1	acetone	A4
75-65-0	2-methylpropan-2-ol	A4
80-62-6	methyl methacrylate	A4
100-41-4	ethylbenzene	A3
77-58-7	dibutyltin dilaurate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**

*n*-butyl acetate  
methyl methacrylate  
2,3-epoxypropyl neodecanoate

· **Hazard statements**

Flammable liquid and vapor.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a poison center/doctor if you feel unwell.  
Specific treatment (see on this label).

(Contd. on page 15)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2020

Reviewed on 09/28/2019

**Trade name: T330 2K MEDIUM YELLOW**

(Contd. of page 14)

If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.  
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department

· **Contact:** N/A

· **Date of preparation / last revision** 04/21/2020 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3