

Page 1/12

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/22/2023

1 Identification

- · Product identifier
- · Trade name: SO23 VOC BASECOAT REDUCER NORMAL
- · Article number: SO23
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- *Manufacturer/Supplier:* General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz
- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244) departamento de seguridad de los productos

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



Skin Irritation 2	H315 Causes skin irritation.
Eve Irritation 2A	H319 Causes serious eve irritati

e Irritation 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



· Signal word Danger

(Contd. on page 2)

US



Page 2/12


Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/22/2023

Trade name: SO23 VOC BASECOAT REDUCER NORMAL





Page 3/12

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/22/2023

Trade name: SO23 VOC BASECOAT REDUCER NORMAL

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

0	•	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>50- <i>≤</i> 100%
79-20-9	methyl acetate	>10- <i>≤</i> 25%
108-32-7	propylene carbonate	>2.5- <i>≤</i> 10%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. For safety reasons unsuitable extinguishing agents: Water with full jet
- Por salely reasons unsultable extinguishing agents. Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Finite protection of the person of the persons are appreciated and the persons are

• Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023 Trade name: SO23 VOC BASECOAT REDUCER NORMAL (Contd. of page 3) · Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. · Protective Action Criteria for Chemicals · PAC-1: 79-20-9 methyl acetate 250 ppm 108-32-7 propylene carbonate 34 ma/m³ · PAC-2: 79-20-9 methyl acetate 1,700 ppm 108-32-7 propylene carbonate 370 mg/m³ · PAC-3: 79-20-9 methyl acetate 10000* ppm 108-32-7 propylene carbonate 2,200 mg/m³

7 Handling and storage

- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

Page 4/12

[·] Handling:

LIS



Page 5/12

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/22/2023 Trade name: SO23 VOC BASECOAT REDUCER NORMAL (Contd. of page 4) · Control parameters · Components with limit values that require monitoring at the workplace: The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits. 79-20-9 methyl acetate PEL Long-term value: 610 mg/m³, 200 ppm REL Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm TLV Short-term value: 250 ppm Long-term value: 200 ppm · Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eves and skin. · Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Page 6/12

(Contd. of page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/22/2023

Trade name: SO23 VOC BASECOAT REDUCER NORMAL

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

General Information	
Appearance: Form: Color: Odor: Odor threshold:	Liquid Clear Characteristic Not determined.
pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 57 °C (134.6 °F)
Flash point:	14 °C (57.2 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)
Density at 20 °C (68 °F):	1.25795 g/cm³ (10.49759 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

s –



Page 7/12

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/22/2023

Trade name: SO23 VOC BASECOAT REDUCER NORMAL

	(Contd. of pag
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/	water): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
Coating VOC content:	0.00 %
-	0.0 g/l / 0.00 lb/gal
Material VOC content:	0.0 g/l / 0.00 lb/gal
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

Oral LD50 5,800 mg/kg (mouse)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

(Contd. on page 8)



Page 8/12

(Contd. of page 7)

2B

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/22/2023

Trade name: SO23 VOC BASECOAT REDUCER NORMAL

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 9)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/22/2023

Trade name: SO23 VOC BASECOAT REDUCER NORMAL

(Contd. of page 8)

Page 9/12

UN-Number DOT, ADR, IMDG, IATA	UN1263
UN proper shipping name DOT ADR IMDG, IATA	Paint 1263 PAINT PAINT
Transport hazard class(es)	NOT APPLICABLE
DOT	
Class Label	3 Flammable liquids 3
ADR, IMDG, IATA	
Class Label	3 Flammable liquids 3
Packing group DOT, ADR, IMDG, IATA	11
Environmental hazards: Marine pollutant:	No
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids 33 F-E, <u>S-E</u> B
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L





Page 10/12

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/22/2023

Trade name: SO23 VOC BASECOAT REDUCER NORMAL

	(Contd. of page
ADR	
 Excepted quantities (EQ) 	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
·IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

Chemicals known to cause cancer:

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 11)

⁻ US



Page 11/12

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/22/2023

Trade name: SO23 VOC BASECOAT REDUCER NORMAL

(Contd. of page 10)

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)
- None of the ingredients is listed.
- · TLV (Threshold Limit Value)

None of the ingredients is listed.

- · NIOSH-Ca (National Institute for Occupational Safety and Health)
- None of the ingredients is listed.
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



GHS02 GHS07

- · Signal word Danger
- Hazard statements
- Highly flammable liquid and vapor.
- Causes skin irritation.
- Causes serious eye irritation.
- · Precautionary statements
- Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wash thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Specific treatment (see on this label).
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing and wash it before reuse.
- If eye irritation persists: Get medical advice/attention.
- In case of fire: Use CO2, powder or water spray to extinguish.
- Store in a well-ventilated place. Keep cool.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 12)



Page 12/12

(Contd. of page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/22/2023

Trade name: SO23 VOC BASECOAT REDUCER NORMAL

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A

 Date of preparation / last revision 06/22/2023 · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent. Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation - Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A • * Data compared to the previous version altered.