



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

1 Identification

- **Product identifier**
- **Trade name:** B640C BASECOAT ORANGE DOME
- **Article number:** B640C
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
info@hymax.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:**
1-800-535-5053 contract number (89244)
departamento de seguridad de los productos

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

Substances and mixtures which, in contact with water, emit flammable gases 1

H226 Flammable liquid and vapor.

H260 In contact with water releases flammable gases, which may ignite spontaneously.



GHS08 Health hazard

Carcinogenicity 2

Specific Target Organ Toxicity - Repeated Exposure 2

H351 Suspected of causing cancer.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irritation 2

Eye Irritation 2A

Specific Target Organ Toxicity - Single Exposure 3

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 1)

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene

methyl acetate

ethylbenzene

n-butyl acetate

· **Hazard statements**

Flammable liquid and vapor.

In contact with water releases flammable gases, which may ignite spontaneously.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not allow contact with water.

Handle under inert gas. Protect from moisture.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

(Contd. on page 3)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 2)

Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use CO₂, sand, extinguishing powder to extinguish.
Store in a dry place. Store in a closed container.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 2

The substance demonstrates unusual reactivity with water.

- **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 2

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

79-20-9	methyl acetate	>25-≤50%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>10-≤25%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5-≤10%
1330-20-7	xylene	>2.5-≤10%
123-86-4	n-butyl acetate	>2.5-≤10%

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 3)

763-69-9	ethyl 3-ethoxypropionate	≤2.5%
100-41-4	ethylbenzene	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Extinguishing powder. Do not use water.
CO₂. Do not use water.
Sand. Do not use water.
Special powder for metal fires. Do not use water.
CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 5)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 4)

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

• **PAC-1:**

79-20-9	methyl acetate	250 ppm
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
100-41-4	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
7664-38-2	phosphoric acid	3 mg/m ³
70657-70-4	2-methoxypropyl acetate	50 ppm

• **PAC-2:**

79-20-9	methyl acetate	1,700 ppm
1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
100-41-4	ethylbenzene	1100* ppm
107-98-2	1-methoxy-2-propanol	160 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
7664-38-2	phosphoric acid	30 mg/m ³
70657-70-4	2-methoxypropyl acetate	1,000 ppm

• **PAC-3:**

79-20-9	methyl acetate	10000* ppm
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
100-41-4	ethylbenzene	1800* ppm

(Contd. on page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

		(Contd. of page 5)
107-98-2	1-methoxy-2-propanol	660 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
7664-38-2	phosphoric acid	150 mg/m ³
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 4.3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

79-20-9 methyl acetate

PEL	Long-term value: 610 mg/m ³ , 200 ppm
REL	Short-term value: 760 mg/m ³ , 250 ppm Long-term value: 610 mg/m ³ , 200 ppm

(Contd. on page 7)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 6)

TLV	Short-term value: 250 ppm Long-term value: 200 ppm
-----	---

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

· Ingredients with biological limit values:

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

100-41-4 ethylbenzene

BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.

(Contd. on page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 7)

Avoid contact with the eyes and skin.

• **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form:	Liquid
Color:	Orange
• Odor:	Characteristic
• Odor threshold:	Not determined.

• **pH-value:** Not determined.

• **Change in condition**

Melting point/Melting range: Undetermined.

(Contd. on page 9)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 8)

Boiling point/Boiling range:	57 °C (134.6 °F)
· Flash point:	27 °C (80.6 °F)
· Flammability (solid, gaseous):	Flammable. Contact with water liberates extremely flammable gases.
· Auto igniting:	450 °C (842 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
· Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)
· Density at 20 °C (68 °F):	1.09 g/cm ³ (9.09605 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	71.2 %
Coating VOC content:	17.43 % 416.0 g/l / 3.47 lb/gal
Material VOC content:	190.0 g/l / 1.59 lb/gal
Solids content:	28.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.

(Contd. on page 10)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 9)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Contact with water releases flammable gases.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 11)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME


(Contd. of page 10)

- **Additional ecological information:**
- **General notes:**
*Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---------------------|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT | Paint |
| · ADR | 1263 PAINT |
| · IMDG, IATA | PAINT |
| · Transport hazard class(es) | NOT APPLICABLE |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |

(Contd. on page 12)


Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 11)

· Label	3
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
Not applicable.	
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

(Contd. on page 13)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 12)

• **Sara**

• **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

• **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

100-41-4 ethylbenzene

7664-38-2 phosphoric acid

• **TSCA (Toxic Substances Control Act):**

79-20-9 methyl acetate

ACTIVE

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

ACTIVE

9004-36-8 cellulose acetate butyrate

ACTIVE

1330-20-7 xylene

ACTIVE

123-86-4 n-butyl acetate

ACTIVE

763-69-9 ethyl 3-ethoxypropionate

ACTIVE

100-41-4 ethylbenzene

ACTIVE

107-98-2 1-methoxy-2-propanol

ACTIVE

108-65-6 2-methoxy-1-methylethyl acetate

ACTIVE

7664-38-2 phosphoric acid

ACTIVE

• **Hazardous Air Pollutants**

1330-20-7 xylene

100-41-4 ethylbenzene

• **Proposition 65**

• **Chemicals known to cause cancer:**

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

100-41-4 ethylbenzene

• **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

• **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

• **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

• **Carcinogenic categories**

• **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

(Contd. on page 14)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 13)

· TLV (Threshold Limit Value)		
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

4-chloro-alpha,alpha,alpha-trifluorotoluene
methyl acetate
ethylbenzene
n-butyl acetate

· **Hazard statements**

Flammable liquid and vapor.
In contact with water releases flammable gases, which may ignite spontaneously.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.
May cause drowsiness or dizziness.
May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not allow contact with water.
Handle under inert gas. Protect from moisture.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 15)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 14)

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use CO2, sand, extinguishing powder to extinguish.
Store in a dry place. Store in a closed container.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:** N/A
- **Date of preparation / last revision** 06/22/2023
- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

(Contd. on page 16)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B640C BASECOAT ORANGE DOME

(Contd. of page 15)

Substances and mixtures which, in contact with water, emit flammable gases 1: Substances and mixtures which in contact with water emit flammable gases – Category 1

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

US