

Page 1/15

Safety Data Sheet

acc. to OSHA HCS


Printing date 06/22/2023

Reviewed on 06/19/2023

1 Identification

- · Product identifier
- · Trade name: B720C BASECOAT PEARL WHITE
- · Article number: B720C
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- *Manufacturer/Supplier:* General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@hymax.biz
- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244) departamento de seguridad de los productos

2 Hazard(s) identification





acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Page 2/15

Trade name: B720C BASECOAT PEARL WHITE

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 Signal word Danger · Hazard-determining components of labeling: 4-chloro-alpha, alpha, alpha-trifluorotoluene methyl acetate ethvlbenzene · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eve irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. (Contd. on page 3)



acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

(Contd. of page 2)

Page 3/15

Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)

 $\begin{array}{c} \textbf{Health} = 2\\ Fire = 3\\ Reactivity = 0 \end{array}$

· HMIS-ratings (scale 0 - 4)

HEALTH2Health = 2FIRE3Fire = 3REACTIVITY0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
	methyl acetate	>25- <i>≤</i> 50%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>25- <i>≤</i> 50%
		>2.5- <i>≤</i> 10%
1330-20-7	xylene	>2.5- <i>≤</i> 10%
763-69-9	ethyl 3-ethoxypropionate	>2.5- <i>≤</i> 10%
100-41-4	ethylbenzene	<i>≤</i> 2.5%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)

US



Page 4/15

(Contd. of page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Mount respir Wear protect Environmen Methods an Absorb with Dispose com Ensure adect Reference to See Section See Section See Section	 ecautions, protective equipment and emergency procedures ratory protective device. tive equipment. Keep unprotected persons away. ntal precautions: Do not allow to enter sewers/ surface or ground water. nd material for containment and cleaning up: liquid-binding material (sand, diatomite, acid binders, universal binders, sawdu taminated material as waste according to section 13. o other sections 7 for information on safe handling. 8 for information on personal protection equipment. 13 for disposal information. 	ıst).
· PAC-1:		
79-20-9	methyl acetate	250 ppm
1330-20-7	xylene	130 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
100-41-4	ethylbenzene	33 ppm
	D)	ontd. on page 5)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

107-98-2	1-methoxy-2-propanol	(Contd. of page 100 ppm
	n-butyl acetate	5 ppm
	2-methoxy-1-methylethyl acetate	50 ppm
	phosphoric acid	3 mg/m ³
	2-methoxypropyl acetate	50 ppm
	Propylene glycol	30 mg/m
	butanol	150 ppr
PAC-2:		
	methyl acetate	1,700 ppm
1330-20-7	-	920* ppm
	ethyl 3-ethoxypropionate	18 ppm
	ethylbenzene	1100* ppm
	1-methoxy-2-propanol	160 ppm
	n-butyl acetate	200 ppm
	2-methoxy-1-methylethyl acetate	1,000 ppm
	phosphoric acid	30 mg/m ³
	2-methoxypropyl acetate	1,000 ppm
57-55-6	Propylene glycol	1,300 mg/m
78-83-1	butanol	1,300 ppm
PAC-3:		<u>.</u>
79-20-9	methyl acetate	10000* ppn
1330-20-7	xylene	2500* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
123-86-4	n-butyl acetate	3000* ppm
	2-methoxy-1-methylethyl acetate	5000* ppm
7664-38-2	phosphoric acid	150 mg/m³
70657-70-4	2-methoxypropyl acetate	5,000 ppm
57-55-6	Propylene glycol	7,900 mg/m
78-83-1	butanol	8000* ppm

(Contd. on page 6)

Page 5/15



Page 6/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

(Contd. of page 5)

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
 Storage class: 3
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

79-20	0-9 methyl acetate	
PEL	Long-term value: 610 mg/m³, 200 ppm	
REL	Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm	
TLV	Short-term value: 250 ppm Long-term value: 200 ppm	
1330	-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
		(Contd. on page 7)
		118



Page 7/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

	Long-term value: 20 ppm
	BEI, A4
	41-4 ethylbenzene
	Long-term value: 435 mg/m³, 100 ppm
	Short-term value: 545 mg/m ³ , 125 ppm
	Long-term value: 435 mg/m ³ , 100 ppm
ILV	Long-term value: 20 ppm OTO, BEI, A3
Ingre	edients with biological limit values:
1330	-20-7 xylene
	1.5 g/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids
	41-4 ethylbenzene
	0.15 g/g creatinine Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
	tional information: The lists that were valid during the creation were used as basis.
Perso Gene	osure controls onal protective equipment: eral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	h hands before breaks and at the end of work.
	e protective clothing separately. I contact with the eyes and skin.
	thing equipment:
In ca expos	se of brief exposure or low pollution use respiratory filter device. In case of intensive or longe sure use respiratory protective device that is independent of circulating air.
1112	
V	Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 8)

US



acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and General Information	chemical properties
· Appearance:	
Form:	Liquid
Color:	Silver grey
· Odor:	Characteristic
· Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	57 °C (134.6 °F)
Flash point:	-10 °C (14 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ail vapor mixtures are possible.
• Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %

Page 8/15

(Contd. of page 7)



Page 9/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

		(Contd. of page 8)
· Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)	
· Density at 20 °C (68 °F):	1.13 g/cm³ (9.42985 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
 Solubility in / Miscibility with 		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	74.1 %	
Coating VOC content:	13.76 %	
	415.4 g/l / 3.47 lb/gal	
Material VOC content:	155.5 g/l / 1.30 lb/gal	
Solids content:	25.8 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.

(Contd. on page 10)

[–] US



Page 10/15

(Contd. of page 9)

2B

2B

3

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene 1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

(Contd. of page 10)

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
ADR IMDG, IATA	1263 PAINT PAINT	
Transport hazard class(es)	NOT APPLICABLE	
DOT		
R MAILER E ICON		
Class	3 Flammable liquids	
Label	3	
ADR, IMDG, IATA		
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT, ADR, IMDG, IATA	111	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
EMS Number:	F-E, <u>S-E</u>	
Stowage Category	A	
Transport in bulk according to Ann MARPOL73/78 and the IBC Code	ex II of Not applicable.	



Page 11/15



Page 12/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

	(Contd. of page
Transport/Additional information:	
DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
ADR	
 Excepted quantities (EQ) 	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
1330-20-7 xylene	
100-41-4 ethylbenzene	
7664-38-2 phosphoric acid	
TSCA (Toxic Substances Control Act):	
79-20-9 methyl acetate	ACTIV
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotolu	ene ACTIV
9004-36-8 cellulose acetate butyrate	ACTIV
1330-20-7 xylene	ACTIV
763-69-9 ethyl 3-ethoxypropionate	ACTIV
100-41-4 ethylbenzene	ACTIV
107-98-2 1-methoxy-2-propanol	ACTIV
123-86-4 n-butyl acetate	ACTIV



Page 13/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

		(Contd. of page 12
	2-methoxy-1-methylethyl acetate	ACTIVE
	phosphoric acid	ACTIVE
	Propylene glycol	ACTIVE
78-83-1	butanol	ACTIVE
· Hazardou	s Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
· Propositio	on 65	
· Chemicals	s known to cause cancer:	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	
100-41-4	ethylbenzene	
· Chemicals	s known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause developmental toxicity:	
None of the	e ingredients is listed.	
· Carcinoge	enic categories	
· EPA (Envi	ronmental Protection Agency)	
1330-20-7	xylene	1
100-41-4	ethylbenzene	D
· TLV (Thre	shold Limit Value)	
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	•
None of the	e ingredients is listed.	
• GHS label The produce • Hazard pice	ct is classified and labeled according to the Globally Harmonized System (G	GHS).



· Signal word Danger

(Contd. on page 14)



Page 14/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

	(Contd. of page 1
Hazard-determining components of labeling:	
4-chloro-alpha,alpha,alpha-trifluorotoluene	
methyl acetate	
ethylbenzene	
Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Causes serious eye irritation.	
Suspected of causing cancer.	
May cause drowsiness or dizziness.	
May cause damage to the hearing organs through prolonged or repeated ex	posure.
Precautionary statements	,
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse ski	n with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing	
If in eyes: Rinse cautiously with water for several minutes. Remove contact	
to do. Continue rinsing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/inte	ernational regulations.
Chemical safety assessment: A Chemical Safety Assessment has not bee	

(Contd. on page 15)



Page 15/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

Trade name: B720C BASECOAT PEARL WHITE

(Contd. of page 14)

119

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 06/22/2023

 Abbreviations and acronvms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation - Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Carcinogenicity 2: Carcinogenicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2