

Page 1/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023

Reviewed on 06/19/2023

1 Identification

- · Product identifier
- · Trade name: B988C BASECOAT SILVER DOLLAR FINE
- · Article number: B988C
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: General Paint Co. SAL

P.O. Box 7623 Beirut

LEBANON info@hymax.biz

- · Information department: Product Safety Department
- Emergency telephone number:

1-800-535-5053 contract number (89244) departamento de seguridad de los productos

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

H351 Suspected of causing cancer. Carcinogenicity 2

Specific Target Organ Toxicity - Repeated Exposure H372-H373 Causes damage to the central nervous system through prolonged or

repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.



H315 Causes skin irritation. Skin Irritation 2

Eye Irritation 2A H319 Causes serious eye irritation.

(Contd. on page 2)



Page 2/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

(Contd. of page 1)

Specific Target Organ Toxicity - Single Exposure 3 H336

May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

4-chloro-alpha, alpha, alpha-trifluorotoluene

methyl acetate

ethylbenzene

Naphtha (petroleum), hydrodesulfurized heavy

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

(Contd. on page 3)



Page 3/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

(Contd. of page 2)

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
	methyl acetate	>25-≤50%
	4-chloro-alpha,alpha,alpha-trifluorotoluene	>25-≤50%
	Solvent naphtha (petroleum), light arom.	>2.5-≤10%
1330-20-7	xylene	>2.5- <i>≤</i> 10%
7429-90-5	aluminium powder (stabilised)	>2.5-≤10%
763-69-9	ethyl 3-ethoxypropionate	≤2.5%
100-41-4	ethylbenzene	≤2.5%
		(Contd. on page 4)

US



Page 4/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

(Contd. of page 3)

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

≤2.5%

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 5)



Page 5/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

(Contd. of page 4)

	Reference	to other	sections
•	ハモιモιモιι	lu ulliel	3 世にはひける

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
	methyl acetate	250 ppm
1330-20-7	xylene	130 ppn
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppn
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
95-63-6	1,2,4-trimethylbenzene	140 ppn
7664-38-2	phosphoric acid	3 mg/m ³
70657-70-4	2-methoxypropyl acetate	50 ppm
PAC-2:		•
79-20-9	methyl acetate	1,700 ppn
1330-20-7	xylene	920* ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
100-41-4	ethylbenzene	1100* ppn
107-98-2	1-methoxy-2-propanol	160 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppn
95-63-6	1,2,4-trimethylbenzene	360 ppm
7664-38-2	phosphoric acid	30 mg/m³
70657-70-4	2-methoxypropyl acetate	1,000 ppn
PAC-3:		·
79-20-9	methyl acetate	10000* ppn
1330-20-7	xylene	2500* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
95-63-6	1,2,4-trimethylbenzene	480 ppm
7664-38-2	phosphoric acid	150 mg/m³



Page 6/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

 70657-70-4
 2-methoxypropyl acetate
 (Contd. of page 5)

 5,000 ppm
 5,000 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

79-2	79-20-9 methyl acetate		
PEL	Long-term value: 610 mg/m³, 200 ppm		
REL	Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm		
TLV	Short-term value: 250 ppm Long-term value: 200 ppm		
	(Contd. on page 7)		

(Contd. on page 7)



Page 7/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

	(Contd. of page 6)
133	0-20-7 xylene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 20 ppm BEI, A4
100-	-41-4 ethylbenzene
PEL	. Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	/ Long-term value: 20 ppm OTO, BEI, A3
· Ingr	redients with biological limit values:
133	0-20-7 xylene
BEI	1.5 g/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids
100-	-41-4 ethylbenzene
BEI	0.15 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



(Contd. on page 8)



Page 8/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

(Contd. of page 7)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties		
· Information on basic physical and	chemical properties	
· General Information		
· Appearance:		
Form:	Liquid	
Color:	Silver grey	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	57 °C (134.6 °F)	
· Flash point:	-10 °C (14 °F)	
· Flammability (solid, gaseous):	Highly flammable.	
· Auto igniting:	450 °C (842 °F)	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	

(Contd. on page 9)



Page 9/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

	(Contd. of pag
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)
Density at 20 °C (68 °F):	1.1 g/cm³ (9.1795 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	75.0 %
Coating VOC content:	14.89 %
_	419.9 g/l / 3.50 lb/gal
Material VOC content:	163.8 g/l / 1.37 lb/gal
Solids content:	25.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

US



Page 10/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

(Contd. of page 9)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

9 9 9	, om outgened	
· IARC (Int	ternational Agency for Research on Cancer)	
98-56-6	6 4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
1330-20-7	7 xylene	3
100-41-4	4 ethylbenzene	2B
· NTP (Nat	tional Toxicology Program)	
None of the	he ingredients is listed.	
· OSHA-Ca	a (Occupational Safety & Health Administration)	
None of the	he ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 11)



Page 11/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

· Other adverse effects No further relevant information available.

(Contd. of page 10)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· DOT, ADR, IMDG, IATA

· Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADR, IMDG, IATA	UN1263
UN proper shipping name	
DOT	Paint
ADR	1263 PAINT
IMDG, IATA	PAINT
Transport hazard class(es)	NOT APPLICABLE
T, AMERICA COCK	
Class	3 Flammable liquids
	3 Flammable liquids 3
Class Label ADR, IMDG, IATA	3 Flammable liquids 3
Label	3 Flammable liquids 3 3 Flammable liquids 3

Ш

(Contd. on page 12)



Page 12/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

	(Contd. of pag
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · EMS Number: · Stowage Category	Warning: Flammable liquids F-E, <u>S-E</u> A
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	III of Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

 Section 355 	(extremel	v hazardous	substances):
---------------------------------	-----------	-------------	------------	----

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

100-41-4 ethylbenzene

95-63-6 1,2,4-trimethylbenzene

7664-38-2 phosphoric acid

· TSCA (Toxic Substances Control Act):

79-20-9 methyl acetate

ACTIVE

(Contd. on page 13)



Page 13/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

00 50 0	A ablance alpha alpha alpha trifficaratali cana	(Contd. of page
	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVI
	cellulose acetate butyrate	ACTIV
1330-20-7		ACTIV
	ethyl 3-ethoxypropionate	ACTIV
	ethylbenzene	ACTIV
	1-methoxy-2-propanol	ACTIVI
	2-methoxy-1-methylethyl acetate	ACTIV
	1,2,4-trimethylbenzene	ACTIV
7664-38-2	phosphoric acid	ACTIV
	s Air Pollutants	
1330-20-7		
100-41-4	ethylbenzene	
Proposition	on 65	
Chemical	s known to cause cancer:	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	
100-41-4	ethylbenzene	
Chemical	s known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
Chemical	s known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
Chemical	s known to cause developmental toxicity:	
None of th	e ingredients is listed.	
Carcinoge	enic categories	
EPA (Env	ironmental Protection Agency)	
1330-20-7	xylene	1
100-41-4	ethylbenzene	1
95-63-6	1,2,4-trimethylbenzene	1
TLV (Thre	shold Limit Value)	
1330-20-7	xylene	A
100-41-4	ethylbenzene	A
	(National Institute for Occupational Safety and Health)	
NIOSH-Ca		,

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 14)



Page 14/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

(Contd. of page 13)

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

4-chloro-alpha,alpha,alpha-trifluorotoluene methyl acetate

ethylbenzene

Naphtha (petroleum), hydrodesulfurized heavy

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

(Contd. on page 15)



Page 15/15

Safety Data Sheet acc. to OSHA HCS

Printing date 06/22/2023 Reviewed on 06/19/2023

Trade name: B988C BASECOAT SILVER DOLLAR FINE

(Contd. of page 14)

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 06/22/2023
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2

Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Śingle Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1