

Page 1/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

1 Identification

- · Product identifier
- · Trade name: N20 FIBRE GLASS
- · Article number: N20
- · Details of the supplier of the safety data sheet
- *Manufacturer/Supplier:* General Paint Co. SAL P.O. Box 7623
- Beirut LEBANON info@hymax.biz
- · Information department: Product Safety Department
- Emergency telephone number: During normal opening times:1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame Flam. Liq. 3 H226 Flammable liquid and vapor. GHS08 Health hazard Carc. 2 H351 Suspected of causing cancer. Repr. 2 H361 Suspected of damaging fertility or the unborn child. STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) US



Page 2/14

(Contd. of page 1)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Hazard pictograms

Reviewed on 05/06/2019

Trade name: N20 FIBRE GLASS

GHS02 GHS07 GHS08 Signal word Danger · Hazard-determining components of labeling: styrene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsina. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3)




acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 3/14

Trade name: N20 FIBRE GLASS



· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

100-42-5 styrene

>10-*≤*25%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

ús

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: N20 FIBRE GLASS

 Indication of any immediate medical attention and special treatment needed No further relevant information available. (Contd. of page 3)

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

20 ppm
130 ppm
1100* ppm

(Contd. on page 5)



Page 4/14



Page 5/14

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: N20 FIBRE GLASS

(Contd. of page 4)

7 Handling and storage

· Handling:

- Precautions for safe handling
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:			
100-	42-5 styrene		
PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs		
REL	Short-term value: 425 mg/m³, 100 ppm Long-term value: 215 mg/m³, 50 ppm		
TLV	Short-term value: (170) mg/m³, (40) ppm Long-term value: (85) NIC-8.5 mg/m³, (20) NIC-2 ppm BEI, NIC-A3, NIC-OTO		
	(Contd. on page 6)		



Page 6/14

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: N20 FIBRE GLASS

	(Contd. of page 5
-	edients with biological limit values:
	42-5 styrene
BEI	400 mg/g creatinine Medium: urine Time: end of shift Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)
	0.2 mg/L Medium: venous blood Time: end of shift Parameter: Styrene (semi-quantitative)
Add	itional information: The lists that were valid during the creation were used as basis.
Gen Keej Imm Was Store Avoi Brea In ca expo	Sonal protective equipment: eral protective and hygienic measures: to away from foodstuffs, beverages and feed. ediately remove all soiled and contaminated clothing. In hands before breaks and at the end of work. e protective clothing separately. d contact with the eyes and skin. athing equipment: ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longe posure use respiratory protective device that is independent of circulating air. Section of hands:
and the	Protective gloves
Due prep Sele degr	glove material has to be impermeable and resistant to the product/ the substance/ the preparation. to missing tests no recommendation to the glove material can be given for the product/ the aration/ the chemical mixture. oction of the glove material on consideration of the penetration times, rates of diffusion and the adation erial of gloves
The qual subs be c	selection of the suitable gloves does not only depend on the material, but also on further marks of ity and varies from manufacturer to manufacturer. As the product is a preparation of severa stances, the resistance of the glove material can not be calculated in advance and has therefore to hecked prior to the application. etration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: N20 FIBRE GLASS

· Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

General Information	
Appearance:	
Form:	putty
Color:	olive green
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	145 °C (293 °F)
Flash point:	31 °C (87.8 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	480 °C (896 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ail vapor mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
Vapor pressure at 20 °C (68 °F):	6 hPa (4.5 mm Hg)
Density at 20 °C (68 °F):	1.49 g/cm³ (12.43405 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

US





(Contd. of page 6)

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Page 8/14

Trade name: N20 FIBRE GLASS

	(Contd. of	f page
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/		
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	14.5 %	
Coating VOC content:	14.53 %	
Ū	216.5 g/l / 1.81 lb/gal	
Material VOC content:	216.5 g/l / 1.81 lb/gal	
Solids content:	83.3 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

100-42-5 styrene

Oral LD50 5,000 mg/kg (rat)

Inhalative LC50/4 h 24 mg/l (rat)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 9)



acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: N20 FIBRE GLASS

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

100-42-5 styrene

· NTP (National Toxicology Program)

100-42-5 styrene

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

3 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10) US



(Contd. of page 8)

Page 9/14

2B

R

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: N20 FIBRE GLASS

(Contd. of page 9)

Page 10/14

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name DOT ADR IMDG, IATA	Paint related material 1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL	
Transport hazard class(es) DOT		
Class Label	3 Flammable liquids 3	
ADR, IMDG, IATA	3 Flammable liquids 3	
Packing group DOT, ADR, IMDG, IATA		
Environmental hazards: Marine pollutant:	No	
Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids F-E, <u>S-E</u> A	
Transport in bulk according to An MARPOL73/78 and the IBC Code	nex II of Not applicable.	





Page 11/14

Safety Data Sheet acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: N20 FIBRE GLASS

	(Contd. of page 1
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

Section 355 (extremely hazardous substances): None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
100-42-5 styrene	
TSCA (Toxic Substances Control Act):	
100-42-5 styrene	ACTIV
38668-48-3 1,1'-(p-tolylimino)dipropan-2-ol	ACTIV
· Hazardous Air Pollutants	
100-42-5 styrene	
Proposition 65	
· Chemicals known to cause cancer:	
Chemicals known to cause cancer: 100-42-5 styrene	
100-42-5 styrene	
Chemicals known to cause cancer: 100-42-5 styrene Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed.	
100-42-5 styrene • Chemicals known to cause reproductive toxicity for females:	
100-42-5 styrene Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed.	



Page 12/14

(Contd. of page 11)

A4

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: N20 FIBRE GLASS

 Chemicals known to cause develop 	pmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

100-42-5 styrene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: stvrene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to the hearing organs through prolonged or repeated exposure. Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

⁻ US

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: N20 FIBRE GLASS

(Contd. of page 12)

Page 13/14

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

6 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 05/06/2019 / -

· Abbreviations and acronyms: ICAO: International Civil Aviation Organisation RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety **OSHA: Occupational Safety & Health** TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Lig. 3: Flammable liquids – Category 3

(Contd. on page 14)

acc. to OSHA HCS

Printing date 05/06/2019

Reviewed on 05/06/2019

Trade name: N20 FIBRE GLASS

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1



HYMA

(Contd. of page 13)

Page 14/14

US -