



# N10 - 1K Putty Fine Beige


## Description:

1K fine putty is a nitrocellulose fine glazing putty to fill surface imperfections such as scratch marks and pinholes.

1K fine putty is very fast drying when applied in thin coats. It is easy to apply and easy to sand.

## Suitable Substrates:

- Through – hardened sanded paintwork.
- Sanded primed surfaces.




Ready to use

## Application:



Apply one to three thin coats as necessary.



15 min at 20°C (70°F)  
Between coats



20 min at 20°C (70°F)



Dry sand with P 400 to P 500 grit paper.



P 600 to P 800 grit wet



## N10 - 1K Putty Fine Beige



1K Fine Putty can be recoated with any Hymax primer surfacer or sealer, it can also be directly topcoated Hymax with basecoat solvent.

---



Wear suitable protection

---

**Flash Point:** 28°C (82.4°F)

---

**Specific Gravity:** 1.47 kg/cm<sup>3</sup>

---

**Solids Content:** 61.2 % by weight

---

**VOC (2004/42/EC):** 2004/42/IIB (b) (250)250. The EU limit value for this product (product category IIB.b) in ready to use form is max 250g/ltr. The VOC content of this product in ready for use form is max. 250 g/l.

---

**Available colors:** N10 Beige

---

**SDS:** See the safety data sheet