

Page 1/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

 undertaking 1.1 Product identifier Trade name: S11 P.U. THINNER NORMAL Article number: S11 1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint Sector of Use Wal Industrial Uses: Uses of substances such as or in preparations at industrial sites SU2 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet 1.3 Details of the supplier of the safety data sheet 1.4 Details of the supplier of the safety data sheet 1.3 Details of the supplier of the safety data sheet 1.3 Details of the supplier of the safety data sheet 1.3 Details of the supplier of the safety data sheet 1.3 Details of the supplier of the Safety data sheet 1.4 Details of the supplier of the Safety Department 1.4 Details of the supplier of themisture refore to the plants, France Tel:+33(0)175293559 Eventer information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 EVENOUS: Hazerds identification Explore (EC) No 1272/2008 Explore fame Explore fame Endication according to Regulation (EC) No 1272/2008 Emergency telephoter Fame Lip 2 Hz25 Highly flammable liquid and vapour.	 undertaking 1.1 Product identifier Trade name: S11 P.U. THINNER NORMAL Article number: S11 1.2 Retevant identified uses of the substance or mixture and uses advised against use as industrial paint Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU2 Professional uses: Public domain (administration, education, entertainment, services, crafismen) Product category Posa Coatings and paints, thinners, paint removers POS Fillers, puties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: P. O. Box 7623 Beint LEBANON info@hymax.biz Genérale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel-43(0)175293559 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 Section of the substance or mixture Classification according to Regulation (EC) No 1272/2008 With a substance or mixture Ause Tox. 4 H332 Harmful fi inhaled. Skin Init. 2 H32 Haufful fi inhaled. Skin Init. 2 H32 Haufful fi inhaled. Skin Init. 2 H33 Causes serious eye irritation. Sy of KS 3 Sy of KS 3 Sy of KS 3 Sy of KS 3 Sy of KS 4 H332 Harmful fi inhaled. Skin Init. 2 H332 Harmful fi inhaled. Skin Init. 2 H332 Causes serious eye irritation. Sy of KS 3 H34 H35 H35 H35 H34 Kin Init. 2 H35 May be cause respiratory irritation. Sy of KS 3 Kin Init. 2 H332 May cause respiratory irritation. Sy of KS 3 Kin Init. 2 H33 Kin Init. 2 H33 Kin Initation. Kin Init. 2<	SECTION 1: Identification of the substance/mixture and of the company/
 Trade name: <u>S11 P.U. THINNER NORMAL</u> Article number: <u>S11</u> 12 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU2 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: P.O. Box 7623 Beint LEBANON info@hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:-33(0)175293559 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 SECTION 2: Hazards identification Elsesification of the substance or mixture Flam. Liq. 2 H225 Highly flammable liquid and vapour.	 Trade name: <u>S11 P.U. THINNER NORMAL</u> Article number: S11 1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: P.O. Box 7623 Beinut LEBANON info@hymax.biz Generate de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 Section of the substance or mixture Classification according to Regulation (EC) No 12722008 Fam. Liq. 2 H225 Highly flammable liquid and vapour. Kin Irit. 2 Kass Almoral Irit inhaled. Skin Irit. 2 H32 Causes serious eye irritation. Eye Irit. 2 Fur Sa Cassification Sim Iritation. Eye Irit. 2 H33 Causes serious eye irritation. Eye Irit. 2 H33 May cause respiratory irritation. Eye Irit. 2 H33 May cause resp	
 Article number: S11 12 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU2 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, puties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet Manufacturer/Supplier: P.O. Box 7623 Beirut LEBANON info@myma.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 SECTION 2: Hazards identification Elassification of the substance or mixture Classification of the substance or mixture Total category (Elassification generation) GHS02 flame Fam. Liq. 2 H225 Highly flammable liquid and vapour.	 Article number: S11 1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint Sector of Use Sul Industrial Uses: Uses of substances such as or in preparations at industrial sites SU2 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC3a Coatings and paints, thinners, paint removers PC3b Fillers, putties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: P. O. Box 7623 Beintu LEBANON info@hymax.biz Generale de Plenture, 70 Rue Contambert 75116 Paris, France Teirther information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 Sector V1 Section of the substance or mixture Elassification according to Regulation (EC) No 1272/2008 Further information defined input data data vapour. <i>Question</i> Fam. Liq. 2 H225 Highly flammable liquid and vapour. <i>Question</i> Acute Tox. 4 H332 Harmful if inhaled. Sin Irrit. 2 H315 Causes skin irritation. Ey Irrit. 2 H315 Causes skin irritation. Ey Irrit. 2 H315 Causes serious eye irritation. System Irritation. Ey Irrit. 2 H315 Causes serious eye irritation. Ey Irrit. 2 H315 Causes eserious eye irritation. System Irritation. Ey Irritation. E	· 1.1 Product identifier
 1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU2 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: P.O. Box 7623 Beirut LEBANON info @hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 SECTION 2: Hazards identification Elassification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Fam. Liq. 2 H225 Highly flammable liquid and vapour.	 1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU2 Professional uses: Public domain (administration, education, entertainment, services, crafismen) Product category PC96 Coatings and paints, thinners, paint removers PC95 Fillers, putties, plasters, modelling clay Application of the substance / the mixture refer to the relevant Technical Data Sheet 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: P.O. Box 7623 Beinu LEBANON into@hymax.biz Générale de Peinture, 70 Rue Contambert 75116 Paris, France Tel:+33(0)175293559 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 SectrON 2: Hazards identification Elassification according to Regulation (EC) No 1272/2008 Fam. Liq. 2 H225 Highly flammable liquid and vapour. Question 4: 1315 Causes skin irritation. Eye Int: 2 H315 Causes skin irritation. Eye Int: 2 H315 Causes skin irritation. Eye Int: 2 H315 Causes serious eye irritation. Story SE 3 H335 May cause respiratory irritation.	· Trade name: <u>S11 P.U. THINNER NORMAL</u>
 Manufacturer/Supplier: P.O. Box 7623 Beirut LEBANON info@hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 SECTION 2: Hazards identification 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour.	 Manufacturer/Supplier: P.O. Box 7623 Beinut LEBANON info@hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559 Further information obtainable from: Product Safety Department 1.4 Emergency telephone number: +33 (0)6 07 87 13 41 SECTION 2: Hazards identification 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. GHS07 Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation. 	 1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay
 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. 	 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. GHS07 Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation. 	 Manufacturer/Supplier: P.O. Box 7623 Beirut LEBANON info@hymax.biz Générale de Peinture, 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559 Further information obtainable from: Product Safety Department
 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. 	 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. GHS07 Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation. 	
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour.	 Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. GHS07 Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation. 	SECTION 2: Hazards Identification
Flam. Liq. 2 H225 Highly flammable liquid and vapour.	Flam. Liq. 2 H225 Highly flammable liquid and vapour.	
	GHS07 Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.	GHS02 flame
GHS07	Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.	Flam. Liq. 2 H225 Highly flammable liquid and vapour.
	Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.	GHS07
Acute Tox. 4 H332 Harmful if inhaled.	Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.	Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.	STOT SE 3 H335 May cause respiratory irritation.	Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.		Eye Irrit. 2 H319 Causes serious eye irritation.
	(Contd. on page 2)	STOT SE 3 H335 May cause respiratory irritation. (Contd. on page 2)
(Cond. on page 2)	GB	GB



Page 2/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S11 P.U. THINNER NORMAL

	(Contd. of page 1
2.2 Label ele	
	cording to Regulation (EC) No 1272/2008 is classified and labelled according to the CLP regulation. ograms
	<u>1</u>
GHS02 GH	IS07
Signal word	Danger
Hazard-dete	rmining components of labelling:
methyl isobu	
	tha (petroleum), light arom.
xylene	
Hazard state	ements
H225 Highly	flammable liquid and vapour.
H332 Harmfu	ıl if inhaled.
	s skin irritation.
	s serious eye irritation.
	use respiratory irritation.
	ry statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources No smoking.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P303+P361+	P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse ski with water/shower.
P305+P351+	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contac
D 405	lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national international regulations.
2.3 Other ha	zards
	BT and vPvB assessment
PBT: Not app	
vPvB: Not ap	oplicable.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S11 P.U. THINNER NORMAL

(Contd. of page 2)

Page 3/12

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

CAS: 108-10-1	methyl isobutyl ketone	>25- <i>≤</i> 50%
EINECS: 203-550-1		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	>10- <i>≤</i> 25%
EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56		
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	>10- <i>≤</i> 25%
EINECS: 265-199-0 Reg.nr.: 01-2119455851-35	Acute Tox. 4, H332; STOT SE 3, H335	
05-2116598517-27		
CAS: 1330-20-7	xylene	>10- <i>≤</i> 25%
EINECS: 215-535-7 Reg.nr.: 01-2119486136-34		
05-2116602925-45 01-2119488216-32		
CAS: 763-69-9	ethyl 3-ethoxypropionate	>2.5- <i>≤</i> 10%
EINECS: 212-112-9		

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

(Contd. of page 3)

Page 4/12

Trade name: S11 P.U. THINNER NORMAL

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

(Contd. of page 4)

Page 5/12

Trade name: S11 P.U. THINNER NORMAL

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

	dients with limit values that require monitoring at the workplace:	
108-1	0-1 methyl isobutyl ketone	
WEL	Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sk, BMGV	
108-6	5-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk	
1330	20-7 xylene	
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV	
Ingre	dients with biological limit values:	
108-1	0-1 methyl isobutyl ketone	
BMG	V 20 μmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one	
1330	20-7 xylene	
BMG	V 650 mmol/mol creatinine Medium: urine Sampling time: post shift	

GB



Page 6/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

(Contd. of page 5)

Trade name: S11 P.U. THINNER NORMAL

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Protection of bands:
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- \cdot 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance: Form:

Colour:

Liquid Clear

(Contd. on page 7)

GB



Page 7/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S11 P.U. THINNER NORMAL

	(Contd. of page 6)
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	Undetermined. : 115 °C
· Flash point:	14 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	315 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	10.8 Vol %
 Vapour pressure at 20 °C: 	8 hPa
· Density at 20 °C:	0.852 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
 Solvent content: Organic solvents: VOC (EC) 9.2 Other information 	100.0 % 852.0 g/l No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

GB

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S11 P.U. THINNER NORMAL

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
 No decomposition if used opporting to apositional
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- Harmful if inhaled.

· LD/LC50 values relevant for classification:

Oral LD50 5,800 mg/kg (mouse)

108-10-1 methyl isobutyl ketoneOralLD502,080 mg/kg (rat)

 Dermal
 LD50
 16,000 mg/kg (rab)

 Inhalative
 LC50/4 h
 8.3-16.6 mg/l (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

 Oral
 LD50
 >6,800 mg/kg (rat)

 Dermal
 LD50
 >3,400 mg/kg (rab)

 Inhalative
 LC50/4 h
 >10.2 mg/l (rat)

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat) Dermal LD50 2,000 mg/kg (rabbit)

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 9)



(Contd. of page 7)

Page 8/12

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S11 P.U. THINNER NORMAL

· Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. of page 8)

Page 9/12

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name		
· ADR	1263 PAINT	
· IMDG, IATA	PAINT	

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

HYMA

Revision: 20.09.2019

Page 10/12

Trade name: S11 P.U. THINNER NORMAL

	(Contd. of page
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	11
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F-E, <u>S-E</u>
Stowage Category	B
14.7 Transport in bulk according to Ann Marpol and the IBC Code	nex II of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 n
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 n
UN "Model Regulation":	UN 1263 PAINT, 3, II

(Contd. on page 11)



Page 11/12

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S11 P.U. THINNER NORMAL

(Contd. of page 10)

GB

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eve irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation.

· Department issuing SDS: Product safety department · Contact: N/A · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 (Contd. on page 12)



Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 20.09.2019

Trade name: S11 P.U. THINNER NORMAL

(Contd. of page 11)

GB

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3