



# S241 Genclean

---

**Description:**

Silicone remover is suitable for cleaning and degreasing solvent based products, including thermoplastic acrylic finishes and glass reinforced polyester parts. Suitable for degreasing all Primer surfacers prior to finishing. Silicone remover has a high performance with anti-static properties combined in one product, which makes it suitable for all repairs in the bodyshop.

---

**Surface Preparation:**

Prior to any repair or refinishing, wash down the vehicle to remove all external contaminants (i.e. bird droppings, flies, tree sap, etc)

---

**Raw material:**

Organic solvents.

---

**Cleaning Technique:**

Use before sanding, apply by means of a soaked cloth and remove with a clean dry cloth. (Wipe on wipe off)

Use also before applying primers and topcoats

---

**Important remarks:**

For professional use only,  
Do not allow silicone remover to dry on surfaces.  
Change cloth often.



Wear suitable protection  
Breathing mask  
Use gloves

---

**Flash Point:** 24°C (75.2 °F)

---

**Specific Gravity:** 0.77 kg/cm<sup>3</sup>

---

**VOC (2004/42/EC):** 2004/42/IIB (a) (850)800. The EU limit value for this product (product category IIB.a) in ready to use form is max 850g/ltr. The VOC content of this product in ready for use form is max. 800 g/l.

---

**SDS:** See the safety data sheet