

## Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

### 1 Identification

- **Product identifier**
- **Trade name:** S241 GENCLEAN
- **Article number:** S241
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. SAL  
P.O. Box 7623  
Beirut  
LEBANON  
info@hymax.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**
- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

## Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

**Trade name: S241 GENCLEAN**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07 GHS08

**· Signal word** *Danger***· Hazard-determining components of labeling:***Naphtha (petroleum), hydrotreated heavy**Naphtha (petroleum), hydrodesulfurized heavy***· Hazard statements***Flammable liquid and vapor.**Causes skin irritation.**May cause genetic defects.**May cause cancer.**Causes damage to the central nervous system through prolonged or repeated exposure.**May be fatal if swallowed and enters airways.***· Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Do not breathe dust/fume/gas/mist/vapors/spray.**Wash thoroughly after handling.**Do not eat, drink or smoke when using this product.**Wear protective gloves/protective clothing/eye protection/face protection.**If swallowed: Immediately call a poison center/doctor.**Specific treatment (see on this label).**Do NOT induce vomiting.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF exposed or concerned: Get medical advice/attention.**Get medical advice/attention if you feel unwell.**Take off contaminated clothing and wash it before reuse.**If skin irritation occurs: Get medical advice/attention.**In case of fire: Use for extinction: CO2, powder or water spray.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)

US

## Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

**Trade name: S241 GENCLEAN**

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 1  
Fire = 3  
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = \*1  
Fire = 3  
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

|            |  |           |
|------------|--|-----------|
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy      | >50-≤100% |
| 1330-20-7  | xylene                                       | >10-≤25%  |
| 67-63-0    | propan-2-ol                                  | >2.5-≤10% |
| 123-86-4   | n-butyl acetate                              | >2.5-≤10% |
| 64742-82-1 | Naphtha (petroleum), hydrodesulfurized heavy | >2.5-≤10% |
| 64742-95-6 | Solvent naphtha (petroleum), light arom.     | >2.5-≤10% |

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 4)



# Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

**Trade name: S241 GENCLEAN**

(Contd. of page 3)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

|            |   |                       |
|------------|---|-----------------------|
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | 350 mg/m <sup>3</sup> |
| 1330-20-7  | xylene                                  | 130 ppm               |
| 67-63-0    | propan-2-ol                             | 400 ppm               |
| 123-86-4   | n-butyl acetate                         | 5 ppm                 |

· **PAC-2:**

|            |   |                         |
|------------|---|-------------------------|
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | 1,800 mg/m <sup>3</sup> |
| 1330-20-7  | xylene                                  | 920* ppm                |

(Contd. on page 5)



## Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

Trade name: **S241 GENCLEAN**

|                 |   | (Contd. of page 4)       |
|-----------------|---|--------------------------|
| 67-63-0         | propan-2-ol                             | 2000* ppm                |
| 123-86-4        | n-butyl acetate                         | 200 ppm                  |
| <b>· PAC-3:</b> |   |                          |
| 64742-48-9      | Naphtha (petroleum), hydrotreated heavy | 40,000 mg/m <sup>3</sup> |
| 1330-20-7       | xylene                                  | 2500* ppm                |
| 67-63-0         | propan-2-ol                             | 12000** ppm              |
| 123-86-4        | n-butyl acetate                         | 3000* ppm                |

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

#### 1330-20-7 xylene

|     |  |
|-----|--|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
|-----|--|

(Contd. on page 6)

US



### Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

**Trade name: S241 GENCLEAN**

(Contd. of page 5)

|     |  |
|-----|--|
| REL | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm        |
| TLV | Short-term value: 651 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm<br>BEI |

**67-63-0 propan-2-ol**

|     |  |
|-----|--|
| PEL | Long-term value: 980 mg/m <sup>3</sup> , 400 ppm   |
| REL | Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 980 mg/m <sup>3</sup> , 400 ppm       |
| TLV | Short-term value: 984 mg/m <sup>3</sup> , 400 ppm<br>Long-term value: 492 mg/m <sup>3</sup> , 200 ppm<br>BEI |

**123-86-4 n-butyl acetate**

|     |   |
|-----|---|
| PEL | Long-term value: 710 mg/m <sup>3</sup> , 150 ppm  |
| REL | Short-term value: 950 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 710 mg/m <sup>3</sup> , 150 ppm |
| TLV | Short-term value: 712 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 238 mg/m <sup>3</sup> , 50 ppm  |

**· Ingredients with biological limit values:**

**1330-20-7 xylene**

|     |  |
|-----|--|
| BEI | 1.5 g/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Methylhippuric acids |
|-----|--|

**67-63-0 propan-2-ol**

|     |   |
|-----|---|
| BEI | 40 mg/L<br>Medium: urine<br>Time: end of shift at end of workweek<br>Parameter: Acetone (background, nonspecific) |
|-----|---|

**· Additional information:** The lists that were valid during the creation were used as basis.

**· Exposure controls**

**· Personal protective equipment:**

**· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

(Contd. on page 7)

## Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

**Trade name: S241 GENCLEAN**

(Contd. of page 6)

- **Breathing equipment:**  
*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*

- **Protection of hands:**



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

- **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

- **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

- **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Fluid

**Color:** According to product description

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 82 °C (179.6 °F)

(Contd. on page 8)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

Trade name: S241 GENCLEAN

(Contd. of page 7)

|   |  |
|---|--|
| · <b>Flash point:</b>                             | 24 °C (75.2 °F)  |
| · <b>Flammability (solid, gaseous):</b>           | Not applicable.  |
| · <b>Ignition temperature:</b>                    | 240 °C (464 °F)  |
| · <b>Decomposition temperature:</b>               | Not determined.  |
| · <b>Auto igniting:</b>                           | Product is not selfigniting.   |
| · <b>Danger of explosion:</b>                     | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · <b>Explosion limits:</b>                        |  |
| Lower:  | 0.6 Vol %  |
| Upper:  | 7 Vol %  |
| · <b>Vapor pressure at 20 °C (68 °F):</b>         | 6.7 hPa (5 mm Hg)  |
| · <b>Density at 20 °C (68 °F):</b>                | 0.80735 g/cm <sup>3</sup> (6.73734 lbs/gal)  |
| · <b>Relative density</b>                         | Not determined.  |
| · <b>Vapor density</b>                            | Not determined.  |
| · <b>Evaporation rate</b>                         | Not determined.  |
| · <b>Solubility in / Miscibility with Water:</b>  | Not miscible or difficult to mix.  |
| · <b>Partition coefficient (n-octanol/water):</b> | Not determined.  |
| · <b>Viscosity:</b>                               |  |
| Dynamic:  | Not determined.  |
| Kinematic:  | Not determined.  |
| · <b>Solvent content:</b>                         |  |
| Organic solvents:                                 | 100.0 %  |
| Coating VOC content:                              | 100.00 %   |
| Material VOC content:                             | 807.3 g/l / 6.74 lb/gal  |
| · <b>Other information</b>                        | 807.3 g/l / 6.74 lb/gal<br>No further relevant information available.                      |

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.

(Contd. on page 9)

US





## Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

Trade name: **S241 GENCLEAN**

(Contd. of page 8)

- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

#### 64742-48-9 Naphtha (petroleum), hydrotreated heavy

|        |      |                    |
|--------|------|--------------------|
| Oral   | LD50 | >5,000 mg/kg (rat) |
| Dermal | LD50 | >3,000 mg/kg (rab) |

#### 1330-20-7 xylene

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 4,300 mg/kg (rat)    |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | >6,800 mg/kg (rat) |
| Dermal     | LD50     | >3,400 mg/kg (rab) |
| Inhalative | LC50/4 h | >10.2 mg/l (rat)   |

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

|           |             |   |
|-----------|-------------|---|
| 1330-20-7 | xylene      | 3 |
| 67-63-0   | propan-2-ol | 3 |

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 10)



## Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

**Trade name: S241 GENCLEAN**

(Contd. of page 9)

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |                                  |            |
|----------------------------------|------------|
| · <b>UN-Number</b>               |            |
| · <b>DOT, ADR, IMDG, IATA</b>    | UN1263     |
| · <b>UN proper shipping name</b> |            |
| · <b>DOT</b>                     | Paint      |
| · <b>ADR</b>                     | 1263 PAINT |
| · <b>IMDG, IATA</b>              | PAINT      |

(Contd. on page 11)

## Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

**Trade name: S241 GENCLEAN**

(Contd. of page 10)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids  
· **Label** 3

· **ADR, IMDG, IATA**



· **Class** 3 Flammable liquids  
· **Label** 3

· **Packing group**

· **DOT, ADR, IMDG, IATA** III

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user** Warning: Flammable liquids

· **Danger code (Kemler):** 30

· **EMS Number:** F-E,S-E

· **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 60 L  
On cargo aircraft only: 220 L

· **ADR**

· **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· **IMDG**

· **Limited quantities (LQ)** 5L

(Contd. on page 12)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

**Trade name: S241 GENCLEAN**

(Contd. of page 11)

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, III

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

67-63-0 propan-2-ol

· **TSCA (Toxic Substances Control Act):**

64742-48-9 Naphtha (petroleum), hydrotreated heavy

ACTIVE

1330-20-7 xylene

ACTIVE

67-63-0 propan-2-ol

ACTIVE

123-86-4 n-butyl acetate

ACTIVE

· **Hazardous Air Pollutants**

1330-20-7 xylene

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

(Contd. on page 13)

## Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

**Trade name: S241 GENCLEAN**

(Contd. of page 12)

· **TLV (Threshold Limit Value established by ACGIH)**

|           |             |    |
|-----------|-------------|----|
| 1330-20-7 | xylene      | A4 |
| 67-63-0   | propan-2-ol | A4 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrotreated heavy  
Naphtha (petroleum), hydrodesulfurized heavy

· **Hazard statements**

Flammable liquid and vapor.  
Causes skin irritation.  
May cause genetic defects.  
May cause cancer.  
Causes damage to the central nervous system through prolonged or repeated exposure.  
May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If swallowed: Immediately call a poison center/doctor.  
Specific treatment (see on this label).  
Do NOT induce vomiting.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF exposed or concerned: Get medical advice/attention.

(Contd. on page 14)



## Safety Data Sheet acc. to OSHA HCS

Printing date 07/12/2019

Reviewed on 05/06/2019

**Trade name: S241 GENCLEAN**

(Contd. of page 13)

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• **National regulations:**

• **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

• **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Product safety department

• **Contact:** N/A

• **Date of preparation / last revision** 07/12/2019 / -

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Muta. 1B: Germ cell mutagenicity – Category 1B

(Contd. on page 15)



**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 07/12/2019

Reviewed on 05/06/2019

**Trade name: S241 GENCLEAN**

Carc. 1B: Carcinogenicity – Category 1B  
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. of page 14)

US